AD-A277 133

PELECTE MAR 17 1994

DESTRIBUTION STATEMENT A

Approved for public releases Bearthadon Unicatied PROCESSE AND COMM

94-08502

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF COLOR PAGES WHICH DO NOT REPRODUCE LEGIBLY ON BLACK AND WHITE MICROFICHE.



DEPARTMENT OF THE ARMY WASHINGTON, D.C. 20310



March 1, 1992

To The Reader:

technologically advanced weapons and equipment to our fully trained and well-led soldiers, the Army has deterred war, of continuous modernization has served us well by providing the structure for an overwhelming victory in the Persian Gulf and an equally impressive victory in the Cold War in Europe. Through the development and fielding of As the Army reshapes to a smaller force, a sound, continuous modernization program is essential. The strategy and when necessary, fought and won.

emphasize too strongly the need to continuously modernize our equipment so that our soldiers have a wide advantage over any adversary -- anytime. This requires balanced investment from the technology base to production. Without the proper balance, the acquisition system will deteriorate and cease to put superior technology into the hands of the It is this success of the Army's long-term modernization program that we must preserve and protect. We cannot

This handbook provides an overview of the Army's major weapon systems and support equipment in their various stages of development. It highlights our efforts to maintain a trained, ready and well-equipped Army. In this new era, we must remember that it takes a long time to develop and field superior warfighting capabilities.

Currently, we have the most capable and modern Army in the We hope you will find this information useful. We are working to maintain that decisive edge.

August M. Cianciolo Lieutenant General, GS Military Deputy to the ASA(RDA)

Stephen K. Conver
Assistant Secretary of the Army
(Research, Development and Acquisition)



Prepared by:

OASA(RDA) ATTN: SARD-CC The Pentagon Washington, DC 20310-0103

Ms. Beverly A. Popelka Editor:

For sale by the U.S. Government Printing Office: Superintendent of Documents, Mad Stop, SSOP, Washington, DC, 20402-0438, ISBN 0-16-036138-9

TABLE OF CONTENTS

CLOSE COMBAT

Longbow. 15 Javelin 17 Abrams Tank (M1) 25
Bradley Fighting Vehicle (BFVS) 27 Multiple Purpose Individual Munition (MPIM)......9 Line of Sight Antitank (LOSAT)......13 Stingray Comanche.....11 Armored Gun System (AGS)......21 Overview 120mm Mortar DEVELOPMENT: PRODUCTION: TECH BASE: FIELDED:

AIR DEFENSE

Automatic Grenade Launcher (40mm)(MK193)......41

Personal Defense Weapon (M9 9mm).

Family of Vehicles (FOV)(M113)......29

Kiowa Warrior 33 TOW Weapon System 35 Rifle (M16A2) 37

Apache......31

Avenger 63
Patriot 65
Hawk 67
Chaparral 67
Stinger 71 DEVELOPMENT: PRODUCTION: TECH BASE: FIELDED:

HIS GRAEI

DIC TAB
Unemnounced
Justification

By

Distribution/
Availability voces
Availability woon

FIRE SUPPORT

TECH BASE:	Overview	75
DEVELOPMENT:	Advanced Field Artillery System-Cannon (AFAS-C).	77
	Future Armored Resupply Vehicle-Ammunition (FARV-A)	77
	Brilliant Anit-Armor Technology (BAT)	62
	Sense and Destroy Armor (SADARM)	81
PRODUCTION:	Army Tactical Missile System (Army TACMS)	83
	155mm Self-Propelled Howitzer(Paladin) (M109A6)	85
FIELDED:	105mm Howitzer (M119)	87
	Multiple Launch Rocket System (MLRS)	. œ
	Air-To-Ground Missile Systems (AGMS).	91
COMBAT SUPPORT		
		ŭ
IECH BASE:	CVECVIEW	ი r ი c
	Joint Sulveniance and Talget Auger nadar System (Joint Stans)	, σ ο σ ::
	Ground Based Common Sensors	101
DEVELOPMENT:	Special Operations Aircraft (SOA)	<u>8</u>
	Lightweight Manportable Radio Direction Finding System.	105
	Black Hawk	.107
	High Mobility Multipurpose Wheeled Vehicle (HMMWV)	109
	Smoke and Obscurants	111
	Nuclear, Biological, and Chemical Reconnaisance System (NBCRS)(XM93)	.113
	Mohawk (OV-1D) Surveillance System	115
	Quick Fix	.117
	Guardrail	119
	Armored Combat Earthmover (ACE)(M-9)	.121
	Hecovery Venicle (M88A1)123	.123
COMBAT SERVICE SL	SUPPORT	
TECH BASE:	Overview 127	127
DEVELOPMENT	Tactical Oniet Generators (TOG)	8
PRODUCTION:	Heavy Expanded Transporter System (HETS).	131
	Palletized Load System (PLS)	133
	Family of Medium Tactical Vehicles (FMTV).	135
	Reverse Osmosis Water Puritication Unit (ROWPU)	137
	Integrated Family of Test Equipment (IFTE)	139
FIELDED:	5 Ton Truck	.141
	Heavy Expanded Mobility Tactical Truck (HEMTT)	143
	Deployable Medical Systems (DEPMEDS)	145
	Logistics Support Vessel.	147

COMMAND, CONTROL, AND COMMUNICATIONS

,		151
	DVerview (CCCC)	155
DEVELOPMENT:	Combat Service Support Command Control and Intelligence (FAAD C21)1	.157
•	-olward Area All Deferred Command, Common and Command Common Common Common (MCC)	159
	Maneuver Collico System (MCS)	161
	Army Data Distribution System (ADDS)	163
	Standardized Integrated Command Post System (SICTS)	185
	All Source System Analysis (ASAS)) () (
	Advanced Field Artillery Tactical Data System (AFATUS)	701.
	Single Chancel Ground and Airborne Radio System (SINCGARS)	. 169
FIELDED:	Makile Citating For inchant (MSF)	171
	MODIFIEDUDSCIIDEI Equipinion (MCE////////////////////////////////////	173
	NAVSTAR Global Positioning objectit (of o)	175
	Military Satellite Communications (MILSATOUM)	177
	Communication System Control Element	- 1
	Digital Transmission Assemblades	6/L:
	Circuit Switch and Message Switch	.181
COLDIER SUPPORT		
	weiwaw	. 185
FCH DASE:	Close Combat Tactical Trainer (CCTT)	. 189
DEVELOPMENT:		•
	Table Since Home	161
DEVELOPMEN 1:	Nuclear Biological, and Chemical Defense	193
STRATEGIC CONFLICT		
		197
TECH BASE:	Overview	6
	Extended Range Interceptor Lectinology (Entity)	201
	Airborne Surveillance Testbed (AST)	203
DEVELOPMENT:	High Endoatmospheric Defense Interceptor (nEDI)	205
	Theater High Attitude Area Defense (THAAD)	207
	Ground Based Anti-Satellite (ASA1) System	209
	Ground Based Interceptor (GDI)	211
	Ground Based Surveillance and Tracking System (Gold)	213
	Ground Based Radar (GBH))
SCIENCE/I ECHNOLOGY	Overview	215

This handbook is arranged by functional area. Within each functional area the systems are listed by their stage in the Life Cycle System Management Model. The model that is used for this book is an abbreviated version, discussed below. In the lower right comer of each system description will be a visual representation of where that system is in the life cycle.

	Fielded	
	Production	
	EMD	
Development	DEM/VAL	_
Dev	Tech Base Concept Eval DEM/VAL EMD	_
	Tech Base	

Tech Base:

Efforts focused on the identification and development of promising technologies (not directly tied to specific acquisition programs) are collectively called the technology base. It encompasses programs in basic research, exploratory development, and advanced technology development.

Concept Evaluation:

Alternative system design and support concepts are explored within the context of the mission need and program objectives. Emphasis is on generating innovation and conceptual competition from industry, both foreign and domestic, and U. S. government research, development and engineering centers and laboratories.

Demonstration and Validation:

Focuses on defining critical design characteristics, addressing manufacturing technological deficiencies, and assessing production feasibility. Analysis, simulation models, or prototypes are used to optimize design and resolve problems.

Engineering and Manufacturing Development (EMD):

The purpose of EMD is to design, fabricate, test, and evaluate a complete system. This includes the principal items necessary for its production, operation, and support, and serves to validate the production process. Reliability and Maintenance design, testing, and evaluation of components should be integrated into the earliest part of this phase.

Production:

After successful completion of technical and user tests, production begins at rates based on manufacturing efficiency, operational demand, and resource availability.

Fielded:

During this phase, the materiel system is operated, supported, and maintained in accordance with its intended operational concept, and opportunities are explored for continued improvement in cost, performance, and reliability based on actual experience. The system is sustained in

CLOSE COMBAT

and indicates, close combat involves two adversaries standing eyeball to eyeball, with man pitted against man, weapon against weapon. This mission area The Close Combat mission area relates to the fighting vehicle application of direct combat power. As the term weapons, nseq are includes such items as tanks, systems, direct line-of-sight mortars that short-range infantryman.

Tech Base	Concept Development	DEVELOPMENT DEM/VAL	EMD	Production	Fielded
Component Advanced		Comanche	Longbow	120 mm Mortar	Abrams Tank
recinology rest bed		LOSAT	Javelin		Bradley
Associate			Stingray		Family of Vehicles
Advance Pilot's Aid			Armored Gun System		Apache
Multi-Sensor Aided Targeting					Kiowa Warrior
Armor/Anti-Armor					TOW Weapon
Combat Vehicle					Rifle M16A2
Command and Control					Personal Defense Weapon
Composite Armored Vehicle					Automatic Grenade
Electric Guns					Launcher
Enhanced Kinetic					Squad Automatic Weapon
Mulitple Purpose					120mmTank Main Gun Ammunition
Individual Munition					Night Vision and Electro-Optics



MULTI-SENSOR AIDED TARGETING - AIR



COMPONENT ADVANCED TECHNOLOGY TEST BED



ROTORCARAFT PILOT'S ASSOCIATE



ADVANCED PILOT'S AID

CLOSE COMBAT - TECH BASE

OVERVIEW:

COMPONENT ADVANCED TECHNOLOGY TEST BED:

ROTORCRAFT PILOT'S ASSOCIATE (RPA):

ADVANCED PILOT'S AID (APA):

MULTI-SENSOR AIDED TARGETING (MSAT) - AIR:

demonstrations described below (also see list of Advanced Technology Transition Demonstrations) are The goal of the Army Technology Base program in Close Combat is to provide the technology for both for upgrades to fielded systems and for next generation systems. Lessons learned from operations such as Desert Storm have led the Army to focus on both evolutionary and revolutionary technologies that focused on advanced technologies to provide increased lethality, survivability, mobility and sustainability, overmatching air and land systems to give our soldiers the winning edge on the battlefield. can improve force projectability and provide a decisive advantage in future operations.

and technologies for combat vehicles. It includes a compact propulsion system that consumes half the fuel of the current tank system; an external suspension system that frees space now occupied by torsion bars; more durable, lighter track; and a modular electronics architecture for power and data distribution. These This demonstration uses a modified Abrams chassis to demonstrate tire integrated, advanced components technologies enable upgrades to fielded systems and more capable, next generation systems.

maximum rotorcraft crew and system performance through a "system of systems" to enhance the pilot's The RPA demonstration will integrate and demonstrate mission equipment package technologies for ability to see the battlefield in day, night and adverse weather. It aslo allows the crew to rapidly handle threat and obstacle information, and take immediate and effective actions.

improved human factors. The results of this demonstration will be used on current and future scout, utility and cargo aircraft. The APA demonstration will exploit technology advances in image intensification, optics materials, and design and human factors research to enhance aviator's effectiveness and reduce pilot workload. The goal is to provide all aviators with increased visual acuity and field of view, integrated flight symbology, and


MSAT will demonstrate aided target recognition sensor fusion and supporting algorithm technology that will reduce the time to detect and recognize targets by more than half. MSAT will process target features lasers, signal processing, and artificial intelligence are some of the technologies being used. Lethality and Millimeter wave radar, second generation forward-looking infrared, obtained from multi-spectral sensors. survivability will be greatly enhanced.





ARMOR / ANTI - ARMOR

ELECTRIC GUN LETHALITY / PROTECTION RENEFITS




ELECTRIC GUN




COMPOSITE ARMORED VEHICLE

- · Electronic map ("birdseye" view of battlefield)
- · Burst transmission of preformatted messages
- Improved decision time



Battlefield opaque to enemy . . Transparent to us

COMBAT VEHICLE COMMAND AND CONTROL



9

CLOSE COMBAT - TECH BASE (CON'T)

ARMOR/ANTI-ARMOR (A3):

COMBAT VEHICLE COMMAND AND CONTROL (CVC2):

COMPOSITE ARMORED VEHICLE (CAV):

ELECTRIC GUNS:

ENHANCED KINETIC ENERGY WEAPON (X-ROD):


This joint program among the Army, Defense Advanced Res arch Projects Agency and the Marine Corps was established in 1985 with a goal of enhancing the A3 technology base within the United States and establishing a competitive modernization rate for the long term. Key activities include armors for all classes of vehicles, warheads, penetrators, related materials research and advanced computer modeling of the effect of penetrators on armor. Technology transfer opportunities include gun and missile systems, the current fleet of armored vehicles and next generation combat vehicles.

vehicle displays will provide map information, enemy and friendly locations and graphic overlays which will show a "bird's eye" view of the battlefield. In addition, CVC2 provides easy preparation and transmittal of standard reports. Collectively, these features will enable synchronization of combat power and reduce The CVC2 concept will provide real-time, data linked tactical information, at battalion level and below. Inpotential for fratricide.

and ceramics, and integrated signature reduction techniques to lighten combat vehicles, thereby making them more deployable while maintaining high levels of survivability. Issues include ballistic and structural integrity, producibility and repairability. Spin-off benefits include lightening current and future medium-to-heavy classes of vehicles and creation of new, light weight systems that are more capable than is possible The primary goal of this ATTD is demonstration of composite structures, such as fiber reinforced plastics with today's technology

as other potential applications, such as air and missile defense. Electrothermal guns use pulses of electrical energy to initiate and control chemical reactions and electromagnetic guns use intense magnetic fields to accelerate projectiles. Electrothermal and electromagnetic gun technologies, along with power The Electric Armament Program will demonstrate two types of prototype electric guns for anti-armor, as well supplies and projectiles, can provide significant increases in muzzle energy over conventional systems. extend engagement ranges, reduce projectile time of flight, and increase hit and kill probabilities.

extended ranges. Superior hit probability is expected by using one of two competing concepts, command guided or fire-and-forget guidance. This technology has applications for fielded main tank armaments or a X-ROD is an advanced, tank-fired, guided kinetic energy projectile system capable of defeating targets at future main battle tank.



MULTIPURPOSE INDIVIDUAL MUNITION (MPIM)

MISSION:

The MPIM is an individual soldier weapon that will augment the M72 series and AT4. Light Antiarmor Weapons currently in inventory. The weapon will have the ability to defeat armored personnel carriers and incapacitate enemy personnel entrenched behind masonry structures and inside bunkers.

CHARACTERISTICS:

The MPIM is a shoulder-fired weapon:

Length: < 32 inches Weight: 12-15 lbs

ability to fire from enclosures disposable round

FOREIGN COUNTERPART:

None. No single weapon exists that can satisy the wide range of requirements in one system.

PROGRAM STATUS:

The MPIM has transitioned from Proof-of-Principle (POP) to Technology Base. Technical problems with a warhead that would defeat all targets and a propulsion system that could be fired safely from enclosures with a 12 pound weight limit precluded entry into EMD. The MPIM is in the Anti-Armor Master Plan and the Army Armor/Anti-Armor Modernization Plan.

POINT OF CONTACT:


 U. S. Army Research, Development, and Engineering Center AMSMI-RD-AC-CC Project Officer - MPIM

Redstone Arsenal, AL 35898-5242

(205) 842-8769 or DSN 788-8769

CONTRACTORS:

To be determined.







COMANCHE HELICOPTER

MISSION:

improved with the Comanche. Its 1260 nautical miles self-deployment range and smaller size will improve Army aviation's rapid strategic deployment. One helicopter, the Comanche will be able to perform the missions currently being performed by three types of helicopters (AH-1, OH-58 and OH-6) better with greater Army's capability to conduct tactical operations in all types of terrain, adverse weather and battlefield environments, during day/night operations with increased survivability. The Comanche with its increased close and deep operations with improved lethality and survivability. The force agility will be significantly attack helicopters. This aircraft in the Army's air cavalry and attack organizations will significantly expand the speed, survivability, air-to-air capability and mission equipment will enhance the combat operation of supported forces. The Comanche supports forward deployed and contingency forces by conducting both he Comanche (RAH-66) is the Army's next generation rotorcraft which will replace the aging scouts and AH-1 operational and support efficiency.

CHARACTERISTICS:

7,500 lbs (target empty weight at production) 170 knots (cruise)

2.5 hours (+5 hour reserve)
2 pilots (single pilot operable)

Air-to-ground and air-to-air missiles
Provisions for additional stores and a turret mounted
cannon, night vision pilotage system, helmet
mounted display, electro-optical target acquisition
and designation system, aided target recognition,
and integrated displays. Each aircraft will have

Mission Equipment Package:

Speed: Endurance: Crew: Armaments: ongbow capability.

FOREIGN COUNTERPART:

Current Soviet-developed HIND series helicopters and developmental HOKUM and HOAVOC series helicopters present the air-to-air threat.

PROGRAM STATUS:

As a result of the decision to indefinitely delay production of the Comanche, the Dem/Val Phase will be extended by two years (Aug 95 - Aug 97). The Longbow integration effort and T800 development will continue. The Program Manager has decided to uprate the T800 engine by approximately 12% to better support recently validated user requirements.

POINT OF CONTACT:

PM-Comanche 4300 Goodfellow Boulevard ATTN: SFAAE-AV-RAH (Bldg 6105) St. Louis, M.O. 63120-1795

CONTRACTORS:

Boeing/Sikorsky (Stratford, CT) Garrett/Allision (LHTEC) (Indianapolis, IN) tech hase Corcose DEM/VAL and Production Resided



LINE-OF-SIGHT ANTITANK (LOSAT)

The Line-of-Sight Antitank (LOSAT), in the dedicated antitank companies of the Mechanized Infantry Battalions, will provide organic antitank fire to fix and destroy enemy armored formations. This fixing fire will provide tanks and infantry the freedom to rapidly maneuver into the enemy's vulnerable flanks and rear. The LOSAT weapon system consists of a Kinetic Energy Missile (KEM) mounted on a stretched Bradley Fighting Vehicle System (BFVS) chassis. LOSAT will replace the Improved TOW Vehicle (ITV). The key attraction of LOSAT will also provide the increased mobility, survivability and fleet commonality of the BFVS over the aging ITV. LOSAT will operate out to the maximum range of direct fire combat engagements and will provide dramatically increased rates of fire and enhanced performance under day/night, adverse weather, and the LOSAT is the tremendous overmatch lethality of the KEM (defeats all predicted future armored vehicles) obscured battlefield conditions.

CHARACTERISTICS:

KEM 170 lbs 112 in 6.4 in Greater than TOW 3 Length: Weight:

Diameter: Range:

Crew:

There are no known foreign antitank missile systems in production or advanced development that operate in the velocity regime of LOSAT or which utilize kinetic energy as the kill mechanism.

FOREIGN COUNTERPART:

The LOSAT program is completing the Demonstration and Validation phase of development and will seek a

Milestone II decision to enter Engineering and Manufacturing Development in the 1st quarter of FY93. LOSAT is building upon the earlier Joint Service Hypervelocity Missile Demonstration (approved in August 1988). Under the current acquisition strategy, the First Unit Equipped date will occur in the 4th quarter of FY99.

POINT OF CONTACT:


CONTRACTORS:

PROGRAM STATUS:

ATTN: SFAE-ASM-LS

Redstone Arsenal, AL 35898

LTV Aerospace and Defense (Dallas, TX) - Prime Texas Instruments (Dallas, TX) - Sub FMC Corporation (San Jose, CA) - Sub Development DEM/VAL Tech Bose



DoD Standard Computer and Enhanced Fau Programming Language Data Transfer

Enhanced Fault Detection Location System Data Transfer/Recording

LONGBOW

1

MISSION:

or night in adverse weather and with battlefield obscurants. The Longbow system is being developed for integration into the Apache attack helicopter and the Comanche armed reconnaissance helicopter. Longbow consists of a mast mounted millimeter wave Fire Control Radar (FCR), a Radio Frequency Interferometer (RFI), and a radio frequency fire and forget Hellfire Missile. The FCR detects ground or air targets, and the RFI identifies active emitters. The central processor then classifies the targets, establishes priority for Longbow is a development and acquisition program for an air/ground targeting radar capable of being used day engagement and passes target information to the missile seeker. The pilot may then engage the targets with significantly reduced decision and exposure times. Longbow is being planned for integration into eleven pure Longbow Apache Battalions in Force Package I, and into one third of the Comanche fleet

CHARACTERISTICS:

Apache consists of the AH-64 aircraft modified with changes necessary to effectively and efficiently integrate the Longbow radar and missile. Changes are additional power, expanded avionics bays, additional cooling, upgraded processors, integrated avionics, and a MANPRINT crewstation. The Longbow Fire Control Radar antenna and RFI are housed in a mast mounted assembly above the helicopter rotor system. The processors for the radar are located in the aircraft's avionics bays. The Longbow

FOREIGN COUNTERPART:

There are presently no known comparable heliborne radar systems.

PROGRAM STATUS:


The Longbow Apache System entered Full Scale Development in December 1990 following an extremely successful Proof of Principle (POP) Phase. Technical success during POP culminated with the live firing of one missile missed its target due to a failed missile gyro, not related to the Longbow seeker. The current program objective calls for 227 Longbow Apache aircraft with first flight of the integrated radar commencing in nine missiles against a wide variety of targets, moving and stationary, through smoke and obscurants. Only August of 1993. The Longbow Apache will add significant warfighting capability to the Apache fleet in survivability, lethality, and versatility, as well as long term reliability improvements.

POINT OF CONTACT:

PM Longbow Attn: SFAE-AV-LB 4300 Goodfellow Bhd. St. Louis, Missouri 63120

CONTRACTORS:

McDonnell Douglas Helicopter Company (Mesa, AZ.) Martin Marietta (Orlando, FL.) Westinghouse (Baltimore, MD)







JAVELIN

MISSION:

CHARACTERISTICS

lethality against conventional and reactive armor and will replace the Dragon. The Javelin is comprised of two major components: a reusable Command and Launch Unit (CLU) and a missile sealed in a disposable launcher container. The CLU incorporates an integrated day/night sight and provides target engagement capability in adverse weather. The CLU may be used in stand-alone mode for battlefield surveillance and target detection. The Javelin is a man-portable anti-tank system for the U.S. Army and U.S. Marines. The system provides high

Dismounted infantry and U. S. Marines are the primary users. The key feature of the Javelin is the utilization of fire-and-forget technology. This technology allows the gunner to fire and immediately take cover. Additional special features are the top attack or direct fire mode (for targets under cover), integrated day/night The Javelin system will weigh less than 49.5 pounds and will have a maximum range of 2000 meters. sight, dual warhead, imaging infrared seeker, target lock-on, and soft launch. Javelin can also be safely fired from enclosures and covered fighting positions.

No other fire and forget systems exist. Similar systems are the Soviet-developd AT-7, Swedish Bofors Bill, and the French MILAN 2.

FOREIGN COUNTERPART:

STATUS

PROGRAM

The Javelin program is beginning the third year of Engineering and Manufacturing Development. There have been five successful guided flight tests thus far. Production deliveries are expected to begin in Jul 95 and extend into the year 2006.

Project Manager ATTN: SFAE-FS-AM

POINT OF CONTACT:

CONTRACTORS

Redstone Arsenal, AL 35898-5650

Texas Instruments/Martin Marietta JAVELIN Joint Venture (Denton, TX) exas Instruments Martin Marietta ARC Seeker Focal Plane Array SubContractors: Propulsion Unit Prime System Prime System

Warhead Main Charge Electronic Safe Arm & Fire Control Actuation System Launch Tube Assembly

National Waterlift

Physics Intl

Magnavox


Kalamazoo, MI Ft. Wayne, IN Oakland, CA Irvine, CA

Santa Barbara, CA Gainesville, VA

Denton, TX Orlando, FL

Development EXE Concept Evol | DEM./

17





STINGRAY FIELD OF GUARD

STINGRAY

MISSION:

against Optical and Electro-Optical (OEO) equipped threats by disrupting threat fire control systems long enough for the user to engage the hostile system by fire or to take other appropriate action. Stingray will detect, track, and countermeasure (CM) systems by neutralizing the Target Acquisition System on the threat forces' tanks, combat vehicles, and other ground and airborne systems beyond the threat's effective ranges. Stingray will be employed to disrupt surveillance by countermeasuring OEO devices servicing threat combat Stingray is a protection system which increases the survivability of the host vehicle and adjacent forces vehicles and weapon systems. This CM capability acts as a force multiplier against numerically superior threat armored and mechanized forces. The system consists of four basic components: (1) sensor assembly with optics, stabilization, and high resolution detector; (2) laser transmitter; (3) commander's controls and display; and (4) system electronics which contain signal processing, built-in test, host vehicle interface and target handoff. The system operates in 3 modes - Automatic, Semi-Automatic (man-in-the-loop), and Manual; provides target acquisition and rangefinding capability; and operates both stationary and on the move, detecting stationary and moving

It is believed that Soviets had developed significant numbers of similar type weapons. With the break-up of the Soviet Union, other nations may try to obtain some of these systems. China also has an R&D program.

FOREIGN COUNTERPART:

PROGRAM STATUS:

CHARACTERISTICS:

months. A second system was assembled for Deser Storm and both were deployed to support ground operations. The program was approved for entry into ingineering and Manufacturing Development at the Milestone II ASARC. Subsequent decisions may cirect the program to continue as a research and development effort that will produce "fieldable" prototypes for evaluation, doctrinal development, and Stingray has been in advanced development since 1982. One system was built and tested for over 36 contingencies. Final decision is pending.

Two systems deployed; 100% oc rational. Not used in combat due to short duration of ground combat.


PM Stingray Attn: SFAE-IEW-EW

PERFORMANCE IN SWA:

POINT OF CONTACT:

Evans Area Ft. Monmouth, N.J. 07703-5000 Martin Marietta Corporation (Orlando, FL)

CONTRACTORS:



ARMORED GUN SYSTEM (AGS)

MISSION:

The Armored Gun System (AGS) is the lightweight strategically and tactically deployable weapon system which will replace the M551A1 Sheridan. The AGS will provide direct fire support to the 82nd ABN DIV, Light Infantry Contingency Forces and other light armor operational requirements. The vehicle will be capable of being committed to areas where timely deployment of the main battle tank may not be feasible or practical. The AGS will be deployable by Low Velocity Air Drop (LVAD) from United States Air Force (USAF) tactical transport aircraft (C-17 required and C-130 desired) and will provide C-130/C-141 Roll-On/Roll-Off (RO/RO) capability.

CHARACTERISTICS:

Weight:

Range: Speed:

Mobility

RO/RO < 44,000 lbs LVAD (C-17) < 49,500 lbs

160 km (LVAD configuration) 480 km (combat loaded) > M551A1 Sheridan

64 kph hard surface roads 40 kph secondary roads

Maingun 105mm/30rds 3 - 4

Çø≹

FOREIGN COUNTERPART:

STATUS:

PROGRAM

Ordnance:

The Soviet-developed counterpart is the ASU-85, which is a versatile air-transportable and air-droppable weapon system principally employed in an antitank role, but is capable of providing general direct fire support.

Contract award for Engineering and Manufacturing Development (EMD) of the AGS is planned for May, 1992. Delivery of prototype vehicles for Technical Test/Early User Test and Evaluation is expected within two years

of contract award.

PM, Armored Gun System ATTN: SFAE - ASM - AG Warren, Mt 48397-5000


CONTRACTORS:

POINT OF CONTACT:

To be determined.

Development EMD Concept Ives DEMA





120mm MORTAR

MISSION:

The 120mm mortar system will provide improved organic indirect fire support capability to the maneuver unit commander. The 120mm mortar was acquired as a nondevelopmental system from Israel. It is a conventional smoothbore, muzzle-loaded mortar system which provides increased range and lethality over the 4.2-inch heavy mortar system. It will be employed in both towed and carrier-mounted versions. The 120mm mortar will fire a family of enhanced ammunition being produced in the U.S. It will replace the WWII vintage 4.2-inch heavy mortars in the mechanized infantry, motorized, armored and cavalry units.

CHARACTERISTICS:

4 rounds per minute, sustained 319 pounds (ground-mounted) 7.240 meters Weight: Rate of Fire:

Ammunition: Q ₩.:

5 (ground-mounted) HE, Smoke, Illumination

FOREIGN COUNTERPART:

The 120mm smoothbore mortar is used by France, Germany, Denmark and other allied armies. The Soviet-developed counterpart is the M43 120mm mortar which has a range of 5,700 meters, weighs 602 pounds and has a 6 man crew

PROGRAM STATUS:

towed system, M120, was fielded in September 1991 to the 199th Infantry Brigade, Ft Lewis, Washington. The The 120mm mortar is currently in low-rate production at Watervliet Arsenal, New York. The 120mm mortar Army plans to field a total of 1725 systems to replace all the 4.2-inch mortars currently in the inventory. The 120mm mortar enhanced ammunition is currently being produced by Martin Marietta Ordnance System, Orlando, Florida. The Army has type classified the M933/934 HE and M930 Illumination rounds for production in 1991. The XM929, Smoke round is scheduled for type classification in early April 1992. M121 carrier mounted version will be fielded to all remaining heavy maneuver units beginning in 4QFY93.


POINT OF CONTACT:

U.S. Armament, Munitions And Chemical Command ATTN: AMCPM-MO Picatinny Arsenal, NJ 07806-5000

CONTRACTORS:

Watervliet Arsenal, NY

Ammunition: Martin Marietta Ordnance Systems (Milan, TN): Scranton AAP, PA; Radford AAP, VA; Brockway Standard Inc., GA; United Ammunition Container Corp. TN; Polymer Technologies, Inc. NJ; ARMTEC Defence Products, Inc., CA; Loral Corp., PA





ABRAMS TANK

MISSION:

The mission of the Abrams tank is to close with and destroy enemy forces on the integrated battlefield using mobility, firepower and shock effect. The 105mm main gun on the M1 and IPM1 and the 120mm main gun on development program builds on the M1A1 to provide an Abrams tank with the necessary improvements in lethality, survivability, and fightability required to defeat the threat of the mid nineties. Improvements being developed for the M1A2 include a Commander's Independent Thermal Viewer, an Independent Commander's Weapon Station, Position Navigation equipment, and a distributed data and power architecture. suitable for attacking or defending against large concentrations of heavy armor forces on a highly lethal battlefield. Additional features of the M1A1 are increased armor protection, suspension improvements and an the M1A1 combined with the powerful 1500 HP turbine engine and special armor make the Abrams particularly NBC protection system which provides additional survivability in a contaminated environment. The M1A2

MIAS	32.25 #	12.52 1	# 0 es	41.5 mph	68.9 tons	120mm	•
M1A1	32.25 #	12.0 ft	8.0 #	41.5 mph	67 tons	120mm	7
M1/IPM1	32.04 ft	120ft	7.79 ft	45.0 mph	60 tons	105mm	4
	Length:	Width:	Height:	Top Speed.	Weight:	Armament:	Crew.

CHARACTERISTICS:

There are numerous main battle tanks throughout the world such as the British Challenger, the German Leopard, the French LeClerc and the Soviet-developed T-64, T-72 and T-80 which are in the same class as the Abrams series tanks.

FOREIGN COUNTERPART:

PROGRAM STATUS:

The Abrams tank is in its eleventh year of production. Over 7,000 tanks are in the field as of the beginning of 1992. By the end of FY 92 all active component armor units will be equipped with the M1A1 or M1. Reserve Component Roundout units are also receiving the Abrams tank. The M1A2 has begun Technical and Operational testing and is expected to enter low rate production in 1992.

The Abrams received outstanding comments on its lethality, mobility and reliability. The Abrams was employed in fast paced, complex, offensive and defensive, day and night operations. The Abrams vastly overmatched Iraqi systems' lethality, mobility, survivability, target acquisition and fire control. The Abrams Operational Readiness (OR) rate exceeded 90% in all units throughout the conflict.

PERFORMANCE IN SWA:

PM-Abrams Tank System, SFAE-ASM-AB Warren, MI 48397-5000.

POINT OF CONTACT:

CONTRACTORS:

General Dynamics Land Systems Div. (Sterling Hts, MI)

Fielded 1 Concept Bres | DBA/VAL





BRADLEY FIGHTING VEHICLE SYSTEM (BFVS)

MISSION:

The BFVS is a lightly armored, full-track fightling vehicle which provides cross-country mobility, mounted firepower, and protection from artillery and small-arms fire to mounted infantry and cavalry combat operations and support to dismounted combat operations.

CHARACTERISTICS:

3 600 Hp 300 Mi Power Train: 60,000 lbs (M2/M3A2 W/OArmor Tiles) 21.5 ft.

9.75 ft. 10.5 ft Length: Height: Width:

Range: Road Speed: Swim Speed:

25mm Cannon TOW, 7.62 Coaxial MG Main Armament:

Secondary Armament:

COUNTERPART: FOREIGN

The BMP is the Soviet-developed infantry fighting vehicle and mounts a 73mm smoothbore cannon, an AT3, AT5, or AT6 antitank guided missile and permits the infantry squad to fire from the inside. The BMP-2 is another variant with a 30mm gun, which fires the AT4 or AT5 and is also being fielded.

PROGRAM STATUS:

At the end of the latest contract with FMC in FY94, the Army will have produced a total of 6724 Bradleys, 4641 in the M2 or Infantry configuration and 2083 in the M3 or Cavalry configuration. Both the M2 and M3 were produced in three versions: the Army initially purchased 2300 basic or AO Bradleys; then 1371 vehicles in the A1 configuration which incorporates the TOW 2 Subsystem; and currently 3053 vehicles in the A2 High Survivability configuration. The Army is also in the process of converting all A1's to the A2 configuration at Mainz and Red River Army Depots.

PERFORMANCE IN SWA:

The BFVS exceeded expectations in lethality, mobility and operational readiness. The 25mm cannon and TOW Subsystem proved to be exceptionally lethal against Iraqi armor.

> CONTACT: POINT OF

Program Manager, Bradley Fighting Vehicle System ATTN: SFAE-ASM-BV

Warren, MI 48397-5000

CONTRACTORS

General Electric Corp (Pittsfield, MA) Cummins (Columbus, IN) FMC Corp, (San Jose, CA)

Alliant Tec Systems (Minneapolis, MN) General Electric Corp. (Burlington, MA) Pentastar (Huntsville, AL) McDonnell Douglas (Mesa, AZ) Hughes Aircraft Corp. (LaGrange, GA) Fielded 8 DEMOVAL Concept Byol

M113 FAMILY OF VEHICLES (FOV)

MISSION:

The M113 FOV has been in continuous production since 1960 with over 85,000 vehicles, consisting of 35 different variants, in use by over 44 countries. The Army's fleet of 32,000 vehicles are used for a variety of missions to include transport of infantry and engineer units, medical evacuation, fire support and Command and Control functions on the battlefield.

CHARACTERISTICS:

2 275 hp Crew: Power Train: 27,180 lbs (M113A3) 17.1 ft Length:

Range: Road Speed: Swim Speed:

300 mi 42 mph

> 8.8 ft .50 Cal machine gun Main Armament:

Height: Width:

COUNTERPART: FOREIGN

PROGRAM STATUS:

The Soviet-developed wheeled BTR-60, BTR-70, and new BTR-80 series amphibious armored personnel carriers are roughly equivalent in function to the M113. The MTLB amphibious, multipurpose, tracked carrier is used to carry infantry and as a prime mover for towed artillery and antitank guns.

Deliveries of the M113A3 began in FY86 and are scheduled for completion in FY92. The A3 configuration adds spall suppression liners, armored external fuel tanks and upgraded engine and transmission to accommodate the added weight of bolt on armor. Depot conversion programs are ongoing in CONUS and OCONUS to modify

lielded M113A2's to the M113A3 configuration.

Commanders and crews were impressed with the performance of the M113A3. The system's mobility and speed were impressive. PERFORMANCE IN SWA:

Program Manager, AMCPM-M113/M60 FOV US Army Tank and Automotive Command Warren, MI 48379-5000

CONTACT:

P

POINT

FMC Corp (San Jose, CA) GMC, Detroit Diesel Allison (Detroit, MI)

CONTRACTORS:

Fielded 1 DEM/NAL Yech Bose





APACHE

MISSION:

Acquisition Designation Sight and Pilot Night Vision Sensor (TADS/PNVS) which permit its two-man crew to navigate and attack in darkness and in adverse weather conditions. The principal mission of the Apache is the destruction of enemy armor with the Hellfire missile. It is also capable of employing a 30mm M230 chain gun and Hydra 70 (2.75 inch) rockets that are lethal against a wide variety of targets. The Apache has a full range system. Terrain limitations and the unknown placement of numerically superior enemy armor dictate the need for a system that can deploy quickly to the heaviest enemy penetration and destroy, disrupt, or delay the attack long enough for friendly ground maneuver units to reach the scene. The Apache is designed to fight and survive at day, night, and in adverse weather throughout the world. It is equipped with a Target The AH-64 Apache is the Army's primary attack helicopter. It is a quick-reacting, airborne antitank weapon of aircraft survivability equipment and has the ability to withstand hits from rounds up to 23mm in critical areas

CHARACTERISTICS:

14,770 lbs 145 knots Mission Gross Weight:

Cruise Speed

Armament:

FOREIGN COUNTERPART:

Hellfire Missiles, Hydra 70 rockets and 30mm M230 chain gun

are also developing the HOKUM attack helicopter. The HOKUM will probably be used as an air-to-air system against other helicopters. The Italian A-129 Mangusta is the nearest NATO counterpart to the Apache. The Germans and French are co-developing the PAH-2 Tiger attack helicopter which has many of the capabilities of the Apache. The Soviet-developed HIND is the Apache's closest counterpart. The Soviets have deployed significant numbers of HINDs in Europe and have exported the HIND to many third world countries. They will deploy the new HAVOC soon. The HAVOC closely resembles the Apache and is expected to be employed similarly. They

PROGRAM STATUS:

Apache production began in FY82 and the first unit deployed in FY86. As of December 1991, 705 Apaches were delivered to the Army. The last Army Apache delivery is scheduled for February 1995. Twenty-five attack battalions are deployed and ready for combat. The Army is procuring a total of 811 Apaches to support a force structure of 40 battalions (26 Active; 2 Reserve; 12 National Guard). The Apache has been sold to Israel, Egypt, Saudi Arabia, the UAE, and Greece.

SWA: PERFORMANCE IN

Apaches fired the first shots of the Gulf war. The Apache performed admirably during day, night and adverse weather against both moving and stationary targets, while maintaining high availability rates in an extremely harsh environment.

POINT OF CONTACT:

PM Advanced Attack Helicopter 4300 Goodf allow Boulevard St. Louis, P.O. 63120

CONTRACTORS:

General Electric (Lynn, MA) McDonnell Douglas Helicopter Company (Mesa, AZ) Martin Marietta (Orlando, FL) Fielded į DEMOVAL Concept Bros





KIOWA WARRIOR

MISSION:

Low-light Television, and a Laser Rangefinder/Designator. A highly accurate navigation system permits precise target designation that can be handed off to other engagement systems via the Airborne Target Handover System. The Laser Designator can provide designation for other laser guided precision weapons. Air-to-Air Stinger (ATAS) provides security against threat aircraft. The armed retrofit program began in FY 91 and provides Air-to-Ground weapons and other reconnaissance aircraft in the inventory until RAH - 66 fieldings in FY 99. The OH-58D supports Army AirLand Battle with reconnaissance, security, command and control, target acquisition/designation and Defensive Air Combat. The armed OH-58D The armed version is currently the only practical armed adds armed reconnaissance, light attack and Multipurpose Light Helicopter (MPLH = rapid deployment, troop lift, cargo and Medivac) to the aircraft's mission capabilities. The OH-58D has a Mast Mounted Sight that houses a Thermal Imaging System, OH-58D Kiowa Warrior is the Army's first true scout helicopter. mprovements to previously produced OH-58Ds.

CHARACTERISTICS:

Max Gross Weight:

5,500 lbs. 118 kts - Clean: 113 kTA

Max Speed: 1181 Armament: ATA

118 kts - Clean; 113 KTAS - Armed ATAS, .50 cal. Machine Gun, 2.75" Hydra 70 rockets (7 shot pod), Hellfire missiles

choices; 1 system per side

Crew:

Germany - BO - 105; France - Gazelle, Alloutte; numerous Soviet-developed helicopters (HINDs, HIPs, Hopites)

PROGRAM STATUS: Kiow

COUNTERPART:

Kiowa Warrior is in the eighth year of production. There have been 222 aircraft accepted through November, 1991. Aircraft deployments include the training bases at Fort Rucker and Fort Eustis, and two operational units in CONUS, USAREUR, and Korea. The Proculement Objective is currently 291, with 255 for the active components and 36 for the National Guard Bureau. Deliveries will end in June 1993. Armed retrofit is scheduled to complete in FY 96.

PERFORMANCE IN

Armed OH-58Ds (Prime Chance) operating from Navy vessels liberated the first Kuwaiti territory (Qurah Island) during the Gulf War. Additional armed OH-58D successes were the damage/destruction of numerous Iraqi watercraft, air defense and anti-ship providing ground maneuver forces critical "real time" intelligence in their rout of the Republican Guards. Additional unarmed missions included Laser designation for precision munitions (HELLFIRE, Copperhead, and USAF laser guided munitions). Cavalry missions (screens, reconnaissance, etc.), and forward observation for field artillery adjustment. missile sites (oil platforms). Unarmed OH-58Ds led the Second Armored Cavalry Regiment's (VII Corps) main effort into Iraq.

POINT OF CONTACT:

PM Kiowa Warrior 4300 Goodfellow BLVD ATTN: (SFAE-AV-ASH-T) ST. Louis, MO. 63120-1798

CONTRACTORS: Bell Helicopter

Bell Helicopter Textron, Inc. (Ft. Worth, TX) McDonne Allison Gas Turbine Division (GM) (Indianapolis, IN) Northrop (Litton Laser Systems (Orlando, FL)

McDonnell Douglas Electronics Systems (Monrovia, CA) Northrop Corp (Anaheim, CA) Horlaywell, Inc. (Defense Avionic Sys Div (Albuquerque, NM) Tech lase Concept find DEM/VAL RND Product





TOW WEAPON SYSTEM

• •
z
0
_
S
S
_
•
~

It is found at battalion level and is mounted on the Bradley Fighting Vehicle System (BFVS), the Improved TOW Vehicle (ITV), the High Mobility Multipurpose Wheeled Vehicle (HMMWV), and the AH-1S Cobra Helicopter. The system consists of a tripod, traversing unit, missile guidance set, launch tube, optical sight, and battery assembly and any of the five missile variations. The system also includes a thermal sight which provides a capability for operations at night, in reduced visibility and in a countermeasure environment. The missiles are The TOW (Tube-Launched, Optically∙Tracked, Wire Command-Link Guided) missile is a long range heavy antitank system designed to attack and defeat armored vehicles and other targets such as field fortifications. all-up rounds encased in a disposable container.

CHARACTERISTICS:

	TOW2A	TOW2B
Crew Size	က	ო
System Weight:	280 lbs	280 lbs
Reliability:	%56	95%
Minimum Range:	65M	200M
Maximum Range:	3750M	3750M

FOREIGN COUNTERPART:

Bofors Bill (Sweden) AT-4/5/6 (Russia) TRIGAT-Heavy (France/Germany/U.K.) MILAN 2 (France/Germany/U.K.) HOT 2 (France/Germany)

PROGRAM STATUS:

that time there have been five variations of the missile and two variations of the TOW Sub-system. The TOW 2B will replace the TOW 2A as the standard production missile in 2QFY92, and will join the over 100,000 missiles and 14,000 platforms already in the field. The TOW is currently in use by over 40 other nations as their primary heavy antiarmor weapon system. A requirement for an integrated target acquisition system is The TOW Weapon System entered its Production and Development Phase with the Basic TOW in 1970. Since addressed by an ongoing program of technical demonstrations and risk reduction efforts.

PERFORMANCE IN SWA:

Both the Army and the Marine Corps used the TOW as their heavy antiarmor weapon. Mounted on the M2/M3, HMMWV, ITV, AH-1S helicopter, and in its ground mounted version, it was extremely effective out to its maximum effective range and under degraded visibility conditions.

POINT OF CONTACT:


ATTN: SFAE-FS-TO Building 5250

Building 5250 Redstone Arsenal, AL 35898-5710

CONTRACTORS:

Hughes Aircraft Company (Tucson, AZ)

	Fielded	
	100	
	9	
retigenent	DEMANAL	
8	Concept Evel DEM/VA	
	Tech Bose	



MISSION:

The M16A2 is an improved version of the M16A1 and is being issued to front line combat soldiers as the Army's primary combat rifle. The M16A2 is a lightweight, air-cooled gas operated, low impulse rifle. It incorporates improvements in sight, pistol grip, stock and overall combat effectiveness. Accuracy is improved by incorporating an improved muzzle compensator, three round burst control, a heavier barrel and by using the heavier NATO standard ammunition which is also fired by the Squad Automatic Weapon.

CHARACTERISTICS:

Weight: Range:

Type of Fire:

5.56mm 8.9 lbs 550 meters Semi-automatic, three round burst 30 rounds

Magazine capacity:

FOREIGN COUNTERPART:

The 5.45mm AK-74 Assault Rifle is currently in service in The Commonwealth of Independent States as well as in some Eastern European forces.

PROGRAM STATUS:

The Army First Unit Equipped (FUE) occurred in January 1987 and to date, approximately 286,000 new weapons have been fielded. Approximately 100,000 M16A1 rifles will be converted to M16A2 rifles during depot overhaul using modification kits. A five year, competitively selected, firm fixed price contract was awarded in September 1988 for approximately 260,000 rifles.

POINT OF CONTACT:

Attn: AMSMC-ASI Rock Island, IL 61299-7150


Armament Munitions and Chemical Command

CONTRACTORS:

Colt Industries (Hartford, CT) began original production in June 1983. Current contractor is FN Manufacturing Inc. (Columbia, SC).

Fielded ŝ MOLENCE DEMONAL





PERSONAL DEFENSE WEAPON 9mm

MISSION:

The M9 9mm pistol replaces the M1911A1 .45 caliber pistol and the four-inch .38 caliber revolver currently used by the Department of Defense. The M9 is a semiautomatic double-action pistol that is more lethal, lighter, and safer than the M1911A1 pistol. It can be used effectively by either right or left handed shooters. The weapon is carried by service members who are not issued rifles, and others who have a close quarter personal defense requirement such as law enforcement personnel and aviators.

CHARACTERISTICS:

Double 15 rounds 50 meters 2.6 lbs Weight (loaded): Range: Trigger action:

Magazine Capacity:

FOREIGN COUNTERPART:

The Soviet-developed 9mm Makarov is the standard pistol for many Eastern European forces. 9mm semiautomatic pistols used by NATO allies include Beretta's 92F series, Heckler & Koch's P7/P9 series, Walther's P5/P88 series, Browning Highpower, and weapons manufactured by Glock, SIG, and Star. Performance of the M9 pistol and foreign counterparts are comparable.

PROGRAM STATUS:

The M9 pistol is in production. An initial five-year multiyear, firm fixed price contract was awarded in April 1985 for 315,930 weapons for all DoD uniformed services. A follow-on competition was conducted in FY 1989-1989 resulting in the award of option quantities totaling 56,705 pistols to Beretta beginning May 1989. As of January 1992, 262,932 M9 pistols have been delivered.

POINT OF CONTACT:


Product Manager, 9mm Pistol ATTN: SFAE-AR-9MM

Rock Island, IL 61299-7150

CONTRACTORS:

Beretta, USA (Accokeek, MD)

Fielded Î NAME DESCRIPTION



AUTOMATIC GRENADE LAUNCHER 40mm

MISSION:

The MK 19-3 is designed to deliver accurate, intense, decisive firepower against enemy personnel and lightly armored vehicles to a maximum effective range of 1600 meters against point targets and 2200 meters against area targets. It is used in offensive and defensive operations in the main battle area and will be the primary suppressive weapon for combat support and combat service support units. The MK19-3 is mounted on the High Mobility Multi-Purpose Wheeled Vehicle (HMMWV), M113 Armored Personnel Carriers, 5 ton trucks, and selected M88A1 recovery vehicles.

CHARACTERISTICS:

Rate of fire: Max effective range: Weight:

Lethality

Anti-armor--2.00 inches penetration to maximum range of 2200M 1500 meters (Point targets); 2200 meters (area targets) Anti-personnel -- 5 meters (Expected Casualty Radius) 325-375 rds/min 72.5 lbs

FOREIGN COUNTERPART:

The Soviet 30mm AGS-17 automatic grenade launcher was developed as a result of the fielding of the U.S. 40mm MK19 Mod O machine gun, which saw extensive service in Vietnam.

PROGRAM STATUS:

The MK 19-3 was developed and approved for Service use by the Navy in 1981. The Army type classified the MK 19-3 standard "A" in January 1986. Initial procurement of MK 19-3 for the 9th Infantry Division was contracted for by the Navy in October 1983. The Army assumed program management responsibilities from the Navy in FY88. A competitive five-year contract was awarded in December 1988. First Unit Equipped (FUE) occurred in November 1989.

POINT OF CONTACT:

Armament Research Development and Engineering Center Attn: SMCAR-GMG Picatinny Arsenal, N.J. 07806-5000

CONTRACTORS:

SACO Defense Inc. (Saco, ME)

Fielded DEMOVAL





SQUAD AUTOMATIC WEAPON

MISSION:

The M249 Squad Automatic Weapon (SAW) provides a lightweight, one-man-portable machine gun capable of delivering a large volume of effective fire for infantry squads. It also provides a sustained fire capability and increased range in rifle squads in order to enhance their survivability. This lightweight machinegun will replace the two automatic M16A1 rifles in the rifle squad on a one-for-one basis in all infantry type units and in elements of air cavalry and other non-infantry units.

CHARACTERISTICS:

Caliber: Weight: Rate:

16.3 lbs 5.56mm

Range: Magazine Capacity:

750 rds/min 800 meters 200 rds

FOREIGN COUNTERPART:

PROGRAM STATUS:

The closest equivalent systems are the Soviet-developed 7.62mm PKM and the 5.45mm RPK 74 which are fielded with Eastern European nations.

Fielding of the M249 started in FY84. Improvements recommended by users have been successfully tested and approved. These changes have been incorporated into the current 5-year, competitively selected, firm fixed price contract awarded in September 1988 for 28,000 guns.

POINT OF CONTACT:

Armaments Munitions and Chemical Command Attn: AMSMC-ASI


Rock Island, IL 61299-7150

CONTRACTORS:

FN Manufacturing Inc. (Columbia, SC)

Fielded DEMOVAL Concept five





TANK MAIN GUN AMMUNITION

MISSION:

The 120mm family of tank ammunition is fired from the M256 Cannon on the M1A1/M1A2 tank. There are four basic cartridge types: Kinetic Energy (KE); Armor Piercing, Fin Stabilized, Discarding Sabot-Tracer (APFSDS-T); Chemical Energy High Explosive (HEAT); and training rounds for each of the tactical cartridges. The Armaments Enhancement Initiative (AEI) program provides upgrades to 120mm ammunition capability which will defeat current armor threats.

CHARACTERISTICS:

High Explosive Anti-tank - Shaped charge warhead, combustible case, multiaction fuzing - M830, and Amor Piercing - One piece depleted uranium penetrator, combustible case, discarding sabot- 120mm M829, M829A1, M829E2 and 105mm - M900 (steel case)

Smart Ammunition.- High explosive, target activated, "fire and forget" (XM943 - STAFF) and armor piercing. with air defense capability - M830A1.

boosted, with terminal guidance (X-ROD).

NATO Allies and Soviet-developed tanks employ similar types of KE and HEAT ammunition. FOREIGN COUNTERPART:

PROGRAM STATUS:

The basic 120mm ammunition was fielded with the M1A1 Tank. The AEI program provides ammunition required to defeat Soviet threat armor vehicles of the 1990's and later. Two munitions from the AEI program have reached production status (M829A1 and M830A1). A third, M829E2, is scheduled for FY93 production. The M830A1 extends range capability and provides a new anti-helicopter, air defense capability.

The accuracy and lethality of the 120mm family of munitions were superb. Comanders and crews were so impressed with the M829A1 that they nicknamed it the "Silver Bullet". PERFORMANCE IN SWA:

POINT OF CONTACT:

Project Manager for Tank Main Armament Systems (PM-TMAS) ATTN: SFAE-AR-TM

Picatinny Arsenal, NJ 07806-5000

CONTRACTORS:

Hercules, Inc (Radford, VA)

Nuclear Metals, Inc (Concord, MA) Aerojet Ordnance (Jonesboro, TN) Martin Marietta (Milan, TN)

Fielded MANAGE BANAM

Alliant TechSystems, Inc. (Brooklyn Park, MN) Olin Ordnance (ST. Petersburg, FL) Chamberlain Mfg Corp (Waterloo, IA) Armtec Defense Products (Coachella, CA) Mason and Hangar (Middletown, IA)

NIGHT VISION DEVISES



IMAGERY WITH HEADS-UP DISPLAY OVERLAY



NIGHT VISION GOGGLE AND INFRARED AIMING LIGHT



THERMAL WEAPON SIGHT



NIGHT VISION & ELECTRO-OPTICS

MISSION:

Night vision (NV) image intensification (I2) and laser thermal technologies provide today's soldier with the capability to operate more effectively and safely at night.

CHARACTERISTICS:

NV Googles (Third generation image intensification):

AN/AVS-6 Aviator's Night Vision Imaging System: Lightweight, high performance, binocular unit for helicopter pilots

AN/PVS-7 Night Vision Goggle (NVG): Lightweight, head mounted, monocular unit used to operate ground vehicles, for navigation, map reading, first aid, etc. NV Googles (Second generation):

AN/PVS-4 Individual Served Weapon Sight

AN/TVS-5 Crew Served Weapon Sight

Miscellangous: AN/PAQ-4A Infrared Aiming Light (IAL): can be mounted on and boresighted to the M16A1/A2 AN/PVS-5 Night Vision Goggle AN/VS-2 Driver's Viewer

rifle, M60 machine gun, M67 recoilless rifle, and the M72A1 rocket launcher. Provides target sighting with an infrared beam which can only be seen when used with NVG. aser/Thermal Technology

AN/PVS-6 Mini Eyesafe Laser Infrared Observation Set (MELIOS): Eyesafe laser rangefinder which

measures and displays range. Thermal Weapon Sights (TWS): Infrared imaging devices used for surveillance and fire control of individual, crew-served, and heavy weapons during day, night and 'dirty' battlefield conditions.

COUNTERPART: FOREIGN

Second generation NV devices are produced in many countries including the Commonwealth of Independent States, Belgium, France, Germany, Israel, Italy, The Netherlands, Spain, Sweden, Switzerland, and the United Kingdom. The bulk of the equipment consists of passive I2 systems and first generation thermal devices.

There are presently several on-going contracts for the production of 12 devices/spares and laser/thermal devices. Additional device acquisitions began in FY92. Prototype thermal devices , with their ability to 'see' through thick smoke on the battlefield, received the highest praise. The AN/PAQ-4A (IAL), used as a weapon sight and terrain perception aid, was mounted on helicopter skids alerting crew to terrain changes. MELIOS was used for ranging as a handheld unit, and mounted on the Bradley.

POINT OF CONTACT:

CONTRACTORS

PERFORMANCE IN SWA:

STATUS


PROGRAM

PM Night Vision & Electro-Optics ATTN: S AE-IEW-NV

Fort Belvoir, VA 22060-5677

ITT Corp, Electro-Optical Products Division (Roanoke, VA) Electro-Optical Sensors, Inc (Palo Alto, CA) Insight Technology, Inc. (Manchester, MH) Litton Industries (Tempe, AZ)

IMO/Optic-Electronic Corp (Dallas, TX) Hughes Aircraft (El Segundo, CA) IMO/Varo (Garland, TX) IMO/Baird (Bedford, MA)




AIR DEFENSE

protect all ground forces elements including troop formations, depots, communications, air bases, key command and control facilities, and other vital relates to the detection and engagement of the air threat with ground fire systems. Air defense systems must area The Air Defense mission


Tech Base	Concept	DEVELOPMENT DEM/VAL	EMD	Production	Fleided
The Army's	Corps	Non-Line of Sight	Light & Special Division Avenger	Avenger	Patriot
Combined Arms	Surface-To-Air		Interim Sensor		
weapons System	Missile		Ground Based Sensor		Hawk
Advanced Air					Chaparral
Defense				•	
Electro-Optical					Stinger
Optical					
Counter-Measures					-

TACAWS Technology Base Program

- · Light weight Anti-helicopter, multi-role
- Acquisition in "clutter"/masked target kill
 - True fire and forget
- On-board IFF capability



THE ARMY'S COMBINED ARMS WEAPONS SYSTEM



ADVANCED AIR DEFENSE ELECTRO - OPTICAL SYSTEM



MULTI-ROLE SURVIVABLE RADAR



OPTICAL COUNTERMEASURES

AIR DEFENSE - TECH BASE

OVERVIEW:

THE ARMY'S COMBINED ARMS WEAPONS SYSTEM (TACAWS) ATTD:

ADVANCED AIR DEFENSE ELECTRO-OPTICAL (AADEOS) ATTD:

MULTI-ROLE SURVIVABLE RADAR (MRSR) ATTD:

OPTICAL COUNTER-MEASURES ATTD:


The goal of the Army Technology Base program in Air Defense is to provide advanced detection, tracking and engagement capabilities for weapon platforms to negate threat targets while enhancing survivability of high value U. S. assets. Improved target acquisition, positive identification and missile engagement technologies are being pursued to provide the leap ahead capabilities required to meet the ever increasing

missile in support of future Air-to-Air (primary), and secondary missions of Ground-to-Air, Air-to-Ground, Ground-to-Ground. The demonstration will include the integration of common guidance, control, propulsion, airframe and warhead technologies capable of performing in high clutter/obscurants, day/night adverse weather environments, and under countermeasure conditions. Capabilities demonstrated must exceed The TACAWS ATTD will demonstrate technologies for a light weight, fire-and-forget, air-to-air multirole current baseline of air-to-air Stinger.

and fixed-wing aircraft provides an incentive for incorporating passive acquisition devices on forward area air defense weapons such as the Line of Sight-Forward Heavy (LOS-FH). Anti-radiation missile employment and fixed-wing aircraft. The proliferation of radar warning receivers on threat Close Air Support helicopters Demonstration will be conducted of an infrared search and track sensor to detect and acquire helicopters Infrared sensors, processors, advanced cooling, optics, and algorithms will be used to assure adequate ability to track clutter-bound, low-signature helicopters to ranges in excess of 4-6 km. adds another stimulus to the development of passive acquisition capabilities.

operating in the presence of anti-radiation missiles and electronic countermeasures (ECM). The MRSR is a mobile sensor on a single vehicle capable of supporting both forward area air defense and corps weapons antenna designs, very wide bandwidths, frequency agility, and non-cooperative target recognition techniques. Design is structured for optimal insertion of very high speed integrated circuit and millimeter The MRSR ATTD will demonstrate a multi-function, track-while-scan, continuous-wave radar capable of and Patriot air defense systems in contingency operations. The demonstration focuses on low side lobe and microwave integrated circuits.

The ATTD will demonstrate a laser technology, anti-sensor tactical weapon to be effective against hardened electro-optical threats for protection of air defense and armor systems. The demonstration will be on a aser system will significantly reduce flyout time thus enhancing the lethality and survivability of U. S. mobile host vehicle against air defense targets to include threat sensors as well as threat missiles.



CRUISE MISSILE ABT SOJ NOTIONAL CORPS SAM CONCEPT CORPS ARM ABT **CORPS SAM** A A TBM 52 CORPS CORPS

CORPS SURFACE-TO-AIR MISSILE (CORPS SAM)

MISSION:

The Corps SAM mission is to protect key military assets in the Corps area and to provide continuous air defense for the supported forces as they maneuver. This mission must be accomplished in the context of Air Land Operations in both mature and contingency theaters. It will have the capability to defeat tactical missiles, tactical ballistic missiles (TBMs), air-to-surface missiles (ASMs), anti-radiation missiles (ARMs) and air-breathing threats (ABTs) which consist of fixed and rotary wing aircraft, cruise missiles, and unmanned aerial vehicles (UAVs).

CHARACTERISTICS:

Corps SAM will be a highly mobile, low-to-medium altitude air defense system designed to replace Hawk in the U.S. Army Corps and theater Air Defense Brigades. It will be strategically and tactically deployable to support rapid deployment to contingency theaters and for rapid reinforcement of deployed forces in mature intensity conflicts. Its high mobility will allow for rapid deployment of its elements in response to evolving theaters. Corps SAM's high firepower and flexible design will sustain operations in high and medium battlefield requirements. Corps SAM will consist of a weapon element, a sensor element and a tactical operations center element. A modular concept is envisioned, enabling the tactical commander to organize rasks based on mission, enemy, troops, terrain and time.

FOREIGN COUNTERPART:

Allied France/Italy -- Joint Famille Surface Air Futur (FSAF) Program Germany -- Medium Surface -to-Air Missile (MSAM) System

PROGRAM STATUS:

concept studies. A request for information was issued to industry on 11 OCT 91 and a request for proposals (RFP) is scheduled to be released during the 2nd quarter FY92. The RFP will facilitate preparation of concept studies providing trade-off analyses and alternative materiel solutions to the Corps Corps SAM was approved by the Secretary of Defense for entry into the Concept Exploration and Definition Phase on 6 AUG 90. This phase focuses on development of operational requirements and material Air Defense Capability Mission Need Statement, System Operational Description, and the releasable threats/scenarios.

POINT OF CONTACT:


PM Corps SAM ATTN: AMCPM-SM

Redstone Arsenal, AL 35898-5797

CONTRACTORS:

To be determined.

Tech base COTICE(P) PREAVAL THE PREAMENT NESSES



FORWARD AREA AIR DEFENSE SYSTEM (FAADS)

MISSION:

FAADS is an integrated program of complementary systems which will provide Army divisions with dedicated Air Defense Artillery (ADA) and integrate Joint and Combined Arms efforts to counter the threat. The FAADS concept is designed to provide total coverage in the division area and permits the enemy no preferred attack option through the 1990's and beyond.

CHARACTERISTICS:

FAADS consists of five components: Line of Sight-Forward-Heavy (LOS-F-H); Line of Sight-Rear (LOS-R); Non-Line of Sight (NLOS); FAAD Command, Control and Intelligence (FAAD C2I); and Combined Arms Initiatives (CAI).

FOREIGN COUNTERPART:

Soviet-developed ZS6, ZSU-23/4, SA-6, SA-9.

PROGRAM STATUS:

Boeing's AVENGER was selected for the LOS-R role. The First Unit Equipped (FUE) for AVENGER was FY89. FAAD C21's Command and Control initial fielding to light forces will begin late FY93. Ground Based Sensor (GBS) and one passive identification component are scheduled for initial fielding in FY97. The Airto-Air STINGER component of CAI is in production for the OH-58C/D. The Bradley Fighting Vehicle sight reticle enhancement was incorporated in production in May 1987. Engineering development continues on upgrading 120mm tank ammunition with an anti-helicopter capability.

PERFORMANCE IN SWA:

AVENGER was deployed in SWA and demonstrated outstanding operational availability. Ground force commanders relied on AVENGER to provide air and ground surveillance during night and limited visibility.

POINT OF CONTACT:

Program Executive Office, IEW (GBS) ATTN: SFAE-IEW-EW Ft. Monmouth, NJ 07703-5304


> ATTN: SFAE-AD Redstone Arsenal, AL 35898-5750

Program Executive Office, Air Defense

FAAD Ground Based Sensor- - TBD

CONTRACTORS:

LOS-R- - Boeing Aerospace Co. (Huntsville, AL) FAAD C2 Software - - TRW (Redondo Beach,CA)



NON-LINE OF SIGHT

MISSION:

Non-Line of Sight (NLOS) is a multiple mission combined arms weapons system which provides a fully adequate anti-armor capability against threat armor well beyond the maximum range of tank main guns or direct fire anti-tank missiles. In addition, NLOS provides air defense protection to the maneuver force against masked, standoff rotary-wing aircraft as well as the capability to destroy other moving or fixed point targets.

CHARACTERISTICS:

Guidance:

Mobility:

Engagement: Control:

Command Via Fiber Optic Datalink
Launch from Defilade, Non-Ballistic Flight Path
Gunner-In-The-Loop Provides Positive Identification Capability
Gunner's Station and Six Ready Missiles Self Contained On
High Mobility Multi-Purpose Wheeled Vehicle (HMMWV)

FOREIGN COUNTERPART:

None

STATUS

PROGRAM


Currently in the proof-of-principle phase. NLOS is planned to enter the Engineering and Manufacturing Development (EMD) Phase in third quarter FY93 to mature the Initial Operational Evaluation (IOE) design into a NLOS Tactical Weapon System. Initial fielding of a test unit and day equipped missiles will occur in the second quarter FY97. First unit equipped is scheduled for second quarter FY99.

POINT OF CONTACT:


Non-Line of Sight Project Office ATTN: AMSMI-NL Redstone Arsenal, AL 35898

CONTRACTORS:

To be selected







LIGHT AND SPECIAL DIVISION INTERIM SENSOR (LSDIS)

MISSION:

The Light and Special Division Interim Sensor (LSDIS) is being deployed as a stand alone system urgently needed to provide air defense early warning for U.S. Army Light and Special Divisions and Contingency Corps Air Defense Artillery (ADA) Battalions and supported maneuver forces. The LSDIS provides 360 degree coverage of airspace to alert and directionally orient air defense weapon system gunners significantly enhancing their ability to engage and destroy hostile fixed and rotary wing aircraft.

CHARACTERISTICS:

20 km range, continuous volume surveillance of aircraft, 360 degrees stand alone system, manportable, air droppable, HMMWV mountable, relatively simple, reliable, lightweight radar.

None.

FOREIGN COUNTERPART:

Completed First Article Test. Proceeding into Production Qualification Tests.

POINT OF CONTACT:

PROGRAM STATUS:


FAAD Sensor & Target Identification Project Office

Redstone Arsenal, AL, 35898-8052

CONTRACTORS:

Lockheed-Sanders (Nashua, NH)





200

FAAD-GBS prototype sensor mounted on a HMMWV.

FAAD-GBS prototype sensor mounted on a 5 ton truck.

FORWARD AREA AIR DEFENSE (FAAD) GROUND BASED SENSOR (GBS)

MISSION:

Aerial Vehicles (RPV/UĂV). Its primary missions are to cue Avenger fire units, protect friendly aircraft from fratricide, and provide targeting information to Line of Sight-Forward-Heavy (LOS-F-H). acquisition and tracking capability for the division's FAAD system and the C2I component. The GBS consists of a radar sensor system with its prime mover/power, Identification Friend or Foe (IFF), Non-Cooperative Target Recognition (NCTR) devices, and C2I interfaces. GBS is the prime contributor to FAAD C2I's development of the recognized air picture over the division area and beyond the forward line of troops. Air targets include fixed and rotary wing aircraft with growth capabilities to acquire cruise missiles and Remotely Piloted Vehicles/Unmanned The Forward Area Air Defense (FAAD) Ground Based Sensor (GBS) is the only sensor providing key target

CHARACTERISTICS:

Exact FAAD GBS characteristics will be determined at the conclusion of the ongoing Source Selection Evaluation. General characteristics are as follows:

Short to medium range air defense sensor Acquire and track fixed and rotary wing (growth to cruise missile/UAV) 360° azimuth, 10 meters to 4 km altitude cueing capability

Electronic Countermeasures (ECM) and Anti-Radiation Missile resistant

High mobility, transportability, and reliability Standard Army wheeled carrier (5 ton or HMMWV)

FOREIGN COUNTERPART:

Soviet-developed Straight Flush and long track radars.

STATUS: PROGRAM

POINT OF CONTACT

It is in the Engineering and Manufacturing Source selection process ongoing. Contract award 2QFY92. Development (EMD) phase of pre-production.

FAAD Sensor & Target Identification Project Office ATTN: SFAE-AD-GSI

Redstone Arsenal, AL, 35898-5796

CONTRACTORS:

To be determined.

Development EMD



AVENGER

MISSION:

defense brigades. Avenger is designed to counter hostile low-flying, high-speed, fixed-wing aircraft and helicopters attacking or transiting the division. Avenger fills the Line of Sight-Rear (LOS-R) portion of the Forward Area Air Defense System (FAADS). To provide air defense support in all divisions, armored cavalry regiments, separate heavy brigades, and corps air

CHARACTERISTICS:

This integrated system provides all the necessary functions to perform day/night and adverse weather target detection, acquisition, tracking, target ranging and friend or foe aircraft identification with either missile or machine gun. The Avenger's Standard Vehicle Mounted Launchers (SVMLs) interface and function with standard unmodified Basic Stinger, Stinger-POST and Stinger-RMP missile rounds.

8 ready Stinger missiles/.50 cal machine gun Modified HMMWV Armament:

2 FLIR/Laser/Optical

Sensors: Fire Control:

Chassis:

Digital fire control computer/gyro-stabilized electronic turret

FOREIGN COUNTERPART:

The Soviet-developed SA-9, introduced in the late 1960's, is the counterpart to Avenger. It has approximately the same range and also uses an infrared homing guidance system. The SA-9 is mounted on a two-axle amphibious vehicle.

PROGRAM STATUS:

The initial production contract was awarded competitively to the Boeing Aerospace Company in August 1987. The Secretary of the Army approved the Avenger system for Type Classification - Standard in February 1990. The Avenger went into full-scale production in April 1990. In 1991, a five year multiyear procurement to buy fire units for the U.S. Army and the Marine Corps began.

PERFORMANCE IN SWA:


Avenger was deployed during Operation Desert Shield/Storm and performed exceptionally. Its operational availability exceeded all requirements. Ground force commanders relied on Avenger to provide air and ground surveillance during night and limited visibility conditions.

POINT OF CONTACT:


Redstone Arsenal, AL 35898-5630 Avenger Product Office ATTN: SFAE-AD-AVG

CONTRACTORS

Boeing Aerospace Company (Huntsville, AL) - Production.







PATRIOT

MISSION:

CHARACTERISTICS:

The Patriot Missile System provides high and medium altitude defense against aircraft and tactical ballistic missiles at the Theater and Corps levels. Patriot's fast reaction capability, high firepower, and ability to operate in a severe electronic countermeasure environment are features not previously available in the systems Patriot replaces. The Patriot design eases the field logistic burden since its overall performance is achieved with less equipment, less manpower, and fewer set, an engagement control station, a power plant, antenna mast group, and eight remotely located launchers. The single phased array radar provides all tactical functions of airspace surveillance, target detection and track, and missile guidance. The engagement control station provides the human interface for control of operations. Each repair parts than previous systems. The combat element of the system is the fire unit which consists of a radar auncher contains four ready-to-fire missiles, sealed in canisters, which serve a dual purpose as shipping containers and launch tubes. Maximum range is 37 nautical miles. It has the ability to track 50 targets

The Soviets have developed several missile systems, including the SA-1, SA-2, SA-4, SA-5, SA-10, and SA-12, that are used to attack aircraft in the regime for which Patriot was designed. Only the SA-10 and SA-12 are considered as advanced or effective as Patriot.

FOREIGN COUNTERPART:

PROGRAM STATUS:

Patriot is in its thirteenth year of production and is fielded in CONUS, Europe, and Southwest Asia. Production of U.S. fire units is complete. U.S. missile production deliveries include Patriot Anti-tactical Missile (ATM) Capability-Level 2 (PAC-2). Germany, The Netherlands, Italy, Japan, Saudi Arabia and Israel are currently participating in PATRIOT acquisition programs. Discussions with other interested allies for Patriot acquisition are ongoing Patriot played a key role in Operation Desert Storm. Patriot protected key military assets and civilian population centers from tactical ballistic missile attack. Deployment of Patriot to Allied countries in the region promoted political cohesion. The production of PAC-2 was accelerated in order to field the ATM capability to SWA. Patriot performance exceeded all expectations and validated its ATM capability.

PERFORMANCE IN SWA:

POINT OF CONTACT:

Redstone Arsenal, AL 35898-5620

Patriot Project Officee ATTN: SFAE-AD-PA

Martin Marietta Corporation (Orlando, FL) Raytheon Company (Bedford, MA)

CONTRACTORS

Fielded





CONTINUOUS WAVE ACQUISITION RADAR



HAWK

MISSION:

Hawk is a medium range, surface-to-air guided missile system designed to provide Air Defense protection for critical assets and maneuver forces against aircraft attack. First fielded in 1960, Hawk has been continuously upgraded through a series of preplanned product improvements which have enhanced all aspects of the Hawk system. Each Hawk firing platoon is comprised of a platoon command post, an acquisition radar, a tracking radar with optical tracking system, and four launchers with three missiles each.

CHARACTERISTICS:

The system is transportable by helicopter and provides all weather, day or night coverage. The missile has a two stage, solid propellant motor with supersonic speed, and a high-explosive proximity-fuzed warhead. It has semi-active homing guidance.

Speed: Length: 40 km 1400 lbs Range: Weight:

800 m/sec 198 in

14.8 in Diameter:

FOREIGN COUNTERPART:

The Soviet-developed SA-6 is similar to Hawk. Its range and attitude capabilities are less than Hawk, but the SA-6 is more mobile. The basic SA-6 unit is a regiment which includes five missile batteries.

PROGRAM STATUS:

SWA:

PERFORMANCE IN

Hawk will remain with the active U.S. Army until 2005. It will be replaced by Corps Surface-to-Air Missile (SAM)

During Desert Shield and Desert Storm Hawk had an excellent readiness record. Reports from the Kuwaiti Air Force stated that at the beginning of the war, Hawk downed numerous enemy aircraft.

which is now in concept definition.

POINT OF CONTACT:


CONTRACTORS

Hawk Project Office ATTN: AMCPM-AP Redstone Arsenal, AL 35898-5660

General Electric (Huntsville, AL) Westinghouse Electric Corp. (Baltimore, MD) Universal Technology, Inc. (Estill Springs, TN) Raytheon Company (Andover, MA) Aerojet (Sacramento, CA)

Electro Design Mfg, Inc. (Decature, AL) Northrup Corp (Anaheim, CA) Summa Technology (Huntsville, AL) Harris Corp (Orlando, FL) Fielded 1 Canoapi thus | DBM/VAL |





CHAPARRAL

MISSION:

receding targets. To enhance missile acquisition range and infrared countermeasure rejection capability the Rosette Scan Seeker (RSS) guidance section has been retrofitted to inventory missiles upon shelf-life expiration of the current "smoky" motors. To assist the gunner in identifying targets as friendly, Chaparral has effective against all types of aircraft at low altitudes and provides protection for corps, theater rear areas and, currently, division areas. Chaparral is a self-propelled system. Its tracked carrier provides excellent crosscountry mobility. The launch station can be removed from the carrier and operated from a ground emplacement. It is equipped with a Forward Looking Infrared subsystem that provides day/night and adverse weather capability and extends system acquisition range. The missile is lightweight, supersonic, fire-andforget, with an all aspect passive infrared homing guidance system capable of engaging both approaching and an Identification Friend-or-Foe (IFF) subsytem. Chaparral carries four ready missites on faunch raits and eight additional missiles in storage compartments. Chaparral, which was initially fielded in 1969, is continually being Chaparral is one of the Army's Short-Range Air Defense (SHORAD) surface-to-air missile systems. It mproved and will remain in the inventory into the 21st Century.

CHARACTERISTICS:

Guidance: Warhead: Fuze:

Infrared Homing, Fire and Forget

FOREIGN COUNTERPART:

Blast-fragmentation Radio Frequency (RF) Directional Doppler

The Soviet-developed SA-9 and SA-13, introduced in late 1960's and 1970's respectively, are the counterparts to Chaparral. They have approximately the same range and also use an infrared homing guidance system. The SA-9 is mounted on a two-axle amphibious vehicle; the SA-13 is on an MTLB tracked

PROGRAM STATUS:

Chaparral has been in production since 1969. Hughes Aircraft Co. was awarded the FY90 RSS missile production contract. The FY90 RSS missiles will be delivered in FY92. With this delivery, a program total of 14,232 missiles and 569 fire units will be achieved.

PERFORMANCE IN SWA:

Chaparral demonstrated outstanding readiness rates in SWA. It proved to be a venerable Air Defense System

which provided short range air defense protection for the massive multi-national heavy forces.

POINT OF CONTACT:

ATTN: AMCPM-CF Redstone Arsenal, AL 35898-5000 Chaparral Project Office

CONTRACTORS:

Loral Aeronutronic (Newport Beach, CA) - System Development and RSS Production Hughes Aircraft Company (Tucson, AZ) - RSS Production

Fielded Ž DEMOVAL Concept Ivel





STINGER

MISSION:

CHARACTERISTICS

or helicopters.

To provide short range air defense coverage to combat units throughout the battlefield. Stinger is a shoulder-fired, infrared homing missile system which homes on the heat emitted by either jet or propeller-driven fixed-wing aircraft

Once the missile has traveled a safe distance from the gunner, its main engine ignites and propels it to the target. Stinger employs the wooden round concept. It can attack much faster targets than Redeye, and most importantly, can destroy aircraft from any aspect. A follow-on seeker (Stinger-Post) improved the capability of the system in certain infrared countermeasures environments. Stinger-Reprogrammable Microprocessor (RMP) further The Stinger system employs a proportional navigation system that allows it to fly an intercept course to the target. enhances the performance in infrared countermeasures environments and provides the capability for software

Passive Infrared & Ultraviolet homing upgrades to the missile as the threat evolves.

Speed: Supersonic Weight: 34.5 lbs Length: 60 in

Proportional with lead bias Navigation: Diameter:

FOREIGN COUNTERPART:

PROGRAM STATUS:

There are several similar Soviet-developed systems. The SA-14, fielded in the late 1970's, has similar performance characteristics to the Stinger. The SA-14 is replacing the SA-7. The SA-16, fielded in the 1980's, is replacing the

Stinger-RMP is currently in production by two manufacturers. Basic Stinger was operationally deployed to Germany in 1981 and production has been completed. Stinger-Post entered production in FY83, first deliveries were made in September 1986, and production was completed in August 1987. Stinger-Post missiles were deployed in FY87. Stinger-RMP entered development in September 1984, transition to production began in November 1985, and initial deliveries began in FY89; fielding began in FY90. The FY91 buy combined a competitive winner-take-all and a sustainment base procurement. Stinger-RMP production was accelerated to meet Desert Shield/Storm requirements.

PERFORMANCE IN SWA:

Stinger-RMP was deployed and provided highly mobile and lethal short range air defense protection to the maneuver forces.

POINT OF CONTACT:

Redstone Arsenal, AL, 35898-5630 Air-to-Air Missile Project Office ATTN: SFAE-AD-ATA

CONTRACTORS

General Dynamics Valley Systems Division (Rancho Cucamonga, CA) - Prime Raytheon (Lowell, MA) - Second Source. Fielded 1 Concept Evel DBM/VAL Tech Boss

FIRE SUPPORT

The Fire Support mission area includes those support provided by cannons, rockets, and missile systems, and also the target acquisition and communication systems integral to field artillery to the generation of indirect firepower. This mission area includes fire systems directly related operations

Tech Base	Concept Development	DEVELOPMENT ' DEM/VAL	EMD	Production	Fleided
Explosively Formed Penetrators	Advanced Field Artillery System-Cannon		BAT	Army TACMS	105mm Howitzer
Deep Attack	Long Fog/Deep Attack Future Armored Missile Nobigla Ammunition				Air-to-Ground
Insensitive Munitions					



LONG "FOG" / DEEP ATTACK MISSILE





EXPLOSIVELY FORMED PENETRATORS

FIRE SUPPORT - TECH BASE

OVERVIEW:

EXPLOSIVELY FORMED PENETRATORS (EFP):

LONG FOG/DEEP ATTACK MISSILE:

INSENSITIVE MUNITIONS:


survivability and lethality while decreasing logistics and training burdens. Among technologies that have recently transitioned from the Technology Base are Liquid Propellant and Unicharge for the Advanced Field Artillery System and for upgrades to fielded artillery systems, respectively. The Technology Base strategy produces advanced technologies to improve accuracy, range, mobility,

An EFP consists of a dish-shaped metal liner (like a saucer) in conte. With an explosive charge. The metal liner is typically made of a heavy metal such as tantalum. In these warheads, the metal liner is rapidly accelerated and shaped by the explosive charge to form a high velocity, stalle penetrator. Its range of several hundred meters provides a long standoff especially suitable for smart munitions. The Technology Base program demonstrates other materials, such as molybdenum, and configurations to increase lethality, range and accuracy and provide greater flexibility, such as choices of single or multiple warheads from the same weapon to best match target characteristics.

kilometers), precision weapon for surgical strikes against hardened and other high value targets. A human operator guides the missile by view ng an image transmitted through the fiber optic cable. This program capitalizes on technology developed under the Non-Line-of-Sigh: (NLOS) program with greater range, This de nonstration uses a fiber optically guided missile system that will provide a long range (100 plus reduced system detectability, improved lethality and reconnaissance capabilities.

The Insensitive Munitions program is designed to provide munitions that are less likely to be detonated suit tentionally by such stimuli as explosive blasts, shraphel and fires. The challenge is to develop less sensitive, yet, energetic molecules and formulations which fulfill all performore equirements for gun propellants and other propulsion systems such as shaped charges and explosively formed penetrators. This technology applies to all weapons systems, such as lank and artillery ammunition and missife warheads and propellants, to increase their survivability.





Future Armored Resupply Vehicle - Ammunition

9/

Advanced Field Artillery System

FUTURE ARMORED RESUPPLY VEHICLE-AMMUNITION **ADVANCED FIELD ARTILLERY SYSTEM-CANNON**

MISSION:

Ammunition (FARV-A) have become the core of the modified Armored Systems Modernization program. The goals of both AFAS-C and FARV-A programs are to develop a more survivable, longer range, self-propelled FARV.A are being developed to displace the M109A6 howitzer and M992 resupply vehicle within Force Package One. Together, they provide the capability for increased rates of fire, reduction in section size, and anillery system that is based on the common component approach to system development. AFAS-C and a fully automated ammunition handling system. Lessons learned from development of these two systems will The Advanced Field Artillery System - Cannon (AFAS-C) and the Future Armored Resupply Vehicle eventually be incorporated into other developing artillery weapon systems.

CHARACTERISTICS:

Automated REARM: 30km HE 40km RAP Range (km): AFASC-C

Rate of Fire:

Range: Speed: Crew.:

> 12-16 rds/min (5 min) 3-6 rds/min Sustained: <u>×</u>

200 rds std 155mm

Stowage Capacity: Macro NBC Protection

35-50 gals/min

2 rds/min 400 miles 53 mph

> 4 rd simultaneous impact Time on Target: (1 gun):

3-4 (operable by 1) Crew:

None known. FOREIGN COUNTERPART: PROGRAM STATUS:

FY93, the Army will continue technology maturation programs in common componentry, regenerative liquid propellant gun technology, extended armament and automated ammunition handling for AFAS-C, as well as Liquid propellant provides a greater degree of flexibility in system design and amplifies crew operations. In In 1991, the Army selected liquid propellant as the propellant of choice for its 21st century artillery system. key technologies associated with FARV-A.

POINT OF CONTACT:

Picatinny Arsenal, NJ 07806 AFAS Program Office Attn: SFAE-ASM-AF

GDLS (Sterling Heights, MI)

Picatinny Arsenal, NJ 07806

FARV-A Program Office

Attn: SFAE-ASM-FR

CONTRACTORS:

Teledyne (Muskegon, MI) FMC Ground Systems Division (San Jose, CA)

MVA. Development Concept Tech Boss



BRILLIANT ANTI-ARMOR SUBMUNITION (BAT)

MISSION:

attacks, and destroys moving tanks and other armored vehicles. It is this autonomous capability that makes this submunition "brilliant." BAT submunitions can be carried deep into enemy territory by a delivery vehicle, it autonomously locates, BAT is a self-guided submunition that uses two sensors: acoustic and infrared. then dispersed over a target to selectively attack and destroy it.

CHARACTERISTICS:

Diameter: Seekers: 36 in 44 lbs

Length: Weight:

Acoustic and Infrared

Army variant of Tri-Service Standoff Attack Missile (TSSAM) Guidance: Autonomous Tandem shaped warhead Payload: Tandem Delivery Vehicles:

Army Tactical Missile System (ATACMS)

FOREIGN COUNTERPART:

None.

PROGRAM STATUS:


demonstrated the system capability to autonomously acquire, track and impact moving armor targets with the necessary accuracy and lethality. Northrop Corporation is currently finalizing the system tactical design leading to a Critical Design Review in the second quarter of fiscal year 1992. approved by the Defense Acquisition Executive for entry into Engineering and Manufacturing Development on May 15, 1991. A contract was awarded to the Northrop Corporation on June 5, 1991. The program was initiated in1984 and has matured under extensive development and testing. These efforts have successfully BAT has just entered a 42-month Engineering and Manufacturing Development program. The BAT system was


POINT OF CONTACT:

Project Manager BAT ATTN: SFAE-FS-XB Redstone Arsenal, AL 35898-7998

CONTRACTORS:

Northrop Corporation (Hawthorne, CA) (Prime) Raytheon Company (Manchester, NH)





SENSE AND DESTROY ARMOR (SADARM)

MISSION:

SADARM is a comparatively low cost, fire-and-forget, sensor-fuzed submunition designed to detect and destroy lightly armored vehicles, primarily self-propelled artillery. SADARM is delivered to the target area by 155mm artillery projectiles or by the Multiple Launch Rocket System (MLRS). Once dispensed from its carrier, the submunition detects appropriate targets using dual-mode millimeter wave and infrared sensors and fires an explosively formed penetrator through the top of the target.

CHARACTERISTICS:

Caliber:
Weight:
Range:
Number Submunitions:
* From M109A6 Howitzer

155mm 5.8 in 26.4 lbs 22.5 km*

MLRS 6.9 in 30.8 lbs

30 km** 6/rocket

FOREIGN COUNTERPART:

The Russians are developing a SADARM-like weapon for application to both cannon artillery and rockets.

PROGRAM STATUS:

SADARM entered Engineering Manufacturing Development in March 1988 and is scheduled for a Low Rate Production decision in March 1993. SADARM is scheduled to be fielded in FY94 in 155mm and FY96 in MLRS.


POINT OF CONTACT:

PM, Sense and Destroy Armor ATTN: SFAE-AR-SD Pication Argord M. 197906 F

Picatinny Arsenal, NJ 07806-5000

CONTRACTORS:

AEROJET (Azusa,CA) LTV Aerospace and Defense (Grand Prarie,TX)







SYSTEM ARMY TACTICAL MISSILE (Army TACMS)

MISSION:

Army TACMS provides a long range missile system that operates in near all-weather conditions, day or night. It is air transportable and capable of effectively engaging high priority land targets at ranges beyond the capability of cannons, rockets, and the LANCE Missile System. The Block I System will be used to attack tactical surface-to-surface missile sites, air defense systems, logistics elements, and command/control/communications complexes, while the Block II System will attack second echelon maneuver

units arrayed in depth throughout the corps area of influence.

Army TACMS is a ground-launched, conventional, surface-to-surface, semi-guided ballistic missile with an Anti-Personnel/Anti-Materiel (APAM) warhead. The Block II System will carry a "smart" antiarmor submunition. Both missile versions are designed to be fired from the modified M270 MLRS launcher, utilizing the same

targeting systems, engagement systems, and command and control systems as MLRS.

PROGRAM STATUS

FOREIGN COUNTERPART:

CHARACTERISTICS:

SCUD Variants and SS-21 (Soviet-developed); Jericho (Israel)

fielded in the modernization program for a "system of systems" deep fires suite, and it has seen combat action in SWA. Army is currently examining the possibility of an extended range version of Block I to perform an anti-Army TACMS is currently in its first year of Full Scale Production. Low Rate Initial Production 1 (LRIP 1) began in 1990. Both LRIP 1 & 2 were accelerated in support of Operation Desert Shield/Desert Storm. Full Scale Production was accelerated in FY91 to prevent a production gap following the completion of LRIP 2. Current Procurement Objective is 1573 missiles. It is the first weapon system to be actical ballistic missile mission.

PERFORMANCE IN SWA:

Army TACMS was used to neutralize or destroy several surface-to-air missile sites, a logistics site, a refueling point, vehicles on a pontoon bridge, and several multiple launch rocket and howitzer batteries while in a counter-fire mode. One of the important lessons learned was the need to develop a joint doctrine for employment and airspace coordination when engaging targets.

POINT OF CONTACT:

Project Manager, Army TACMS ATTN: SFAE-FS-AT

35898-5650 Redstone Arsenal, AL

CONTRACTORS:

LTV Aerospace and Defense (Dallas, TX)

Production 2 Concept Evel | DEM/VAL |



M109A6 SELF-PROPELLED HOWITZER (PALADIN)

MISSION:

and navigation system, secure communications, an improved cannon and gun mount, automotive improvements, improved crew nuclear-biological-chemical protection, driver's night vision capability, and buitin test equipment. The Paladin possesses improved responsiveness, survivability, lethality, and reliability. Like the earlier M109 models, the Paladin (M109A6) will provide the primary indirect fire support to the The Paladin is capable of firing both conventional and nuclear 155mm munitions. The M109A6 modifications include an onboard ballistic computer maneuver brigades of armor and mechanized infantry divisions.

CHARACTERISTICS:

30 km (with Rocket Assisted Projectile) 24 km (with unassisted projectiles)

Maximum: 4 rounds/min. for 3 minutes Rate of Fire:

Sustained: 1 round/min. M284 155mm Cannon Main Armament:

Caliber .50 Machine Gun 32 tons Weight (combat loaded): Secondary Armament:

155 GCT (France) Slammer (Israel)

COUNTERPART:

FOREIGN

PROGRAM STATUS:

AS90 (U.K.) PzH 2000 (Germany)

Low rate production began in FY 1991 to achieve a First Unit Equipped date in 1993. The Army will acquire 824 Paladins as a product improvement of the current M109A2/A3 howitzer. The balance of the M109 howitzer fleet will receive the M109A5 upgrade which includes some automotive and crew nuclear-biological-chemical protection improvements and Paladin's M284 cannon.

POINT OF CONTACT:


Picatinny Arsenal, NJ 07806-5000 Product Manager, Paladin ATTN: SFAE-AR-HIP

Honeywell (Clearwater, FL) BMY (York, PA)

CONTRACTORS:

Alliant Techsystems (Minneapolis, MN),

GE (Burlington, MA), Carrier (Ft. Washington, PA)





M119A1 HOWITZER

MISSION:

lightweight, 105mm, towed howitzer that improves fire support for the Army's Airborne, Air Assault and Light Infantry Divisions and Separate Brigades. It fires all conventional 105mm ammunition in the inventory, the M913 High Explosive Rocket Assisted (HERA) ammunition now in production, and the new Dual Purpose Improved Conventional Munition (DPICM) in development. It is airmobile with the UH-60 Black Hawk helicopter and its prime mover is the High Mobility Multipurpose Wheel Vehicle (HMMWV). The M119A1 provides improved direct support artillery capabilities for the Army's Light Contingency forces. The M119A1 was procured as a non-developmental item based on the L119 British Light Gun. It is a

CHARACTERISTICS:

14.3 HE, 19.5 HERA, 14.9 DPICM

Range: Weight: Width:

4,000 lbs

241.5 in

54 in (travelling configuration)

Ammunition: Crew:

Length: Height:

HE, Smoke, Illumination, HERA, DPICM

FOREIGN COUNTERPART:

The nearest counterpart is the L119 British Light Gun and the Soviet-developed D-30 122mm howitzer.

PROGRAM STATUS:

The M119 was first fielded to the 7th Infantry Division, Ft Ord, California in December 1989. Since the initial fielding, it has been reclassified the M119A1 and was fielded to the 82nd Airborne Division in July 1991.

POINT OF CONTACT:

U.S. Armament, Munitions, and Chemical Command ATTN: AMSMC-ASA-H Rock Island Arsenal, IL 61299-6000

Watervliet Arsenel, NY Rock Island Arsenal, IL

CONTRACTORS:

Fielded DEM/VAL nount live





MULTIPLE LAUNCH ROCKET SYSTEM (MLRS)

MISSION:

The primary missions of MLRS are counterfire and suppression of enemy air defenses, light materiel and personnel targets. The MLRS is a free-flight, area fire, artillery rocket system which supplements cannon The basic warhead carries improved conventional submunitions. A growth program is underway to add the Sense and Destroy Armor (SADARM) warhead to improve counterbattery fires. The MLRS M270 launcher is artillery fires by delivering large volumes of firepower in a short time against critical, time-sensitive targets. being updated to accommodate launching a new MLRS family of munitions (MFOM), including the Army Factical Missile System (ATACMS)

CHARACTERISTICS:

6.8 m Cruisi 3 m Avera 24,756 kg Maxin

Length: Width: Weight:

ange; 483 km

Rocket Range: 3; Crew: 3

FOREIGN COUNTERPART:

STATUS

PROGRAM

Cruising Range: Average speed: Maximum speed:

40 kph 56 kph There are nine systems which have a broad range of capabilities similar to MLRS, e.g. Soviet-developed 220 mm BM-22, Yugoslavian 262 mm ORKAN and Chinese 273 mm MRL

operational capability for MLRS was achieved in 1983. Starting in FY89, MLRS has been coproduced by the United States, United Kingdom, Germany, France, and Italy. As of 5 Dec 1991, a total of 406 units have been The second multiyear procurement contract for FY89-93 was awarded in July 1989 for MLRS. The U.S. initial fielded. Potential improvements to the system include the improved fire control system (IFCS). The IFCS will mitigate electronic obsolescence currently existing in the fire control system (FCS) and will accommodate the needs of the MFOM weapon systems under development and provide growth for future weapon systems.

PERFORMANCE IN SWA:

MLRS performed extremely well in Operation Desert Storm (ODS). Significant numbers of MLRS launchers were deployed. All operational requirements were met and, in most cases, exceeded for readiness, reliability, and maintainability. MLRS units from the United Kingdom were also involved in ODS and proved the value of this multi-national system. The new upgraded MLRS (Deep Attack Launcher) also demonstrated its enormous capability during the first operational firings of the longer range ATACMS.

POINT OF CONTACT:

Project Manager MLRS Attn: SFAE-FS-ML Redstone Arsenal, Al 35896

TV Accessed to the control of the co

CONTRACTORS:

LTV Aerospace and Defense (Dallas, TX) Brunswick Corp (Camden, AR)
Norden System (Norwalk, CT)
Atlantic Research (Camden, AR)
Bendix Corp (Teterboro, NJ)

Tech base Concept five DBA/VAL BAD Presbucy Fielded

83



AIR-TO-GROUND MISSILE SYSTEMS (AGMS) (Formerly Hellfire)

폿
9
SS
₹

AGMS is a third-generation airborne antiarmor weapon. It is presently employed as the main armament of the Apache helicopter. AGMS homes on a laser spot that can be projected from ground observers, other aircraft and the launching aircraft itself. This enables the system to be employed in a variety of modes: autonomous, air or ground, direct or indirect, single shot, rapid or ripple fire.

CHARACTERISTICS:

Modbuo 7 in 106 lbs HOMS 7 in 100 fbs 64 in Improved 7 in 106 lbs 7 in 100 lbs Basic Diameter: Weight:

FOREIGN COUNTERPART:

Numerous countries possess one or more wire, radio, or laser homing antiarmor missiles of varying accuracy and lethality

PROGRAM STATUS:

There are four versions of the AGMS missile in various stages of the life cycle:

<u>Basic Hellfire</u> - Semi-active laser seeker, approximately 35,000 produced by both Martin Marietta and Rockwell International since 1983. All deliveries have been completed.

<u>mproved Hellfire</u> - (Adds precusor for reactive armor) Final buy of Improved Hellfire missiles currently being produced by Rockwell

<u> Jeltire Opimized Missile System (HOMS)</u> - Under development by Martin Marietta (Engineering and Manufacturing Development (EMD) contract 1990-92), with Low Rate Initial Production award in FY 92 and priced production options for 1993-96. Lethal against the threat, fully Electro-Optical Counter Measure (EOCM) capable, restores the bast line weight and length (lost with the Improved Helifire). Longbow.- Millimeter wave seeker variation for the HOMS missife body. Under EMD by a joint venture (JV)

between Martin Marietta and Westinghouse

PERFORMANCE IN SWA:

AGMS missiles performed exceptionally well, as evidenced by the high percentage of hits and overall mission success reported by the using units. While the Hellfire is designed for an Air-To-Ground antiarmor role, it was used in a number of missions other than antiarmor (i.e., fixed structures, air targets and other missions requiring precision guidance).

POINT OF CONTACT:

Air-To-Ground Missile Sys. ATTN: SFAE-FS-HD Project Manager

Redstone Arsenal, Alabama 35898

CONTRACTORS

Martin Marietta (Orlando, FL) (Hellfire Optimized Missile System and part of Longbow JV)
Westinghouse (Baltimore, MD) (Part of Longbow JV) Rockwell International Corporation (Duluth, GA) (Improved Helifire Warhead Missile)

Fielded 3 DEMINAL


COMBAT SUPPORT

planning, combat operations, and readiness. This mission area includes essential force multipliers to improve the commander's battle management and sustainment in the highly lethal and mobile AirLand Combat Support includes those items providing operational assistance to the combat arms in Battlefield.

		DEVELOPMENT			
Tech Base	Concept Development	DEM/VAL	EMD	Production	pepieli
Radar Deception and Jamming			Joint Surveillance and Target Attack Radar	Lightweight Mannorfable	Black Hawk
Countermine			System	Radio Direction	HMMWV
Joint Air/Land/Sea Precision Strike			Trackwolf Crance Book of Control of Control Book of Control Book of Control o		Smoke and Obscurants
Demonstration			Sensors		Nuclear, Biological,
			Special Operations Aircraft		and Chemical Reconnaisance System
					Mohawk
					Quick Fix
					Guardrail
	-				Armored Combat Earthmover
					Recovery Vehicle



COUNTERMINE



Lethal strike before the enemy can react

JOINT AIR / LAND / SEA PRECISION STRIKE DEMONSTRATION



RADAR DECEPTION AND JAMMING

TECH TECH COMBAT SUPPORT

OVERVIEW:

locate and classify high priority targets and direct weapon systems for engagement. Additionally, investments in this mission area focus on the demonstration of advanced techniques/devices to detect and The goal of the Army Technology Base program in Combat Support is to provide the technologies to identify, neutralize enemy mines/minefields to support mobility and survivability of U. S. troops and assets.

> RADAR DECEPTION AND JAMMING ATTD:

Demonstrations will include Apache and Blackhawk escort and standoff jammers, wideband/expert systems other avionics for situation awareness, survivability, and targeting. It will also demonstrate state-of-the-art This ATTD will demonstrate sensor fusion and power management of Identification Friend or Foe (IFF) and suppression of enemy air defense (SEAD) and deception to protect attack and Special Operations Aircraft. upgrades and airborne deception of an integrated air defense network. Specialized advances in high power microwave control components and wide band space-fed antenna arrays will be demonstrated

COUNTERMINE:

countries. The Army will aggressively exploit novel mine neutralization technologies in high power microwave, magnetic signature silencing and wide area neutralization to counter both antipersonnel and antiarmor mines possessed by potential adversaries. These technologies will provide a more rapid fielding Operation Desert Shield/Desert Storm highlighted the capabilities in landmine warfare possessed by hostile of a next generation countermine solution and will help in leveraging industry efforts.

JOINT AIR/LAND/SEA PRECISION STRIKE

DEMONSTRATION (ARMY LEAD):

DoD Science & Technology Thrust which identifies a requirement for all-weather, day/night precision strike against 21st century critical mobile and fixed targets. The demonstration, conducted in FY93-96, will surveillance and aided target recognition (ATR) assets, Joint Surveillance and Target Attack Radar System (JSTARS), Army Tactical Missile System (ATACMS) and Air Force and Navy precision munitions to achieve an all-weather precision strike execution capability. End-to-end system capabilities to successfully engage targets with high accuracy will be simulated on a combined arms electronic battlefield (EB) and correlated to test exercise data. Promising advanced technologies will then be evaluated using the correlated EB model for real-time assessment of weapons effectiveness in a dynamic battlefield. An assessment will also be range, short-dwell targets. Linkage and integration will be demonstrated in a test exercise between A Joint Air/Land/Sea Precision Strike demonstration (Army lead) will be initiated in FY93 in response to the integrate surveillance, target acquisition, processing and attack for rapid response execution at extendedagainst 21st century critical mobile and fixed targets. made of clutter, countermeasures and execution times





USAF E-8 Joint STARS Aircraft

US Army Joint STARS Ground Station Module (GSM)

JOINT SURVEILLANCE TARGET ATTACK RADAR SYSTEM (Joint STARS) GROUND STATION MODULE (GSM)

MISSION:

and deep targeting data on both moving and fixed targets during daylight, darkness and near all weather conditions to detect, locate, track, classify and assist in attacking targets beyond the Forward Line of Troops (FLOT). Joint STARS is a joint Air Force/Army program. Orbiting a safe distance on the friendly side of the FLOT, the Joint STARS radar covers a wide area at great depth on the unfriendly side of the FLOT. The radar data is simultaneously received by Air Force and Army operators aboard the aircraft and by multiple GSMs at Echelons Above Corps (EAC), Corps, Corps Artillery, Division, and Division Artillery. he Joint STARS system provides tactical air and ground commanders near real time wide area surveillance

CHARACTERISTICS:

analyzes and disseminates information. GSM is being developed in three versions: Block I on a 5-Ton truck, Block II in an Electronic Fighting Vehicle System (EFVS) on a Bradley chassis and Block IIA on a HMMWV Airborne Platform: USAF E-8 (Militarized Boeing 707), multi-mode radar (wide area surveillance and synthetic Ground Station Module (GSM): It is a mobile, tactical, multi-sensor ground processor that receives, displays, aperture), 18 operation and control consoles, surveillance and control data link, secure communications.

FOREIGN COUNTERPART:

British ASTOR (airborne radar on Pilatus Britten-Norman Defender aircraft), French HORIZON (airborne radar on Aerospatiale Super Puma helicopter). GSM is interoperable with both.

PROGRAM STATUS:

The Joint STARS GSM is in Engineering and Manufacturing Development (E&MD). Six Interim GSMs (IGSM) are available for test, demonstration and contingency operations. An Operational Field Demonstration (OFD) of the E-8 aircraft and GSMs was successfully completed in the fall of 1990 in Europe gaining wide acceptance and support from senior US and allied commanders.

PERFORMANCE IN SWA:

Two E-8 Joint STARS aircraft and six KSSMs deployed to SWA from 11 Jan to 6 Mar 1991. The Army's GSMs were in direct support of deployed ground forces. The Joint STARS system made significant contributions to the coalition effort, saved innumerable lives and proved that it is a major force multiplier. The Army Central Command (ARCENT) Deputy Chief of Staff for Intelligence stated that Joint STARS was the single most valuable intelligence and targeting system in Desert Storm.

POINT OF CONTACT:

Army Project Manager, Joint STARS SFAE-IEW-JS

Fort Monmouth, N.J. 07703-5304

CONTRACTORS:

Motorola Corporation (Scottsdale, AZ)
Hughes Simulation Systems, Inc (Minneapolis, MN)
Norden Systems Div of United Technologies (Norwalk, CT)

Grumman Aerospace (Melbourne, FL) CUBIC Defense Systems (San Diego, CA)





TRACKWOLF

MISSION:

subsystems: a Collection and Processing Subsystem (CPS) and a Direction Finding Subsystem (DFS). The CPS consists of command and control, receiving system, and collection analysis shelters. The DFS consists together by landline or HF radio. Trackwolf has two primary missions: signals intercept, performed by the CPS; and direction finding, performed by the DFS. The CPS is normally located in the theater rear area approximately 200 kilometers behind the Forward Line of Troops (FLOT). The system supports Echelon Above Corps (EAC) commanders by supplying intelligence information to the theater level All Source Analysis System (ASAS). It communicates with the ASAS through the Single Source Processor - SIGINT (SSP-S) link. The AN/TSQ-152 Special Purpose Receiving System (Trackwolf) is a High Frequency (HF) sky wave, intelligence, and emitter location system. The Trackwolf system is comprised of two separate interactive of a Net Control Station (NCS) collocated with the CPS and three remotely located DF outstations which net

CPS is modular with all components linked together via a Local Area Network (LAN). This allows systems to be tactically sized to meet operational requirements ranging from Field Station operations to rapid deployment Corps operations. The hardware suite of equipment within the CPS is a combination of non-developmental item (NDI) and field station components. The software is the NDI Conventional Signal Upgrade (CSU) utilized in The DFS is capable of both netted Direction Finding (DF) and Single Station Location (SSL) operations. The ield stations.

FOREIGN COUNTERPART:

CHARACTERISTICS:

None known.

PROGRAM STATUS:

Development. Initial Key Personnel (IKP) training and Phase I Initial Operational Test and Evaluation (IOT&E) have been completed. System is scheduled to arrive OCONUS in 2nd QTR FY92. Phase It IOT&E is scheduled for 4th QTR FY92. System handoff is scheduled for 2nd QTR FY93. Procurement of a second downsized Trackwoff is scheduled for FY94, pending the results of IOT&E.

Trackwolf is being handled as a Quick Reaction Capability (QRC) Program that is now in Full Scale

Tactical HF skywave DF was a noted deficiency in Operation Desert Shield/Storm. Pre-Trackwolf proof of

PERFORMANCE IN SWA:

principle systems performed well

POINT OF CONTACT:


CONTRACTORS:

Warrenton, VA 22186 PM Signals Warfare Vint Hill Farms Station

TCI, Technology for Communications International (Fremont, CA)

Development EMD Concept Ivol DRV

GROUND BASED COMMON SENSORS



GBCS - H

IEW GROUND BASED COMMON SENSORS

MISSION:

MLRS chassis (M993). Both GBCS-L and GBCS-H, are elements of the Intelligence Electronic Warfare Common Sensor (IEWCS) program, interoperates with the other elements of the IEWCS and the Advanced Quickfix in order to locate and acquire targets beyond the Forward Line of Troops. Situation development information is transmitted to the Technical Control and Analysis Element (TCAE) of the All Source Analysis HMMWV mounted while GBCS-H is mounted in an Electronic Fighting Vehicle System (EFVS), which uses a Ground Based Common Sensor - Light (GBCS-L) and Ground Based Common Sensor - Heavy (GBCS-H) are mounted signals intercept and emitter location systems which search, intercept, locate, identify and provide electronic countermeasures against enemy communications and noncommunications emitters. GBCS-L is System (ASAS) and targeting information is transmitted through the TACFIRE system to their respective users. Both GBCS-H and GBCS-L will be built with "open systems architecture" to accomodate rapid echnology insertion and keep pace with changes in threat characteristics. The light and heavy variant of the EWCS system have the same common sensor subsystems as the Advanced Quickfix.

CHARACTERISTICS:

Roll-on, roll-off (RO-RO) Intercept, locate & jam: Setup/Teardown time: Vehicular operation: Mission operation:

Twenty-four hours HE, VHF, UH All terrain

C-5 (GBCS-H); C-130, C-141 (GBCS-L)

FOREIGN COUNTERPART:

None known PROGRAM STATUS:

Both are in Engineering and Manufacturing Development. The Technical Test/User Test is scheduled for FY93 FY94. The advanced development system, Tomcat, was fielded with the Marines and was the only ground system able to operate against low probability of intercept signals. Key lesson learned in SWA is that IEW systems require deployability and mobility equal to the supported force.

POINT OF CONTACT:


CONTRACTORS:


PERFORMANCE IN SWA:

PM Signals Warfare Vint Hill Farms Station Warrenton, VA 22186

ELECTROSPACE Systems Inc. (Richardson, TX) Sanders/AEL Joint Venture (Hudson, NH) Motorola Inc. (Scottsdale, AZ)

IBM Corp. (Owego, NY) Magnavox (Fort Wayne, IN) FMC Corp. (Santa Clara, CA)





MH - 60K

SPECIAL OPERATIONS AIRCRAFT (SOA)

MISSION:

an aerial refueling capability, upgraded engines and worldwide communications equipment. Additional improvements include a totally integrated cockpit, which dramatically reduces pilot workload, as well as improved terrain following/terrain avoidance radar and forward kooking infrared radar capability. Their missions cover rapid deployment, strategic intelligence strikes, and other operational missions supported by the Special Operations Forces. helicopters that will provide the Army with the capability for low level, night, adverse weather, extended range, and precision navigation through unfamiliar mountainous terrain. Both the utility and medium-lift version (designated MH-60K and MH-47E, respectively) will be provisioned with extended range fuel systems including The Special Operations Aircraft (SOA) are modified Black Hawk (UH-60L) and medium-lift Chinook (CH-47D)

CHARACTERISTICS:

MH-50K		7.6 hrs	755 nm		3 - 7.62 mm (M134) 2 - 7.62 mm (M134)	•
54.000 15	138 kts	9.8 hrs	i; 1,260 nm	4 42 traces	3 - 7.62 m	machine guns
Mission Weight:	Cruise Speed:	Endurance*: Maximum Self	Deployment Range*;	Javload:	Armament:	- oc/m polonyoxum

The Soviet-developed MI-8 is a medium-lift helicopter and the MI-26 is a heavy lift helicopter. The HIP series and HALO perform troop carrier and general cargo transport.

* unrefueled w/30 min reserve; however, also has air-to-air refuel capability.

FOREIGN COUNTERPART:

PROGRAM STATUS:

The MH-47E and MH-60K are currently under Engineering and Manufacturing Development. MH-47E production started in FY91 with First Unit Equipped (FUE) date during the 4th Qtr, FY93; for MH-60K, 1st Qtr, FY93. The SOA program will provide 23 MH-60K and 26 MH-47E aircraft.

POINT OF CONTACT:

PM Special Operations Aircraft (SOA) 4300 Goodfellow BLVD


SFAE--AV-SOA ST. Louis, MO 63120-1798

CONTRACTORS:

Boeing Helicopter Company (Philadelphia, PA) Siskorsky Aircraft Division (Stratford, CT) IBM FSD (Owego, NY)

		į	
_		oduciton	
	Development	EMD	
	Developm	Tech Base Concept Eval DEM/V	
		lech Bose	





LIGHTWEIGHT MANPORTABLE RADIO DIRECTION FINDING SYSTEM

MISSION:

AN/PRD-12 is a man-transportable ground-based communications intercept and direction finding (DF) system. It consists of a receiver processor and two antenna subsystems. The system can be deployed by two people. The system provides intercept and direction finding of enemy HF/VHF/UHF communications emmitters. The system also nets with the AN /TRQ-32(V) Teammate. The basis of issue is six per Light Division and four per Special Forces Group.

CHARACTERISTICS:

Intercept Frequency Range: DF Frequency Range: Weight:

0.5 - 500 Mhz 0.5 - 500 Mhz 53 lbs

FOREIGN COUNTERPART:

There are several commercially available systems similar to the AN/PRD-12 available from US & UK firms.

STATUS: PROGRAM


The system is in production and will begin fielding in 2QFY92. There are currently two materiel changes underway to extend the intercept and DF frequency range to 1.2 Ghz and to provide a smaller antenna for Special Operations Forces (SOF) operations.

POINT OF CONTACT:

PM Signals Warfare Vint Hill Farms Station Warrenton, VA 22186

CONTRACTORS:

ESL Inc. (Sunnyvale, CA).







BLACK HAWK

MISSION:

missions. The Black Hawk can carry more than twice the payload and is capable of transporting an entire 11-man, fully equipped squad faster and in most weather conditions. The Black Hawk is the first utility/assault The UH-60 Black Hawk is replacing the UH-1 "HUEY" in air assault, air cavalry, and aeromedical evacuation helicopter that adds to the Army's Division level mobility; for example it can reposition a 105mm howitzer, its crew of 6, and up to 30 rounds of ammunition in a single lift. Its critical components and systems are armored or redundant to enable it to withstand multiple small arms hits, and its airframe is designed to progressively crush on impact to protect the crew and passengers in a crash. Advanced technology in the Black Hawk makes it easier to maintain in the field than any other helicopter in the world. Black Hawk's full squad carrying ability significantly improves the small-unit commander's ability to retain control of his forces under combat conditions, and permits more rapid replacement of ammunition and other combat consumables in a high intensity war.

CHARACTERISTICS:

159 kts Max Gross Weight:

Cruise Speed Endurance:

2.3 hrs

Max Range:

two 7.62mm machine guns 2 pilots, 1 crew chief 330 nm

Armament: Payload:

2640 lbs (or 11 combat equipped troops) External Load:

FOREIGN COUNTERPART:

STATUS

PROGRAM

The Soviet-developed HIP series is much slower and is used as a troop carrier and general cargo transport, can carry up to 24 troops.

Black Hawk is being procured under a new five year, multiyear contract covering FY92 to FY96. This multiyear program will allow the Army to modernize the National guard and Reserves with the Black Hawk.

Army is presently fielding the UH-60L to its high-priority units.

areas of the combat mission area. The UH-60's were heavily used for positioning and resupplying the troops. The Black Hawk flew over 44,000 flight hours during the operation. Additional missions included MEDIVAC, Command and Control, and Special Operations. The UH-60 Black Hawk was considered the "backbone" of The UH-60 was well represented in the Desert Shield/Storm Operation with over 400 aircraft operating in all Army Aviation.

POINT OF CONTACT:

PERFORMANCE IN SWA:

ATTN: (SFAE-AV-BH) ST. Louis, MO 63120-1798 4300 Goodfellow BLVD PM Utility Helicopter


CONTRACTORS:

Sikorsky (Stratford, CT)

General Electric (W. Lynn, MA)

Fielded Concept Eval DEM/VAL BAID Nech Base





HIGH MOBILITY MULTIPURPOSE WHEELED VEHICLE (HMMMV)

MISSION:

to the 1/4 ton Jeep, M718A1 Ambulance, 1/2 ton M274 Mule, 1 1/4 ton Gamma Goat, and M792 Ambulance. The HMMWV is a Tri-Service program that also provides vehicles to satisfy Marine Corps and Air Force requirements. The HMMWV program is complementary to the 1 1/4 Ton Commercial Utility and Cargo Vehicle (CUCV) Non-developmental Item (NDI) program. Other The HMMWV is a light, highly mobile, diesel powered, four-wheel drive tactical vehicle that uses a common 1 1/4 ton payload armament carrier, S250 shelter carrier, two or four litter ambulance, or TOW missile carrier. The HMMWV provides a successor chassis. The HMMWV can be configured through the use of common components and kits to become a cargo/troop carrier, developmental models include prime mover for the light howitzer, towed VULCAN system, and heavy variant shetter carriers.

HARACTERISTICS:		Cargo/Troop <u>Carrier</u>	Armament <u>Carrier</u>	TOW	Ambulance <u>Carrier</u>	S250 Carrier	Heavy <u>Variant</u>
		5200	5960		7180	5483	2600
		2500	2240		1920	3177	4400
		7700	8200		9100	8660	10000
		2/4	4		2/4 (litters)	2	2/4
		180	180		203	188	180
		72	72 w/o launcher		72 w/o	105	104
		82	85		82	88	82
	Capacity:	3400lbs					4200lbs
	Range:	300 miles					
NEITH							

OREIGN

COUNTERPART: No known foreign counterpart.

A new five-year letter contract was awarded in August 1989. Total multiyear quantity is approximately 33,000 vehicles. PROGRAM STATUS:

PERFORMANCE IN SWA: Excellent.

POINT OF CONTACT: PM-Light Tactical Vehicle
PEO-Combat Support

Automotive Command Warren, MI 48397-5000


Commody Command US Tank

Warren, MI 48397-5000

AM General Corporation (South Bend, IN)

CONTRACTOR:

Tech lass Cancept feet | DilatviA. | Teah | Field



LARGE AREA SMOKE GENERATOR SYSTEM

SMOKE GENERATOR SYSTEM MAKING A LARGE AREA SMOKE SCREEN



SMOKE and OBSCURANTS

MISSION:

vehicles produce an instantaneous screen that defeats enemy electro-optic sensors and weapon guidance systems. Artillery, mortar and rocket delivered smoke rounds degrade enemy vision or screen the advance of friendly forces. Mounted on tactical vehicles, large area smoke systems help obscure high priority targets (airfields, bridges and ammunition depots) as well as Smoke and obscurants greatly improve survivability on today's high intensity battlefield. Smoke grenades fired from comb. convoys and troop movements. Smoke projectiles, mortars, grenades and rockets are also used for signaling and marking.

> FOREIGN COUNTERPART:

Countries using Soviet doctrine emphasize extensive use of smoke during tactical operations. Many nations, especially those in the Middle East, are realizing the benefits of smoke and have developed programs in this area.

PROGRAM STATUS:

Smoke and obsurants technology initiatives focus on enhancing obscurant effects in the infrared and millimeter wave (radar) spectrum bands. These expanded capabilities will defeat advanced target and guidance systems.

VEHICLE DEFENSE: Visual and infrared smoke grenades for vehicle self protection are available. A millimeter/infrared

PROJECTED SMOKE: Improved submunition rounds are available for artillery and mortars. A new smoke warhead for the 2.75

screening grenade is being developed. Multi-salvo launchers for wheeled and tracked vehicles are also being developed.

LARGE AREA SMOKE: New tracked and wheeled smoke generators have been fielded. System upgrades with enhanced

rocket is completing development.

infrared/millimeter wave screening and other mission enhancements are already being developed.

POINT OF CONTACT: PM SMOKE

CONTRACTORS:

U.S. Army CRDEC

ATTN: SMCCR-MU

Aberdeen Proving Ground, MD 21010

Aberdeen Proving Ground, MD 21010

ATTN: AMCPM-SMK

MRC Division of Chamberlain Manufacturing Corp (XM56 Development) (Hunt Park, MD) Minowitz Manufacturing Corp (M157 production) (Detroit, MI) (Completed)

Tierney (Turbines for XM56 development) (Detroit, MI) Brinswick Defense (Deland FI) (XM6)

Brunswick Defense (Deland, FL) (XM6)

BEI Corporation (Eulers, TX) (XM264)

Sech hase Concept heat DBM/VAL BAD Preduct FIGIGGG





NUCLEAR, BIOLOGICAL, CHEMICAL RECONNAISSANCE SYSTEM (NBCRS) - FOX

MISSION:

The M93 is a wheeled armored vehicle equipped with a fully integrated NBC detection, warning and communication system. It will detect, identify and mark areas of NBC contamination; collect soil, water and vegetation samples for later analysis; mark areas of nuclear and chemical contamination; and transmit NBC information to unit commanders in the area of operation. The hazards to the NBCRS crew will be minimized through the inclusion of vehicle NBC collective protection providing overpressure with heating and cooling for crewmen.

CHARACTERISTICS:

6 wheel, armored-collective protection Body Style:

V8 Diesel - 320 HP Engine:

18.7 ton Weight:

500 miles 65 mph Speed: Range:

4 soldiers (3 soldiers - system improvement vehicle) Crew:

COUNTERPART: FOREIGN

3RDM-ZRKH, MTLB, RKHM, UAZ-469RKH (Soviet-developed). Chinese also have a NBC Recon System.

PROGRAM STATUS:

orces and 10 with the Marine Corps during Operation Desert Storm. These systems are now with their units and being used in The NBCRS is a new non-developmental item (NDI) program consisting of four phases: (1) Proposal Evaluation and Shoot-off Phase during which proposals were evaluated, competition conducted and a winner selected; (2) Interim System Production Phase which provides 48 contractor supported (FY90-8, FY91-15, FY92-25) interim systems for urgent fielding to Central Command; (3) A System Improvement Phase to design, fabricate and test the NBCRS that will satisfy all ROC requirements; (4) Full Rate Production Phase to produce the improved NBCRS for world wide fielding. As a result of Operation Desert Storm, the German government donated 60 German NBCRS to the United States Government. Fifty systems were fielded with the Army

PERFORMANCE

Office of Project Manager

Above 90% Equipment Readiness Rate. Won high praise from soldiers and commanders.

POINT OF CONTACT:

ATTN: AMCPM-NN

Aberdeen Proving Ground, MD 21010

DSN 584-2566

CONTRACTORS:

Thyssen Henschel of the Federal Republic of Germany General Dynamics Land Systems (GDLS) (Detroit, MI) Fielded 1 Concept Evel DEM/VAL fech Base



MOHAWK SURVEILLANCE SYSTEM

MISSION:

combat aircraft equipped with Side Looking Airborne Radar (SLAR) and photographic systems. Radar data is data linked to ground terminals for near real time display. The OV-1D Mohawk is assigned to the Military Intelligence Battalion (Aerial Exploitation), Military Intelligence Brigade (Combat Electronic Warfare The OV-1D Mohawk radar surveillance system provides Corps commanders location and moving target data on first and second echelon units during daylight, darkness and in near all weather conditions allowing tactical commanders to monitor threat disposition and movement. The OV-1D Mohawk is a two place, twin turboprop. intelligence (CEWI)) at Corps.

210 kts Cruise speed:

CHARACTERISTICS:

18,587 lbs 2,129 lbs 4.0 hrs. Mission weight:

Endurance: Payload:

820 naut mi

FOREIGN COUNTERPART:

Max range:

Armament: None

STATUS: PROGRAM PERFORMANCE IN SWA:

British ASTOR (airborne radar on Pilatus Britten-Norman Defender aircraft), French HORIZON (airborne radar on Aerospatiale Super Puma helicopter).

Fielding of the OV-1D Mohawk surveillance system was completed in 1987. The OV-1D Mohawk fleet has begun a phased drawdown to full retirement by FY97 when the Joint Surveillance Target Attack Radar System

(Joint STARS) will fulfill the radar mission for the Army.

25 OV-1D Mohawk aircraft with SLAR systems assigned to two Military Intelligence Battalions (Aerial Exploitation) successfully deployed to SWA and supported the Army's VII Corps, XVIII Airborne Corps and Coalition forces during Operations Desert Shield and Desert Storm in 1990/1991. Overall system readiness was over 90% and the SLAR performance was characterized as extremely effective.

POINT OF CONTACT:

Product Manager AN/UPD-7

SFAE-IEW-RD-UP

Fort Monmouth, N.J. 07703-5000

CONTRACTORS:

Motorola, Incorporated, Scottsdale, AZ (airborne radar, data link and ground station) Grumman Aerospace, Stuart, FL (aircraft and integration)

Fielded Ž Concept Evel DEM/VAL Tech Bose

QUICKFIX

MISSION:

17A communications jammer and airborne self-protection equipment mounted in a modified UH-60A helicopter. Quickfix systems interoperate with each other and Trailblazer in a netted configuration for DF purposes. Advanced Quickfix, an element of the Intelligence Electronic Warfare Common Sensor (IEWCS) program, interoperates with other elements of the IEWCS, the Ground Based Common Sensor - Heavy and Light in order to acquire and locate targets beyond the Forward Line of Troops. Advanced Quickfix will transmit situation development information to the Technical Control and Analysis Element (TCAE) of the All Source Analysis System (ASAS) and targeting information will be transmitted through the TACFIRE system to their respective Quickfix is a tactical heliborne communications intercept, direction finding (DF) and electronic countermeasures system. Quickfix consists of: AN/ALQ-151 intercept and DF mission equipment, AN/TLQ-

CHARACTERISTICS:

Advanced Quickflx 675 naut mi/4.8 hrs 22,000/3,978 THOUTHOUTH THOUTHOUTH EH-60A (4) 128 kts 266 naut mi/2.0 hrs 6,500/2,130 EH-60A (4) VAF,UFF 37 kts Electronics Countermeasures (jam): Mission / Payload Weight (lbs): Maximum Range / Endurance: Intercept, Locate (DF): Aircraft (Crew): Cruise Speed:

FOREIGN COUNTERPART:

The Soviet-developed technology consists of an extensive fleet of dedicated MI-8 HIP J / HIP K electronic warfare helicopters. The UK, France and other nations also have a heliborne electronic warfare capability.

PROGRAM STATUS:

approved on 6 Sep 91 that will evolve Quickfix into Advanced Quickfix. Advanced Quickfix will be built with an "open systems architecture" and will use the common sensor subsystems of the Intelligence and Quickfix has been fielded and Advanced Quickfix is under development. A Materiel Change (MC) was Electronic Warfare (IEW) family of common sensors.

PERFORMANCE IN SWA:

POINT OF CONTACT:

Quickfix was one of the few IEW systems able to keep up with the pace of the M1 equipped forces.
PM Signals Warfare
Vint Hill Farms Station

Warrenton, VA 22186


CONTRACTORS:

ELECTROSPACE Systems Inc. (Richardson, TX) Sikorsky Aircraft (Stratford, CT) IBM Corp. (Owego, NY) Chrysler Technologies Airborne Systems (Wa∞, TX)

Magnavox (Fort Wayne, IN)
Motorola Inc. (Scottsdale, AZ)
Sanders/AEL Jt Veriture (Hudson, NH)

Teach Base Concept Port DBA/VA BAD Preduct





GUARDRAIL

MISSION:

applications include follow-on force attack, contingency, counterinsurgency and counterdrug operations. Guardrail systems currently in active Army service include the Guardrail V (RU-21H aircraft), the Improved Guardrail V (RC-12H aircraft), the Guardrail Common Sensor Minus (RC-12H aircraft) and the Guardrail Common Sensor (RC-12H aircraft). corps and division commanders with targetable information to influence the enemy's decision cycle. Guardrail To provide fixed wing communication and electronic emmiter intercept and direction finding system.

CHARACTERISTICS:

16,000 /2,000 lbs 250 knots 5(+) hours 1,200 naut miles **RC-12K** 14,200 /1,600 lbs 200 knots 5(+) hours 1,200 naut miles RC-12D/H 10,200/1,126 lbs 1,000 naut miles 176 knots RU-21H 4.0 hours Mission Weight/Payload: Maximum Range: Cruise Speed: Endurance:

Numerous countries possess airborne electronic warfare systems, but none obtain the direction finding accuracy of the Guardrail system using multiple aircraft.

PROGRAM STATUS

FOREIGN COUNTERPART:

provide oustanding support to INSCOM, XVIII and III Corps. Two of these systems possess a remote relay capability, which allows forward deployment of the aircraft while the ground processing facility remains in CONUS. Two other GRCS systems are in Engineering and Manufacturing Development, are transitioning into production and will be fielded in FY93 and FY95. A remote relay capability for the GRCS system is also under development. Intelligence information is passed to users via the Commanders Tactical Terminal. and direction finding capability, and a communication high accuracy airborne location system (CHAALS). The first GRCS system was fielded to Europe in 1991 - both KGRV systems previously there have been deployed to the CONUS for modification. GRCS(Minus) was fielded to Korea in 1988. Guardrail V systems continue to Guardrail Common Sensor (GRCS), combines the Improved Guardrail V (IGRV) Communication Intelligence (COMINT) sensor package with the Advanced Quicklook electronics signals (ELINT) intercept, classification,

Three Guardrail units deployed to Saudia Arabia and provided outstanding support during. Operation Desert Shield/Storm. VII Corps' organic IGRV unit supported VII Corps operations, while XVIII ABN Corps was supported by its organic GRV unit and V Corps' IGRV unit from Germany.

POINT OF CONTACT:

PERFORMANCE IN SWA:

ATTN: SFAE-IEW-EW Ft. Monmouth, NJ 07703-5000 PEO-IEW: PM Guardrail

IBM (Oswego, NY ESCO (St. Louis, MO)

Beech Aircraft (Wichita, KS)

Fjelded Concept five DBM/VAL | IND Nech Bos

CONTRACTORS:

ESL, Inc. (Sunnyvale, CA) UNISYS (Saft Lake City, UT)



ARMORED COMBAT EARTHMOVER (ACE)

MISSION:

survivability missions in support of forces in both offensive and defensive operations. The ACE can prepare defilade and breach berms and perform limited countermobility tasks, such as preparing anti-tank ditches and hauling obstacle materials. The M9 ACE engine, drive train and driver's compartment are laid out in the rear of the vehicle, while the front is occupied by an 8.7 cubic yard scraper bowl, apron and attached dozer blade. Its unique hydropneumatic suspension The M9 ACE is a highly mobile, fully tracked armored earthmover capable of performing mobility, countermobility and protected positions for guns, tanks and other critical battlefield systems. It can prepare combat roads, remove roadblocks, system has eight high-pressure hydraulic rotary actuators which connect to the roadwheel stations assuring a smooth ride during high-speed travel through the use of shock-absorbing accumulators.

CHARACTERISTICS: Weight:

36,000 lbs (net); 54,000 lbs (ballasted) Swim capability: 20 ft 5 in

Length: 20 ft 5 in Height: 8 ft 9 in

Cummins V903, 295 hp

Air transportable: C130, C141, C5A
Bowl capacity: 8.7 cu yds

Speed: 30 mph (max, road travel)
Suspension: Hydropneumatic, w/rotary actuators

FOREIGN

COUNTERPART:

There is no vehicle similar to the M9 ACE.

fransmission: Clark, 6 forward, 2 reverse speeds

1 operator

Engine: Crew sìze:

PROGRAM STATUS: The ME

several vehicle improvements has been accelerated. These include a fix to a battery overheating problem, removable 219 of the 448 vehicles produced have been fielded to Combat Engineer units in CONUS and USAREUR. An additional 30 vehicles have been loaned to the US Marine Corps. As a result of the Operation Desert Storm experience, evaluation of The M9 ACE will complete production in 4th Quarter FY92 and is midway through worldwide fielding. As of January 1992, cutting edge with ripper teeth, steel roadwheels and microclimate cooling.

PERFORMANCE

available to conduct the mission, and that it performed adequately. The M9 ACE proved itself through superior mobility and The ACE was used prior to and in the early stages of the ground war to breach Iraqi berms. All units stated that the ACE was crew protection, although the D7 bulldozer remains a better pure digger when mobility and protection are not required.

POINT OF

CONTACT: Product Manager, M9 Armored Combat Earthmover ATTN: AMCPM-M9


Warren, MI 48397-5000

DSN 786-6635, Comm 313-574-6635

CONTRACTORS: Production - BMY Corporation (York, PA)

ork, PA) Systems Technical Support - AM General Corporation (Livonia, MI)

Non-times Company that DELIVIAL SIND Preduct FIEIGGGG



RECOVERY VEHICLE

2	2	
()
i	i)
Ì	1)
3		į
•		

the primary recovery vehicle in the Army inventory for M2/M3 Bradley Fighting Vehicles, M60 series tanks, and heavy self-propelled artillery. An improved M88A1 is currently under development, and is being designed operations for battlefield recovery and evacuation of tanks and other tracked combat vehicles. The M88A1 is The M88A1 Recovery Vehicle is a fult-tracked armored vehicle designed for hoisting, winching and towing

CHARACTERISTICS:

specifically for towing the Abrams tank.

Height: Length: Width:

air-cooled diesel engine with 3 speed automatic 12-cyl, 750 hp

Power Train:

325 inches 135 inches 123 inches

56 tons 30 mph One .50 cal machine gun Top Speed: Weight:

transmission 90,000 lbs 25 tons 300 miles

Armament:

Cruising Range: Draw Bar Pull: Boom Capacity:

FOREIGN COUNTERPART:

The Soviets have historically based recovery vehicles on existing chassis. The most current is the BREM-1

based on a T-72 chassis. T-54, T-55-T, and JSU-T recovery vehicles are still in the Soviet inventory.

PERFORMANCE IN SWA:

PROGRAM STATUS:

Approximately 2500 M88A1s are fielded to date. An improved M89A1 is currently under development

Technical and Operational Testing of prototypes will begin in June 1992.

As a result of the military operations in SWA, it was determined that the current M88A1 Recovery Vehicle lacked the tractive power to safely tow the 65+ ton M1A1 Abrams tank without a second M88A1 or M1A1 tank to act as a brake vehicle.

POINT OF CONTACT:


Program Manager Improved Recovery Vehicle US Army Tank-Automotive Command Warren, MI 48397-5000

CONTRACTORS:

GMC, Detroit Diesel Allison Div. (Indianapolis, IN) BMY Company (York, PA)

Teledyne Continental Motors (Muskegon, MI) Goodyear Tire (St. Mary's, OK) Standard Products (Port Clinton, OH) Firestone Tire (Noblesville, IN)

Buckeye Steel Casting (Columbus, OH) Maynard Steel Casting (Milwaukee, WI) Bata Engineering (Ontario, Canada) Ferguson Gear (Gastonia, NC) Berwick Forge (Berwick, PA) Adviondack (Watervliet, NY)



COMBAT SERVICE SUPPORT

The Combat Service Support mission area relates to providing tactical commanders with supply, providing tactical commanders with supply, maintenance, personnel and administration, civil affairs, medical, transportation, and other services. In terms of equipment modernization of the force, this handbook includes those major items that the Army is developing to improve its tactical transportation capability.

		DEVELOPMENT			
Tech Base	Concept Development	DEM/VAL	EMD	Production	Fielded
Artillery Rearm				Tactical Quiet Generators	5 Ton Truck
MOQUIE				HETS	немтт
Logistics Over-The-Shore				Palletized Load System	Deployable Medical
Combat Casualty				FMTV	Systems Support
Care				Reverse Osmosis Water Puridication Unit	Vessel
				Integrated Family Test Equipment	



COMBAT CASUALTY CARE

COMBAT SERVICE SUPPORT - TECH BASE

OVERVIEW:

The goal of the Army Technology Base program in Combat Service Support focuses on exploiting Non-Developmental Items (NDI) to improve combat power through increased logistics capabilities, decreased resource requirements (e.g., O&S costs), and enhanced soldier and civilian performance. This includes technologies to improve the efficiency and effectiveness of tasks such as arming, fueling, manning and

ARTILLERY REARM MODULE (ARM):

This program demonstrates rearm technologies capable of enhancing and automating the handling of projectiles and propellants which can be configured to fit a variety of vehicles. The ARM will provide rapid, automated ammunition handling capable of supporting resupply rates up to 1,000 complete rounds per artillery weapon per day, reduce numbers of resupply personnel and significantly increase crew survivability

> LOGISTICS OVER-THE-SHORE (LOTS):

and outsized equipment, defeating shallow gradient environments and facilitating causeway system emplacement operations over shallow beaches. The High Sea State Container Transfer System (HISEACOTS) will be developed and demonstrated to expand a ship's operational capability to transfer cargo. The HISEACOTS will provide for automated container discharge and handling in heavy seas (i.e., sea The Pontoon Air Cushion Kit (PACK) is a portable air cushion which will provide increased mobility and enhanced amphibious capability for Logistics Over-the-Shore (LOTS) by providing a means of lift for heavy state 3 to 4), resolving a major LOTS problem while increasing safety and productivity of cargo offloading by 100% and decreasing manpower requirements and ship offloading times by 50%

COMBAT CASUALTY

Important features of this program will include technologies and techniques supporting far-forward treatment, individual sustainment (self-aid devices and techniques) compounds to reduce the seventy of An example of far-forward treatment is the use of Hypertonic Saline Dextran (HSD) solution to replace intravascular volume lost during hemorrhage with only 250 ml of HSD as compared to 3000 ml of conventional fluid therapy. This technology will significantly reduce the medical logistics burden and enable ballistic, thermal and laser injuries, blood replacements and substitutes and miniature and filmless x-rays. Improvement in combat casualty care will save lives and expedite the return of soldiers to the battle. far-forward treatment of shock





TACTICAL QUIET GENERATORS (TQG)

MISSION:

The Tactical Quiet Generator (TQG) Set is the new DOD standard family of power sources that meets the users' current and future Altitude Electromagnetic Pulse (HAEMP) protected electrical power systems for command post, C3I systems, weapon systems, logistics and maintenance functions and other battlefield support equipment. The new power generators will counter threat forces requirements. The new 3kW-200kW TQG provides DOD with more reliable, quieter, lighter weight, single fuel, and improved Highwhich have the capability of locating critical targets by detecting the high aural and thermal signatures.

CHARACTERISTICS:

	Current Fieet	
	Performance	TOG Bequirements
Aural Signature:	79-85 dBA @25M	70 dBA @7M
Fuel:	GAS/DSL/JP4	JP8/DSL
Environment:	All Climatic Conditions	3 of 4 Climatic Conditions
KW:	1.5-200	3-100
Hertz:	DC/50/60/400	60, 50/60, 400
HAEMP:	2	Yes
IR Suppressed:	W/Nets	W/Nets
Reliability (MTBOMF)	140-408 hrs	500/600 hrs
Standard Voltage Connections:	Yes	Yes
Slave Recentacle:	Ordnance	NATO

PROGRAM STATUS: TQG contract award for 5kW-60k

TQG contract award for 5kW-60kW TQG sets was made in August 1988. During April 1989, a contract was awarded for the 3kW TQG. The First United Equipped (FUE) for the TQG sets is scheduled for January 1994.

POINT OF CONTACT: DOD Project Manager-Mobile Power 7500 Baklick Road

Department of the Army
HO, US Army Troop Support Command
4300 Goodfellow Boulevard
St. Louis, MO 63120-1798


CONTRACTORS:


Libby Corporation (Kansas City, MO)

Springfield, VA 22150-3107

Dynamics Corporation (Fermont Division) (Bridgeport, CT)

Federal Prison Industries





HEAVY EQUIPMENT TRANSPORTER SYSTEM (HETS)

MISSION:

poor durability when overloaded beyond 60 tons. The new HETS will transport 70 ton payloads, primarily M1 series tanks. Operates on OCONUS highways; on CONUS highways with permits. System will have automatically steerable The HETS is required to transport, deploy and evacuate the M1 Tank and other tracked vehicles on highway, unimproved roads and cross-country. The HETS consists of the M1070 Truck Tractor and M1000 Semitrailer, 70 ton. Each being procured under separate acquisition programs. Current HETS (M911/M746 with M747) demonstrates very axles and load leveling hydraulic suspension on semitrailer. The tractor will have front and rear axle steering with central tire inflation system and cab space for 5 crewmen.

CHARACTERISTICS:

40-45 mph 300 miles Range: Speed:

with 70 ton payload:

95% on road C-5 aircraft Transport: Mobility:

3,000 MMBHMF for both tractor and trailer

TATRA-813(tractor)/ChMZAP-5212 (trailer) (Soviet-developed) PAK:

Payload:

COUNTERPART:

FOREIGN

Speed: Engine:

with 60 ton payload: 10 km/h 40 km/h

TRH 350 (France)

65 km/h 55 Ton

Diesel

The HETS is currently in low rate initial production. The HETS is a Non-developmental Item (NDI) program. The HETS is required to meet the Army's critical need for a 70 ton tank transporter capability in support of fielding the M1 Series Tank. The current M1A1 Tank weighs over 64 tons, overloading the current HET (M911/M747) to the extent that readiness is below acceptable levels. PROGRAM STATUS:

PERFORMANCE IN SWA:

The current HETS (M911/M747) saved wear and tear on tanks, Bradleys and self-propelled howitzers. The M911/M747 was overloaded by the M1A1 tank, was limited to roads, speed reduced to 15mph. The HETS (M1070/M1000) was not

available for SWA.

PM-Heavy Tactical Vehicles ATTN: AMCPM-TVH POINT OF CONTACT:

Warren, MI 48397-5000

Southwest Mobile Systems (St. Louis, MO) (Trailer)

Warren, MI 48397-5000

ATTN: SFAE-CS

Oshkosh (Oshkosh, WI) (Tractor) CONTRACTORS:

Production TOUR | DEMANAL | BAD





PALLETIZED LOAD SYSTEM (PLS)

MISSION:

integral self-load/unload capability, a 16.5 ton trailer, and flatracks (demountable cargo beds). Vehicles can also modernized, highly mobile organizations. The PLS is a 16.5 ton tactical vehicle composed of a prime mover with selectively replace or augment the standard tactical vehicles currently authorized in such units as Field Antillery and Transportation. Flatrack will be interoperable with United Kingdom and Germany flatracks. PLS is required for improved ammunition transport with greater efficiencies and productivity in the supply distribution role. PLS reduces dedicated personnel, Materials Handing Equipment (MHE), line haul and heavy cargo transport vehicle The Palletized Load System (PLS) will be deployed in the Army's Maneuver Oriented Ammunition Distribution System (MOADS). The PLS will perform line haul, local haul, unit resupply, and other missions in the support of be equipped with material handing equipment and/or winch. The PLS prime movers with associated trailers will equirements in the current ammunition distribution system.

Fruck payload, tons: CHARACTERISTICS:

Number of Driven Wheels: Transmission:

Range, integral fuel at

8x20 Diesel 16.5 16.5 Flatrack dimensions, feet: Trailer payload, tons:

Engine Type: FOREIGN

COUNTERPART:

255 miles **Gross Combined Weight:**

United Kingdom - Demountable Rack Off-Loading and Pick-Up System (DROPS):

Diesel Engine Type: Payload:

350 Horsepower:

ZF Transmission 8 Transmission:

Number of Driven Wheels:

PLS is currently in low rate initial production, the contract was signed in September 1990. PLS is a Nondevelopmental Item (NDI) program. The system is scheduled to undergo Production Qualification Testing (PQT) in FY92. The flatrack design is being upgraded to allow for its transportation as an International Standards Organization (ISO) container. PROGRAM STATUS:

POINT OF CONTACT:

ATTN: SFAE-CS TACOM PM-Heavy Tactical Vehicles

Warren, MI 48397-5000 ATTN: AMCPN-TVH

Warren, MI 48397-5000

CONTRACTORS:

Oshkosh (Oshkosh, WI)

Production BOT BYELL DEMAYAL



FAMILY OF MEDIUM TACTICAL VEHICLES (FMTV)

MISSION:

has a 2 1/2 ton payload capacity consisting of cargo and van model variants. The Medium Tactical Vehicle (MTV) has a 5 The FMTV will perform line haul, local haul, unit mobility, unit resupply and other missions in combat, combat support, and combat service support units. Vehicles will operate worldwide on primary and secondary roads and trails. The FMTV will The FMTV consists of a family of vehicles based on a common truck chassis. The Light Medium Tactical Vehicle (LMTV) ton payload capacity and consists of the following models: cargo with and without material handling equipment (MHE), tractor, wrecker, and dump truck (van and tanker models to be developed concurrent with production of other models). replace overaged and maintenance intensive trucks currently in the fleet.

CHARACTERISTICS:

ISTICS:	LMTV cargo	MTV cargo
Payload (lbs)	2000	10000
Towed Load (lbs)	7500	21000
Engine:	Diesel	Diesel
Transmission:	Automatic	Automatic
Horsepower:	225	290
Drive:	4×4	9x9

FOREIGN LMTV MTV
COUNTERPARTS: Soviet: ZIL-131 URAL-375
GAZ-66 6A2 9301

 ZIL-157
 KA2 4430 (same as 5 Ton)

 Italy:
 Fiat, 75PM
 Fiat 6602

 Germany:
 Urimog U110OL
 Mercedes 1017A, MAN 5 Ton

 France:
 RVI Saviem TRM-2000
 RVI TRM-4000

 Spain:
 Santana 2000
 Peguso 3050

Austria: Steyr 630 M3 Steyr 1291M

PROGRAM STATUS: The FMTV production contract was awarded on 11 October 1991 and the program is currently in the Low Rate Initial Production (LRIP) phase and will be limited to 150 per month for the first two program years.

U.S. Army Tank Automotive Command POINT OF CONTACT: PM - Medium Tactical Vehicles ATTN: SFAE-S-TVM


Warren, MI 48397

Narren, MI 48397

Stewart and Stevenson Services, Inc. (Houston, TX) Engine: Caterpillar, Inc. (Peoria, IL)

CONTRACTORS:

Tech has Connect to the Production region



REVERSE OSMOSIS WATER PURIFICATION UNIT (ROWPU)

MISSION:

The 3000 Gallons Per Hour (GPH) ROWPU provides fresh drinking water worldwide. The ROWPU purifies fresh, saline, brackish, as well as nuclear, biological, and chemical (NBC) contaminated water. It is used in Echelon Above Divisions.

CHARACTERISTICS:

chemicals, tools, distribution and raw water pumps, a 60KW generator set and a M871 semitrailer. This equipment is designed to clarification, RO, and NBC post treatment subsystems, along with the process control station, is enclosed in a 8-foot wide by 8 operate 20 hours a day at a production rate equivalent to 3000 gallons per hour of fresh water and 2000 gallons per hour of sea water. This unit is transportable by two C-230s, one C-141, rail, ship, or standard military vehicles. The ROWPU replaces the subsystem, clarification subsystem, reverse osmosis (RO) subsystem, NBC post treatment subsystem, chemical feed foot-high by 20-foot long container. Support system components of the system include collapsible water storage tanks, hoses, The 3000 GPH ROWPU represents state-of-the-art technology in water purification equipment. The unit consists of a raw water subsystem, process control station, piping, fittings, and a storage area for pumps and operating supplies. The chemical feed, existing equipment which can purify only fresh water.

COUNTERPARTS:

they use distillation process equipment, called OPS, incorporated into their current standard desalinization equipment. Japan The Soviets have developed two pieces of equipment to accomplish the task for which the United States has developed the ROWPU. To purify fresh water and NBC contaminated water, they currently use the MAFS-3. To purify brackish or saline water, offers similar commercial equipment of the same size and capacity.

PROGRAM STATUS:

The 3000 GPH ROWPU is in production. First Article Test was approved and a competition Technical Data Package was accepted on 10 JAN 92.

PERFORMANCE

The 3000 GPH ROWPU was a valuable resource to the U.S. Army water production capability in Operation Desert Sheild and Desert Storm. It provided a high level of mobility, responsiveness, and water production capability.

U.S. Army Troop Support Command POINT OF CONTACT:


4300 Goodfellow Boulevard St. Louis, MO 63120-1798 ATTN: AMCPM-PWL

CONTRACTORS:

Aqua Chem, Inc. (Milwaukee, WI)

Production 100 PERSON







INTEGRATED FAMILY OF TEST EQUIPMENT (IFTE)

MISSION:

electronics, ensuring combat readiness for the 1990's and beyond. It allows the isolation of weapon systems faults to the electronic Line Replaceable Units (IRUs) at Direct Support (DS) areas of quick turnaround and minimum spares pipeline, isolation of faults in Shop Replaceable Units (SRUs) at General Support (GS) areas and The Integrated Family of Test Equipment (IFTE) supports weapon systems state-of-the art technology depots, and adapts to and accepts new weapon systems.

CHARACTERISTICS:

and the documentation an operator uses to perform test operations. The non-tactical systems: the Automatic Test Set Support Environment (ATSE) and the CEE feature the software system that operates on Sun interrelated systems that provide generic Automatic Test Equipment (ATE) capability through all levels of the Army maintenance structure. Two tactical systems: the Contact Test Set (CTS) and the Base Shop Test Facility (BSTF) are capable of electronic ATE support, Electronic Technical Manuals (ETM), and Electro-Optical (EO) capability will be fielded in FY 94). The CTS is a man portable ATE system that augments supported systems DIT/BITE and isolates weapon systems failure to the appropriate LIUs. The BSTF consists of the Base Shop Test Station (BSTS), in a 5-ton truck mounted S-280 shelter, plus another 5-ton truck mounted S-280 shelter for Test Program Sets (TPS) storage; powered by 60KW generator sets. It will be positioned at DS/GS levels to fault diagnose evacuated LRUs to the Shop Replaceable Line Unit (SRU) level. The TPS is the software program the Interface Connecting Device (ICD) to connect the UUT to the BSTS or Commercial Equivalent Equipment (CEE), workstations and develop 65% of the software portion of the TPS. The CEE is a non-ruggedized equivalent of the IFTE is a modular Test, Measurement and Diagnostic Equipment (TMDE) system which consists of four BSTE that is used in Special Repair Activity (SRA)/depots.

FOREIGN COUNTERPART:

There is no known counterpart to the IFTE

PROGRAM STATUS:

Operational Test and Evaluation (IOTE) has been completed. A Milestone IIIb Decision Review for Full Scale The ESTF and CTS are in the Low Rate Initial Production Phase (LRIP) which started in March 89. Initial Production will occur in Jan 92. First Unit Equipped (FUE) for the BSTF and CTS will take place in FY92. Electro-Optical capability will be added to IFTE in FY94.


POINT OF CONTACT:

Redstone Arsenal, AL 35898-5400 IFTE Product Manager

CONTRACTORS:

Grumman Aerospace Corp, Electronic Systems Division (Great River, NY)

Production Î ROOM ING DIRAN



5 TON TRUCK

powered, 6 wheel drive tactical vehicle. The M939 series is improved over the old M809 series with new commercial components such as engine, transmission and brakes. It comes in six body styles: cargo, dump, tractor, wrecker, van, and long wheelbase cargo. The FY 86-90 mulityear procurement provides M939A2 series trucks which include a new The 5 ton trucks meet the requirement for general cargo transport, unit mobility, and special purpose use. It is a diesel lightweight, fuel efficient engine and a central tire inflation system for improved mobility in difficult terrain. It supports the fielding of many other systems such as Patriot, DEPMEDS, Apache, and MLRS.

MISSION:

CHARACTERISTICS: Body Styles:

10,000 Payload (lbs):

21,000 Towed Load (lbs):

Automatic Diesel Fransmission: Engine:

Horsepower:

Soviet: COUNTERPART: FOREIGN

Drive:

Fiat 6602 Italy: URAL 375

France: KAZ-4430 GAZ-4301

RVI (Saviem) TRM-4000

Peguso 3050 Steyr 1291M

Austria: Spain: Mercedes 1017A

Germany:

MAN 5 Ton

PROGRAM STATUS: Vehicle production for the US Army has been completed. BMY is currently producing vehicles in support of Foreign

Military Sales (FMS) cases with other nations.

PERFORMANCE

IN SWA:

POINT OF CONTACT:

The A2 Series trucks performed admirably in Operation Desert Storm. The central tire inflation system provided greatly

enhanced off road mobility in desert terrain.

U.S. Army Tank Automotive Command ATTN: SFAE-CS PM - Medium Tactical Vehicles

Warren, MI 48397 ATTN: SFAE-CS-TVM

Warren, MI 48397

BMY (York, PA) CONTRACTORS:

Engine: Cummins Engine Co. (Columbus, IN)

Fielded 1 DEMOVAL Days Prod -

	~

×	
Ž	
7	
Sa Ja	
it.	
19	
Ġ.	
90	
=	
8	
9	
8	
M M	
>	
3	
₹	
_	

HEAVY EXPANDED MOBILITY TACTICAL TRUCK (HEMTT)

MISSION:

The HEMTT vehicles are used for resupply, refueling, and recovery operations. Doctrine states that support for combat elements should occur as far forward as possible. The HEMTT family is assigned to Armor, Field Artillery, Engineer, Missile, Air Defense Artillery, Aviation and Cavalry units worldwide. There are five configurations, a light cargo vehicle with crane (M977), a 2500 gal fuel tanker (M978), a tractor version (M983), a wrecker (M984) and a heavy cargo vehicle with material handling crane (M985).

CHARACTERISTICS:

Diesel 445 8x8 96 in 13 in
Fording dooth:

SAURER D33OMF
COUNTERPART:
FOREIGN

-T:	SAURER D33OMF	ZIL-135	MAZ-7310	MANLKW
	(SSIMS)	(SOVIET)	(SOVIET)	(GERMAN)
Payload:	10 ton	8-10 ton	16 ton	10 ton
Speed:	45 mph	40 mph	40 mph	90km/h
Engine:	Diesel	Gas	Diesel	Diesel
Horsepower:		300	520	320
Drive:	9x9	8x8	8×8	8×8

PROGRAM STATUS:

The HEMTT is a fielded system. Direct Army production completed as of Oct 90 (11,492). A total of 12,638 vehicles have been built of the 13,286 ordered. Production continues at 4/day for Foreign Military Sales (FMS) and dedicated National Guard and Army Reserve requirements. An additional 177 HEMTTs are expected to be purchased for Army using Operation Desert Storm Supplemental II funds.

PERFORMANCE

IN SWA:

The HEMTT displayed excellent cross-country mobility; the vehicles operated in all weather conditions over all types of terrain; made the turning movement by VII Corps possible.

POINT OF CONTACT: PM-Heavy Tactical Vehicles

TACOM ATTN: SFAE-CS

Warren, MI 48397-5000

ATTN: AMCPM-TVH

Warren, MI 48397-5000

CONTRACTORS: Oshkosh (Oshkosh, WI)

Tech base Concept five DBAVAA BASD Predact Fielded





DEPLOYABLE MEDICAL SYSTEMS (DEPMEDS)

MISSION:

hospitals, ranging from forward deployed Mobile Army Surgical Hospital (MASH) units in the combat zone to General medical technology and equipment, expendable supplies, and major non-medical support equipment power units, Tent all climatic conditions. The fielding of the 129 Army hospital sets will eliminate serious shortages of field medical equipment The DEPMEDS family of equipment is Department of Defense (DOD) approved equipment packaged into standardized Hospitals in the Communications Zone (COMMZ). Each is composed of different configurations of standard modules such as operating rooms, laboratories, X-ray units and wards. The DEPMEDS hospital sets standardize the use of the latest Standard modules improve medical unit mobility and patient distribution densities. The hospital sets can be deployed under and achieve major advances in equipping the Total Army. Gaining units will receive their DEPMEDS equipment in one package under the Total Package Fielding concept. This is the largest Total Package Fielding effort ever undertaken by the modules for use by all services to equip their theater of operations deployable hospitals. There are seven types of Army Extendable Modular Personnel (TEMPER) Tents, tactical shelters, heating and air conditioning throughout the DOD. Army Medical Department.

CHARACTERISTICS:

System characteristics vary by type of hospital set. All provide adequate but austere care, are maintainable and relocatable, have modular configuration and quad-service compatibility, and are transportable by strategic air.

There is no known counterpart to DEPMEDS.

PROGRAM STATUS:

COUNTERPART:

FOREIGN

Sixty-nine hospitals fielded, as of 30 Sep 91, for a total of 23,460 Beds and 57 Minimum Essential Equipment for Training The DOD Medical Standardization Board insures compatibility among the Services. The Army program is managed by the DEPMEDS Project Manager, operating under the authority of the Secretary of the Army. Fielding began in the 4QFY87.

Performance of DEPMEDS equipped hospitals worked well in SWA. Lessons learned from both unit/materiel deploying and operation prospective are being used to rebuild/replenish units, to strengthen readiness and training capabilities commensurate with the unit mission and authorization.

PERFORMANCE IN SWA:

Falls Church, VA 22041 5109 Leesburg Pike PM DEPMEDS


POINT OF CONTACT:

4Q, U.S. Army Troop Support Command 4300 Goodfellow Boulevard St. Louis, MO 63120-1798

CONTRACTORS:

A large number of contractors are involved in providing the 3,400 plus medical and non-medical components of DEPMEDS. These components are assembled into modules and hospital sets by the Defense Logistics Agency, Defense Depot, Fielded





LOGISTICS SUPPORT VESSEL (LSV)

to underdeveloped areas along coastlines and on inland waterways. The LSV can discharge sea going roll-on/roll-off ships in The LSV performs inter-theater level haul of military equipment to support troop deployment, relocation and resupply operations support of Logistics Over the Shore (LOTS) operations.

MISSION:

CHARACTERISTICS: Displacement: 4,199 long tons Full load speed: 11 kts

Range: 5,500 nm Cargo Capacity: 2,000 short tons

Crew: 30 Length: 272 ft

Beam: 60 ft

FOREIGN COUNTERPARTS:

The LSV was developed by industry, consequently, similar vessels are found in commercial and foreign military applications.

The LSV is currently fielded. The Army's requirement for five LSV was procured, and the last vessel was delivered in December PROGRAM STATUS:

1990. All five ships are on station and fully operational.

PERFORMANCE IN SWA:

this type of vessel. LSV were also used to transport Air Force munitions and airbase defense tanks to ports nearest the airlield The self-deployment of LSV to Southwest Asia, carrying much needed containers and material handling equipment was a first for where they were stored and used. Army watercraft moved over 2,000 pieces of equipment for the Army and Marines.

POINT OF CONTACT: U.S. Army Troop Support Command

ATTN: AMCSTR-PD

4300 Goodfellow Boulevard

St. Louis, MO 63120-1798

CONTRACTORS: Trinity Marine Group, Inc. (Gulfport, MS)

COMMAND, CONTROL, AND COMMUNICATIONS (C3)

to combat units. In order for a commander to effectively control tactical elements, the area includes resources for providing effective command and control, automation, and communications support The systems included in this mission area provide that capability. Without them, the Army would be as commander must know where they are located and must have a means by which to talk to them even in an enemy electronic countermeasure environment. helpless as a person without a nervous system Control, Communications (C3) mission Command, Tactical The

		DEVELOPMENT			
Tech Base	Concept Development	DEM/VAL	EMD	Production	Fielded
Airland Battle Management		Combat Service Support Control	Army Distribution System		SINCGARS
Survivable Adaptive		System Forward Area Air	Standardized Integrated Command Post System		Equipment
		Defense Command,	All Courses Application		GPS
Multipand Multimode Radio		Intelligence	All Source Arialysis System		Military Satellite
		Mane Iver Control	Advanced Field Artillery		Communications
		System	Tactical Data System		Communication
					System Control Element
					Digital Transmission Assemblages
					Circuit Switch and Message Switch

AIRLAND BATTLE MANAGEMENT

SURVIVABLE ADAPTIVE SYSTEM TECHNOLOGY

COMMAND

CONTROL and COMMUNICATION (C3) - TECH BASE

OVERVIEW:

of the Army Tactical Command and Control System (ATCCS). The Army will continue to modify and upgrade ATCCS capabilities by using the information technologies available from the commercial market as well as from Significant strides are being made to introduce automation into the C3. Mission Area through the development government-sponsored R&D. When fully deployed, ATCCS will provide the Army with a survivable and robust system capable of supporting the commander's decision making process.

> AIRLAND BATTLE MANAGEMENT (ALBM):

planning and battle execution monitoring decision and application prototypes to support the enhancement and evolution of the ATCCS by FY93. It will provide the Commander and his staff automated reasoning capabilities and supervisory tools to manage the large volume of data which must be processed, analyzed, and implemented to yield combat decisions. The integration of artificial intelligence, simulation modeling, soldiermachine interface, and distribution data based technologies are key to the demonstration. The results will be software packages which will transition to ATCCS. This ATTD has been abbreviated in scope until 1993 at This Advanced Technology Transition Demonstration (ATTD) will demonstrate computer technology-based which time ALBM will become a living testbed/beta site that will assess opportunities for other transitions. System supported: ATCCS upgrades, Force Level Knowledge Systems, and Command & Control Lower

SURVIVABLE ADAPTIVE SYSTEM TECHNOLOGY (SAST):


media data links. SAST will enhance system survivability through emerging communications (wireless Local Area Networks (LANs), high capacity fiber optic backbone LAN, automated gateway) and distributed processing (automated network management, multi-function host capability) to meet some of the objectives of Command and Control (C2) on the move, expanded Command Post dispersion, and compliment Multiple borne of recent lessons learned in Southwest Asia, an early demonstration in FY93 of secure packet-switched wireless LAN (data only) will provide 20Kb/s effective data rate transfer over 10 km range. A follow-on phase in FY95 will demonstrate an EHF wireless LAN capable of 10Mb/s transfer rater over 2 to 10 km with fiber optic This ATTD will demonstrate combat survivable C3 systems consisting of dispersed assets supported by multibackbone handling voice, data, and video. Integration into MSE will also be complete. System supported: Subscriber Equipment (MSE) in providing long-haul/inter-echelon connectivity. With focus on C2 on the move, ATCCS. Future systems will include: Local Area Transport System and Force Level Knowledge System.

CONTROL and COMMUNICATION (C3) - TECH BASE (Con't) COMMAND

MULTIBAND MULTIMODE RADIO (MBMR):

firmware and sofware reconfiguration to meet the dynamic changing requirements of threat, interoperability, and modes of operation. The firmware and software allow the control of electronic counter countermeasure waveforms, data waveforms, signal modulation and demodulation, and interface to ancillary devices. Integration of digital technology, very high speed integrated circuits (VHSIC), millimeter wave/microwave monolithic integrated circuit (MMIC), and signal processing is required. The results of this demonstration will This technology will demonstrate a tactical (HF, VHF, UHF) radio system with an architecture which allows rapid form the baseline for the objective combat net radio and will support the development of the Future Local Area Transport System. It will provide the survivability, reliability, interoperability, and adaptability required for C2. Systems supported: Wide Area Transport System and MSE, SINCGARS upgrades, Objective Combat Net Radio, LAN, and Wide Area and Range Extension Transport Systems.





COMBAT SERVICE SUPPORT CONTROL SYSTEM (CSSCS)

MISSION:

the functions of command, control and resource management. The CSSCS implementation automates the CSS commander and staff with an analysis tool to evaluate CSS information with respect to the force level commander's tactical courses of actions. CSSCS will be organic to CSS units and headquarters staffs within the maneuver brigades, separate brigades, armored cavalry regiments, divisions, Corps and Echelons The Combat Service Support Control System (CSSCS) is a computer software system designed to assist the CS commander and his staff to rapidly collect, store, analyze, and disseminate CSS information to support Above Corps (EAC)

CHARACTERISTICS:

The CSSCS will consist of transportable and lightweight computer units (LCU) procured through the Program Manager (PM) Common Hardware/Software (CHS), shelters provided by PM CHS, Common ATCCS Support Software (CASS), CSSCS-unique software, and any CSSCS unique items identified during development.

FOREIGN COUNTERPART:

Great Britain, Canada, and Australia are monitoring the status of CSSCS development.

PROGRAM STATUS:

five versions. Initial development of the CSSCS software (Versions 1 and 2) began in early 1988 by TRW under the Maneuver Control System (MCS) contract with PM OPTADS. A RFP was released in June 1990 for the Versions 3 and 4 software. In February 1991, TRW was awarded the software development contract for System (ATCCS) capability. Improvements and added capabilities for all echelons will continue in Versions 4 and 5. Version 3 is to be completed and tested by the end of FY93. Version 4 will be completed and tested by these two versions. In FY93, version 3 will provide the Army an integrated Army. Tactical Command & Control The CSSCS is currently in full scale development. Program development has been structured to evolve over the end of FY95. Fielding of the CSSCS is scheduled to begin in April 1994


POINT OF CONTACT:

PM CSSCS ATTN: SFAS-CSSCS Et Belvoir Va 22060

Ft Belvoir, Va 22060


CONTRACTORS:

TRW, Systems Engineering & Development Division (Carson, CA)





FAAD C2 CONTINGENCY/LIGHT FORCES ARCHITECTURE



COMMAND and CONTROL (FAADC2) **FORWARD AREA AIR DEFENSE**

MISSION:

The mission of FAADC2 is to provide an automated means of providing timely target data to FAAD weapons, to developmental computers, displays and printers that are common to the Army Tactical Command and Control System (ATCCS), non developmental ground sensors and the requisite software. The system will be fully integrated with other FAAD elements and the ATTCS. The initially deployed light system will use Single Channel Ground to Air Radio System (SINCGARS) for data transfer while the objective heavy system will use the Army Data Distribution System (ADDS). The system will provide an automated exchange of (Air Defense protect friendly aircraft and to facilitate management of the air battle. The system consists of non Artillery) command information, dissemination and acknowledgement of Air Defense Artillery air battle management date, air track and remote sensors.

CHARACTERISTICS:

The systems consist of multiple subsystems for deployment to various echelons of command. The subsystems are tailored to the functions to be performed and vary in size and complexity from the fire unit processor to the Air Battle Management Operation Center (ABMOC). The fire unit subsystem consists of a simplified, hand held terminal unit weighing approximately 8 pounds with battery, cables, and carring case. The ABMOC is in a standard integrated command post shelter (rigid wall).

FOREIGN COUNTERPART:

None known.

by a contractor integration, assembly and test in 4Q FY92. Government tests are scheduled to begin 1Q FY93 and be completed 3Q FY53. First Unit Equit, 3ed for the light division is scheduled for 4Q FY93. It is currently envisioned that the system will ultimately be fielded to 9 heavy divisions, 5 light special divisions, 2 ACRs, 3 Versions 1 & 2 have completed and successfully passed a laboratory demonstration. Version 3, to be fielded to light forces, is currently under development with a format qualification test scheduled for 3Q FY92, followed Sep Bdes, 4 Corps Hq, 10 - Corps Missile Battalions and 2 training base systems. Fielding will occur between FY93 and FY01. The FAAD C2 system is currently in the engineering and manufacturing development phase. The basic development effort consists primarily of software development, which is being developed incrementally

PROGRAM STATUS:


POINT OF CONTACT:

US ARMY MISSILE COMMAND ATTN: SFAE-FAAD Redstone Arsenal, AL


CONTRACTOR:

TRW Defense System (Redondo Beach, CA)

Tech term Concess DEM/VAL the Preduction Frasted



ANALYST CONSOLE



TACTICAL COMPUTER PROCESSOR

MANEUVER CONTROL SYSTEM (MCS)

Ihrough battalion) automated on-line, near-real-time, systems for planning, coordinating, and controlling tactical operations and for receiving, processing, and displaying the increasing volume the Army Tactical Command and Control Systems (ATTCS). MCS is the force level commander's systems of the other four functional areas (Fire Support, Air Defense, Intelligence/Electronics Maneuver Control System (MCS) provides Army tactical commanders and their staffs (corps The MCS capability continues to expand in pre-planned, time-phased steps toward the objective information system and integrates the maneuver function with the command and control (C2) and variety of tactical command and control information available. MCS software is written in Ada. system in the mid 1990's. Maneuver Control is one of the five battlefield functional areas (BFA) of warfare and Combat Service Support).

CHARACTERISTICS:

Non-Developmental Item (NDI) Equipment and Common Hardware will be used with MCS. Additionally the Common Hardware will be fielded with the Standardized Integrated Command Post Systems (SICPS) (XM-1068, M998 Soft top and Rigid Wall Shelter).

TCP Weight: 798 lbs AC Weight: 318 lbs NDI Analyst Console/Tactical Computer Processor (AC/TCP):

Commoin Hardware TCU Weight: 45 lbs LCU Weight: 27.5 lbs

None known. FOREIGN COUNTERPART:

PROGRAM STATUS

MCS is in Milestone III with an Initial Operational Test and Evaluation (IOT&E) scheduled for Sept-Oct 92. NDI deliveries began in FY89 (III Corps) and will be completed in FY92. Common Hardware fieldings begin in FY94. Currently MCS Version 10.03.1 software is fielded to all heavy Army units on NDI, and MCS V11 will be fielded in FY94 on Common Hardware.

Overall MCS performed admirably. However it was determined that more training was required for the soldiers to effectively operate Common Hardware with the MCS software. MCS V.10.03.1 software was utilized in SWA. MCS V11 will provide the more user friendly software requested by

POINT OF CONTACT:

PERFORMANCE IN SWA:


Project Manager, Operations Tactical Data Systems ATTN: SFAE-CC-MVR-P Fort Monmouth, NJ 07703-5000

CONTRACTORS:

Loral Command and Control Systems (Colorado Springs, CO) (NDI and software) TRW (Redondo Beach, CA) (System Engineering and I Integration) MILTOPE (Milville, NY) (Command Hardware/Software)







ARMY DATA DISTRIBUTION SYSTEM (ADDS)

MISSION:

computers being fielded as part of the Army Tactical Command & Control System (ATCCS) and other battlefield automated systems. The Army Data Distribution System (ADDS) consists of two major products: The Enhanced Position Location Reporting System (EPLRS) for medium speed data distribution and the Joint Tactical Information Distribution System (JTIDS) for high speed data distribution. The ADDS provides near real time data distribution in the division and corps areas under the anticipated electronic countermeasure To provide a tactical data distribution system designed specifically to support the needs of the multitude of environment.

CHARACTERISTICS:

ADDS uses Time Division Multiple Access (TDMA) communications architecture to avoid transmission contention. Frequency hopping and spread spectrum technology provide jam resistance. The EPLRS user unit (28 lbs manpack size) and JTIDS terminal (94 lbs rack mounted) will be operated by the user of the host computer. Net Control Stations and dedicated relay functions will be provided by signal units.

FOREIGN COUNTERPART:

There is no known foreign counterpart to ADDS. JTIDS is a joint and multi-national system which will be interoperable with NATO units.

EPLRS is in low rate initial production while JTIDS is completing manufacturing development and system technical testing.

PROGRAM STATUS:

PERFORMANCE IN SWA:

The USMC used the basic PLRS radio in SWA to provide position/navigation at all levels of command. was used aboard the JSTARS to receive Airborne Warning and Control System (AWACS) data.


POINT OF CONTACT

ATTN: SFAE-CM-ADD Fort Monmouth, New Jersey 07703

CONTRACTOR:

Hughes Aircraft Company (Fullerton, CA & Forest, MS) GEC-Marconi (Totowa, NJ & San Marcos, CA)

Development END Concept five | DEM/



STANDARDIZED IINTEGRATED COMMAND POST SYSTEM (SICPS)

MISSION:

facilities will provide protected work area for command and control functions at corps through battalion levies. SICPS will be fielded as components of the Maneuver Control Systems, the Forward Area Air Defense Command and Control System the Advanced Field Artillery Tactical Data System, the All Source Analysis System and the Combal Service Support Control System. (ĆP), a Rigid Wall Shelter CP, a Track Vehicle CP (M577 variant) and a 5-Ton Expando Van CP. These CP The SICPS is a family of command post facilities developed to house the Army Tactical Command and Control System (ATCCS) across all battlefield functional areas. Variants of SICPS consist of a tent. Command Post

CHARACTERISTICS:

Bigid Wall Shelter CP. Mounts on the HMMWV shelter carrier and is intergrated with 5KW power unit, 9000 tents together; supported by a three-piece aluminum frame; fielded with two tables, two mapboards and a flourescent light set. The tent CP can be attached to any of the other SICPS variants by replacing one sidewall with an interface wall. The tent CP is part of the other three SICPS variants. Tent CP: 11 ft. x 11 ft. with interchangeable sidewalls, any of which can be removed for combining two or more

<u>Irack CP.</u> Installation kit for existing M577 tracked vehicles to provide C2 equipment racks, power and signal BTU/hr air conditioner, collective chemical/biological protection, command and control (C2) equipment racks, power and signal import/export panels, intercorn and operator seats.

import/export panels, and operator seats.

None. FOREIGN COUNTERPART:

PROGRAM STATUS:

TENT CP: Type Classified Standard 8 Feb 90. Production contract awarded 31 Oct 90 RIDGED WALL SHELTER: Technical Testing is ongoing TRACK CP: Full Scale Engineering Development Contract in place


5-TON CP: In development

PERFORMANCE IN SWA:


CONTRACTORS

XM-1068 Command Track Prototypes were deployed to SWA in Support of 1 CAV DIV. Overall performance was acceptable

TENT CP: Camel Mft. Co. (Knoxville, TN)
RIGID WALL SHELTERM CP: Brunwick Corp. Defense Div. (Marion, VA)
THACK CP: FMC Corp (San Jose, CA)
5-TON CP: CECOM Engineering Support Activity (Ft. Monmouth, NJ)



ALL SOURCE ANALYSIS SYSTEM



ALL SOURCE ANALYSIS SYSTEM (ASAS)

:NCISSIN

guide the employment of maneuver forces and systems such as the Joint Surveillance and Target Acquisition Radar System (JSTARS) and the Army Tactical Missile System (ATACMS). Today, many sophisticated sensor systems provide targeting information. The capability to process and respond to the information is limited by successfully execute AirLand Operations, and is the Intelligence Electronic Warfare (IEW) sub-element of the Army Tactical Command and Control System (ATCCS). ASAS automates command and control of IEW The All Source Analysis System (ASAS) is the central nervous system guiding field commanders to operations and intelligence fusion processing. It generates a near real-time picture of the enemy situation to manual and partially automated processing methods. ASAS uses state-of-the-art computers to speed the process and improve accuracy.

FOREIGN COUNTERPART:

There is no known foreign counterpart for this system.

PROGRAM STATUS:

The program employs an evolutionary acquisition strategy. Testing of system modules began in FY86 and continued through FY89. A Limited Capability Configuration (LCC) was delivered to Ft. Hood, TX in FY89. In EY91, an Army Systems Acquisition Review Council (ASARC) restructured the program incorporating the Balanced Technology Initiative (Hawkeye). The Block I Initial Operational Test and Evaluation will take place in 4th QTR, FY92 at Ft. Hood. A materiel release decision is scheduled for Apr 93. Block I fielding is scheduled for Fy93-95. Contract award for Block II development is programmed for Sep 92. Block II will transition ASAS to the ATCCS common hardware and software.

PERFORMANCE IN SWA:

Hawkeye was deployed with VII Corps and was extremely successful during Desert Shield/Storm. Hawkeye provided signal intelligence and asset management.

POINT OF CONTACT:

All Source Analysis System Project Office 1500 Planning Research Drive McLean, Virginia 22102

CONTRACTORS:

The Jet Propulsion Laboratory (JPL), Pasadena, CA, acts in the role of prime integrator for Block I.

Tech base Cencest tve | Development | Testes





ADVANCED FIELD ARTILLERY TACTICAL DATA SYSTEM (AFATDS)

MISSION:

AFATDS is the multi-service (Army/Marine Corps) automated fire support command, control and coordination system of the Army Tactical Command and Control System (ATCCS) which satisfies the fire support requirements of AirLand Battle doctrine. AFATDS will provide integrated, automated support for the planning, coordination and control of all fire support assets (mortars, close air support, naval gunfire, attack helicopter, and offensive electronic warfare), execution of counterfire, interdiction, and suppression of enemy targets for close and deep operations. AFATDS will replace TACFIRE and Light TACFIRE.

CHARACTERISTICS:

AFATDS uses non-developmental ruggedized Common Hardware and Software. AFATDS software is being developed, in modular, object-oriented Ada computer code. Successive versions each implement additional functionality and interoperability. The System will be capable of processing fire missions at peak per hour load as follows: Version 1 - 120; Version 2 - 420; Version 3 - 720.

FOREIGN COUNTERPART:

AFATDS will interoperate with the United Kingdom and German Fire Support Systems. An automated artiflery tactical command and control system was previously fielded by the Warsaw Pact. Their system provides digital linkage from battery to brigade or regiment level for fire planning, targeting, logistics and terrain management calculations.

PROGRAM STATUS:

Preliminary Design Reviews for Version 1 of the software are done and Detail Design is on-going for Version 1. Other FY92 activities will include Critical Design Review for Version 1 and Version 2 development.

POINT OF CONTACT:

PM FATDS ATTN: SFAE-AFATDS Fort Monmouth, NJ 07703

DELINOS LO INIO

Software - MAGNAVOX (Ft. Wayne, IN) Hardware - MILTOPE (Long Island, NY)

CONTRACTORS: Software -

Tech Bas Concept five | Development | Paster

SINCGARS COMBAT NET RADIO FAMILY



RECEIVER/ TRANSMITTER









ECCM FILL DEVICE





VEHICULAR SHORT RANGE RADIO

VEHICULAR SHORT RANGE/ LONG RANGE RADIO

VEHICULAR LONG RANGE RADIO



VEHICULAR ANTENNA





AIRBORNE REMOTE RADIO

SINCGARS REMOTE CONTROL UNIT (SRCU)





AIRBORNE DEDICATED REMOTE RADIO AND REMOTE CONTROL UNIT



AIRBORNE PANEL MOUNTED RADIO

SINGLE CHANNEL GROUND and AIRBORNE RADIO SYSTEM (SINCGARS)

MISSION:

SINCGARS provides commanders with a reliable, easily maintained Combat Net Radio (CNR) for command and control and provides Electronic Counter Counter Measures (ECCM) against Threat Electronic Warfare (EW). SINCGARS configurations include manpack, vehicular (both low and high power) and airborne models. COMSEC is integrated in currently produced versions of the ground and airborne models.

CHARACTERISTICS:

PROGRAM STATUS:

22.5 lbs w/battery and COMSEC 30.00 to 87.975 MHz

Frequency Range: Channels:

First source SINCGARS ground radios passed First Article Tests in Jan 88 and production deliveries began

immediately. A Follow-On Test and Evaluation (FOTE) was successfully completed in May 88 on the non-integrated Communications Security (COMSEC) (non-ICOM) version of the radio. An Initial Operational Test and Evaluation (IOTE) and FOTE were successfully completed on the ICOM radio in Nov 90. Award for and Evaluation (IOTE) and FOTE were successfully completed on the ICOM radio in Nov 90. Award for Option 3 for 8,000 radios was made in Jun 89. Option 4 for 16,000 radios was awarded in 1QFY91, completing the first source contract 44,100 ground radios. Of this quantity, 27,625 will have integrated COMSEC (ICOM). All SINCGARS procduced after FY90 will be ICOM. A second source of ICOM ground radios was selected and a firm fixed price contract was awarded in Jul 88 with two options for FY91 and FY92. Full competition will begin in FY94. The program office has fielded over 15,000 radios including the training base, Army units in SOUTHCOM, WESTCOM, and CONUS. The SINCGARS airborne radio passed First Article Tests in Sep 85. Contract 3 was awarded in Jan 91.

PERFORMANCE IN SWA:

Radio worked exceptionally well in both the combat and desert environment of SWA.

POINT OF CONTACT:

ATTN: SFAE-CM-GAR FT Monmouth, NJ 07703 PM SINCGARS

CONTRACTORS:

First Source: ITT Aerospace/Optical Division (Fort Wayne, IN)

Second Source: General Dynamics (San Diego, CA)

Fielded ŝ ncept Eval | DBM/VAL ech frae



MOBILE SUBSCRIBER EQUIPMENT (MSE)

MISSION:

MSE provides the tactical U.S. Army commander with a secure, automatic, highly mobile, quickly deployable survivable tactical communications system capable of passing data, facsimile and voice traffic throughout the division and corps area of operations.

CHARACTERISTICS:

The major items of equipment are integrated into five functional areas: Subscriber Terminals provide the voice and data elements to interface with other functional areas of the MSE system. Mobile Subscriber Access radiotelephone terminals permit mobile and stationary users to ...tomatically communicate secure voice and data throughout the tactical area of operations. Wire Subscriber Access allows non-radio users entry to the MSE system through concentrations of automatic switching equipment. Area coverage of the battlefield from of commanders and staff to retain the same telephone number regardless of their location. System Control provides an automated Corps-wide MSE system management capability which is itself mobile, moving with the mobile or fixed locations is achieved through secure automatic switching, continuous coverage and the ability elements it controls.

FOREIGN COUNTERPART:

There is no known counterpart to the MSE system.

PERFORMANCE IN SWA:

PROGRAM STATUS

The MSE program is progressing according to the acquisition plan. Fifty percent of the Signal Battalions scheduled to receive MSE have been successfully fielded. All fieldings will be completed by November 1994.

Nodes of MSE were deployed to SWA, MSE proved faster and more reliable than anything the Army ever had before. Switch reliability was solid. MSE was operational during the entire 350km high speed advance by the 3RD AD through Iraq and Kuwait.

POINT OF CONTACT:

Project Manager MSE ATTN: SFAE-MSE Ft. Monmouth, New Jersey 07703-5210


CONTRACTORS:

GTE (Taunton, MA) is the prime contractor for the MSE system. GTE is supported by

over 30 subcontractors in this country and aboad.

Fielded 1 Concept five | DEM/VAL lech Bose

GPS RECEIVERS



NAVSTAR GLOBAL POSITIONING SYSTEM (GPS)

MISSION:

based users. GPS has three segments: space segment consisting of 24 satellites; ground control segment; and user segment. The Army is the lead service in the Joint Program Office (JPO) for the manpack/vehicular The GPS is a Joint Army, Navy, Air Force program with the Air Force as the lead service. It is a space-based navigation, three dimensional positioning and time distribution system that will provide accurate, continuous, all-weather, common grid, worldwide navigation, positioning and timing information to land, sea, air and spaceand low-to-medium dynamic aircraft receivers.

CHARACTERISTICS:

The user segment consists of receiver configurations for manpack/vehicular, low-to-medium and high dynamic aircraft and seacraft applications. The GPS receiver is a passive device that will be deployed extensively at all echelons and with Army aircraft.

FOREIGN COUNTERPART:

PROGRAM STATUS:

The Soviets have developed a similar system, GLONASS, but insufficient data are available to permit in meaningful comparison to GPS.

The JPO is planning and preparing to implement an off-the-shelf non-developmental item procurement of the Precision Lightweight GPS Receiver (PLGR), an inexpensive ground set. Milestone III for the PLGR is projected to be early FY94 following first article and operational testing with initial production sets in late FY93. The PLGR procurement will satisfy most other Arrny ground applications and replace the previously deployed AN/PSN-8, once sufficient assets are available. During Desert Shield/Desert Storm, waivers were obtained from ASD(C3I) for the Army to acquire over 8000 commercially available sets called the Small Lightweight GPS Receiver (SLGR) as an interim capability until the PLGR is deployed. As SLGRs are displaced by PLGRs, it is planned that the SLGRs will be reallocated. An additional interim buy of SLGR-type devices is envisioned during FY92. Program Manager (PM) GPS will explore alternatives for functional substitutes for the 2-channel Air Set, AN/ASN-149; the Miniaturized Airborne GPS Receiver (MAGR) is being

PERFORMANCE IN SWA:

Desert Storm experience has shown the utility of GPS sets for The GPS was used extensively in SWA.

POINT OF CONTACT:

Ft Monmouth, NJ 07703 Magellan Corp (Monrovia, CA) Texas In:

CECOM/PosNav Coordinator ATTN: AMSEL-RD-ASCO Ft. Monmouth, NJ 07703

CONTRACTORS:

Magellan Corp (Monrovia, CA)

Texas Instruments (Plano, TX)

Rockwell International (Cedar Rapids, IA)

Trimble Corps (Sunnyvale, CA)


o, TX) SCI (Huntsville, AL)

Teach base Concept five | DRM/VAL | BMD | Product

MILSATCOM TERMINALS



TACTICAL TERMINALS



TACTICAL MANPACKS



STRATEGIC TERMINALS

MILITARY SATELLITE COMMUNICATIONS (MILSATCOM)

MISSION:

communications, and intelligence requirements supporting the President, Commanders-in-Chief (CINC), National Command Authority (NCA), Military Departments, intelligence community, and NATO. The satellite equipment use all DoD MILSATCOM systems, including Fleet Satellite/Air Force Satellite (FLTSAT/AFSAT) system; Defense Satellite Communications System (DSCS); and, the future Military Strategic/Tactical Relay The Army is the DoD's executive agent for all satellite communications ground equipment, per JCS Memorandum of Policy 178, dated 1986. This equipment satisfies JCS-validated command, control, MILSTAR) system.

CHARACTERISTICS:

Fixed strategic, theater and mobile tactical satellite communications terminals.

PROGRAM STATUS:

increase the capacity of the existing system are underway. In the tactical DSCS, Army is modifying the AN/TSC-85B/93B terminals to provide commanders with an anti-jam capability. Strategically, Army will continue to modify its large fixed site facilities, provide digital equipment upgrades, and expand the control subsystem to oriented MILSTAR program by developing low data rate manpack terminals and medium data rate multichannel terminals. Army is continuing the Single Channel Objective Tactical Terminal/AN/TSC-124 terminal test and Army is procuring commercial non-developmental item (NDI) terminals and related equipment in support of contingency force and special operations forces (SOF) unit requirements for use on FLTSAT/AFSAT. Efforts to embed Comunications Security (COMSEC) and develop a demand assigned multiple access capability to enhance satellife and communications payload control operations. Army is supporting a more tactically development program.

PERFORMANCE IN SWA:

PM MILSTAR (Army)
ATTN: SFAE-CM-MS
Ft. Monmouth, NJ 07703

ATTN: SFAE-CM-SC Ft. Monmouth, NJ 07703

Satellite communication was a success during Desert Shield/Desert Storm. It provided commanders the command and Control (C2) for long haul nets and extends terrestrial communications systems.


CECOM
ATTN: AMSEL-SS
Ft. Monmouth, NJ 07703

CONTRACTORS

POINT OF CONTACT:

GE Corp (Valley Forge, PA)
Harris Corp (Melbourne, FL)
Loral Corp (Colorado Springs, CO)
Magnavox Corp (Torrence, CA)

Motorola Corp (Scottsdale, AZ) Titan Corp (San Diego, CA) Tech base Concept the Designment and Preduce Field@d



COMMUNICATIONS SYSTEM CONTROL ELEMENT

MISSION:

network, the message switched network, and the transmission network at signal brigades, battalions and communications node. The distribution of this system and its proximity to the switches provide for the rapid dissemination of directives and reports to the appropriate elements in the network at the time they are needed. This network management element provides the capability to plan, engineer, and control the circuit switched

CHARACTERISTICS:

AN/TYQ-30(V) 1 is a dual shelter (S-712 & S-713) unit used at theater signal command (Army) and signal brigade levels.

AN/TYQ-30(V) 2 is a single shelter unit used at signal battalion level. AN/TYQ-31 is a single shelter used at nodes with the AN/TTC-39 Circuit Switch.

FOREIGN COUNTERPART:

None.

These equipments were authorized for production in FY86, and fielding began in FY90 and will continue through FY95.

PROGRAM STATUS:

Deployed to SWA in Dec 90. Operated and met requirements successfully.

PERFORMANCE IN SWA:


ATTN: AMSEL-LC-MMR-T Ft. Monmouth, NJ 07703 DSN 992-2436 ATTN: SFAE-CM-MSC-CMS FT. Monmouth, NJ 07703 DSN 992-23110 PM, MSCS

POINT OF CONTACT:

GTE (Raleigh, NC) (Software) ESE (Richardson, TX) (Hardware)

CONTRACTORS:

Fielded 3 Concept (vel DBM/VAL



DIGITAL TRANSMISSION ASSEMBLAGES

MISSION:

This equipment represents a family of high capacity, digital radio systems which link circuit and message switches into communications networks supporting telephone and message traffic at the theater tactical level. They also provide the transmission path for linking extension switch subscriber locations into the main switching network.

CHARACTERISTICS:

The digital transmission assemblage provide a series of radio relay and radio terminal equipment in a variety of sizes, capabilities and characteristics.

FOREIGN COUNTERPART:

PROGRAM STATUS:

Unknown.

Fielding began in FY88 and is expected to be completed in FY95. Production and set assembly are expected to be completed in FY93 and FY95 respectively.

Outstanding. Lessons learned did not highlight any significant problems. There were several suggesstions for product improvements to provide system enhancements.

PERFORMANCE IN SWA:


POINT OF CONTACT:

ATTN: AMSEL-LC-MMR-T Ft. Monmouth, New Jersey 07703 DSN 99248 CECOM-DMM ATTN: SFAE-CM-MSC-CTS Ft. Monmouth, New Jersey 07703 DSN 992-3474

CONTRACTORS:

Digital Group Multiplex Equipment: Raytheon (Marlboro, MA); Group Technologies (Tampa, FL) Antennas: Harris Corp. (Melbourne, FL) Assemblages: Laguna Industries (Laguna Pueblo, NM)

Fielded Tech Bose



CIRCUIT SWITCH AND MESSAGE SWITCH

MISSION:

connecting telephones, message traffic, and data users in both a secure and nonsecure mode in the area network at Echelons Above Corps. The AN/TYC-39 system provides corps and theater echelons tactical, Equipment provides automatic switching service - interconnecting analog and digital users - between tactical and Defense Communication System (DCS) switches; and between U.S. and NATO national switches. The AN/TTC-39A/D system is the heart of the multi-channel switched network and is a highly efficient means of automatic store and forward record traffic capability.

CHARACTERISTICS:

The AN/TTC-39 circuit switch family consists of three fielded versions. The "A" model switches are an S-J280, 7444 line analog/digital switch with integral COMSEC and a downsized, modified S-250, 324 analog/digital switch. Both provide up to 7500 calls per hour service, 5 level precedence, conference and many other subscriber features. The "D" model is an S-280, 708 line analog/digital switch which incorporates the same affiliation and flood search routing as provided in Mobile Subscriber Equipment (MSE). Most features are still available in the "D" model. The AN/TYC-39 message switch family consists of three fielded versions. All are in automatic store and forward switches which provide service for both strategic (R) and intelligence (Y) communities. The switches provide interface with inventory, TRI-TAC and Automatic Digital Network S-280 shetters. There is a dual shetter 50 line switch and single shetter 24 and 48 line switches. All are tactical, AUTODIN) equipment with precedence, security and other subscriber features.

FOREIGN COUNTERPART:

PROGRAM STATUS:

Force and Joint communities. The "D" model fielding has begun in Germany and Korea. The message switch is currently in the engineering phase of product improvement which will result in an "A" model. The fielding of the Both switches are currently deployed and were initially authorized for production in FY80. Both switches are currently in product improvement phases. The circuit switch "A" model has been fully fielded to the Army, Air *A* model is anticipated to begin in FY94.

PERFORMANCE IN SWA:

The multiplicity of equipments, different architectures and the analog and digital mix problems found in the operational force structure were resolved through the flexiibility of the AN/TC-39 and AN/TYC-39 communications system deployed at Echelons Above Corps (EAC).

POINT OF CONTACT:

ATTN: SFAE-CM-MSC-CSW A
Ft. Monmouth, NJ 07703 F
DSN 002-218149 D

ATTN: AMSEL-LC-MMR-T Ft. Monmouth, NJ 07703 DSN 992-4361

CONTRACTORS:

GTE Government Systems Corp, Command and Control and Communications (Needham Heights, MA)

Tech base Concept first DBM/VAL NuD hostics Fleided

SOLDIER SUPPORT

The Soldier Support mission area includes those items that directly support the individual soldier. This mission area includes organizational clothing and individual equipment, nuclear, biological, and chemical defense equipment, and individual As we modernize the Army with new equipment, we must keep the individual soldier equally up-to-date. Weapons.

	DEVEL	DEVELOPMENT		
Tech Base	Concept Development	DEM/VAL EMD	Production	Fielded
Medical	Close Combat			Soldier Support Items
Battlefield Distributed Simulation- Developmental	ractical Frainer			Nuclear, Biological, and Chemical Defense
Nuclear, Biological, Chemical Defense				
Night Vision and Electro-Optics				
Soldier Integrated Protective Ensemble				



Sea Electronic Battlefield

der to CINC Training

Tements Analysis

Virtual Prototyping

Louisiana Maneuvers

MEDICAL (AUTOMATIC INJECTOR)

BATTLEFIELD DISTRIBUTED SIMULATION - DEVELOPMENTAL

البا Precision Strike (

Global Surveillance

SW USA Exercise

TECH BASE SOLDIER SUPPORT -

OVERVIEW:


The goal of the Army Technology Base program in Soldier Support is to enhance the soldier's winning edge. This includes medical products, Nuclear, Biological and Chemical defense equipment, night vision devices, training systems, and individual equipment.

MEDICAL:


Medical research and technology programs are designed to support the soldier in the field and to meet other Army health needs. This program encompasses: increasing efficiency of manpower through medical knowledge and equipment; enhancing recovery from combat wounds; prevention and treatment of infectious diseases; providing protection from hazardous environments; and enhancing individual performance.

BATTLEFIELD DISTRIBUTED SIMULATION-DEVELOPMENTAL (BDS-D):

The cornerstone of the Army's program to incorporate battlefield simulation technology into the acquisition process is the BDS-D project. BDS-D will create state-of-the art distributed network links between government, university, and industry sites into a simulation of the combined arms and joint forces battlefield. Use of an object-oriented design approach for networking simulators will provide a and operational testing by providing a cost effective afternative to proc.-of-principle demonstrations, field tests, and operational evaluations. For example, Future Armored Vehicles and the Rororcraft Pilot's Associate will be virtually prototyped under the BDS-D concept. Mobility, weapons station stability, ride muticlimensional, virtual-reality, simulation of the battlefield environment that maintains the warfighter in the quality, and survivability will be evaluated in a true combined-arms simulation using BDS-D technologies, loop. The BDS-D program will support material development, combat development, training development, without incurring the cost of a complex and costly field training exercise.



SOLDIER INTEGRATED PROTECTIVE ENSEMBLE (SIPE)



NIGHT VISION AND ELECTRO-OPTICS

SOLDIER INTEGRATED PROTECTIVE ENSEMBLE NUCLEAR, BIOLOGICAL, CHEMICAL DEFENSE

The plantage of the property o

Navigation

3 4 204 controls offer to

6 40 for the controls

6 40 controls

7 4 for the controls

9 10 for the co

MATERIALS

TECH BASE (CON'T) SOLDIER SUPPORT -

NUCLEAR, BIOLOGICAL, CHEMICAL (NBC) DEFENSE:


NIGHT VISION AND AND ELECTRO-OPTICS:


SOLDIER INTEGRATED PROTECTIVE ENSEMBLE (SIPE):

biological threats. Improved casualty care practices and doctrine will increase the return to duty rate, thus includes development of multi-agent sensors and detectors to provide real-time detection and identification of chemical and biological agents. Additionally, detectors will be more compact so they may be placed on a chemical agents. This detector has been mounted on a Unmanned Aerial Vehicle platform and is designed to operate up to 5 km from the target. Decontamination systems of the future will emphasize noncorrosive, multi-agent systems for use with individual equipment and sensitive electronics. offer increased respiratory protection against current and future NBC threats while providing improved weapons systems interface, and minimizing the physiological burden imposed by NBC protective equipment. Medical chemical-biological defenses will provide new pretreatments for nerve agents, topical skin protectants for vesicants, new vaccines for biological threats, and novel therapies for chemical and adding to force sustainment. The emphasis of the contamination avoidance component of NBC defense variety of platforms and will not have large space and power requirements. An example of such a detector is the Lightweight Standoff Chemical Agent Detector which will offer on the move standoff detection of The NBC defense technology base includes: materiel for individual physical and medical protection; collective protection; contamination avoidance; and decontamination. Individual protective equipment will

a low-cost integrated system of ultra lightweight sensor, display, and laser modules configured for multiple infantry missions. The demonstration will integrate weapon sighting with the helmet displays, providing infantrymen significant increases in mobility and lethality. Uncooled sensors, optics, and laser technologies will be applied in '' 9 AIMS Demonstration. The demonstration follows the Soldier Integrated Protective Ensemble Advanced Technology Transition Demonstration to enhance the successfully Advanced Integrated Man Portable System (AIMS) will demonstrate an experimental night vision device that demonstrated visual augmentation components.

SIPE will demonstrate a modular, head-to-toe, individual fighting system for the dismounted soldier to allow improved combat effectiveness, while providing balanced protection against multiple battlefield hazards. SIPE will integrate technologies and components for clothing/equipment, communications, weapons interface, night vision and microclimate conditioning/power.





MIAI TANK MANNED MODULE

TYPICAL CREW STATION VIEW

CLOSE COMBAT TACTICAL TRAINER (CCTT)

MISSION:

actions, placing the stresses of combat on all participants. Conduct of Joint operations, involving other US services and members of the allied forces with whom we routinely operate outside CONUS. The system will allow To train active and reserve component M1 Tank and M2/3 Bradley crews on individual and collective (crew through battalion task force) tasks and skills in command and control, communications and maneuver on a simulated, fully interactive, real time battlefield. Will simulate, in real time, the conduct of combat operations in a realistic environment with an appropriate and challenging opposing force that will require realistic individual, crew and staff individuals, crews and units to operate in a simulated combat environment reducing the impact of restrictions of weapon effects, safety, terrain limitations, time, and will assist in overcoming the effects of crew turbulance and scarce resources.

CHARACTERISTICS:

replicating the M1 and M2/3 vehicles and weapon systems of a company/team operating on a simulated real-time System will exist in both fixed and mobile versions. The fixed version will be static at all times during operation. The mobile version will be static during operation but will move over primary and secondary roads during A group of fully interactive networked simulators and command, control and communications work stations, ransport from site to site. battlefield.

PROGRAM STATUS:

The CCTT program successfully completed Milestone I/II ASARC. RFP was released Oct 91 with contract award expected 4Q92.

POINTS OF CONTACT:


PM Training Devices (PM TRADE) 12350 Research Parkway Orlando, FL 32826-3276 ATTN: AMCPM-TND Fel. (407) 380-8073

DSN: 960-8073

Army Materiel Command (AMC) Alexandria, VA 22333-0001 5001 Eisenhower Avenue Tel. (703) 274-8605 DSN: 284-8605 ATTN: AMCDE-S

CONTRACTOR:

TBD (Contract Award Expected 4Q92)






OPTICS FOR LIGHT WEAPONS



SOFT MOUNT



EXTREME COLD WEATHER CLOTHING SYSTEM

IMPROVED DESERT BOOT

SOLDIER SUPPORT

MISSION:

Provide the soldier improved individual equipment, weapons, clothing, subsistence items and quality of life equipment to enhance his overall effectiveness and survivability on the battlefield. Soldier Support includes several related programs which respond to changing threat requirements and advances in state of the art technology.

CHARACTERISTICS:

The Soldier Modernization Plan is the basis for soldier support efforts. It provides a cohesive plan for the coordinated development of soldier support equipment and is the roadmap for near term, mid term and far term efforts. A key element of the soldier support and modernization process is the Soldier Enhancement Program (SEP). SEP projects are primarily Nondevelopmental Items and are focused in four general areas: weapons and munitions, combat clothing and individual equipment, communications and navigation aids and food/water and shelter. Ongoing efforts in addition to SEP are:

CLOTHING AND INDIVIDUAL EQUIPMENT (CIE). Currently, emphasis is placed on combat CIE to improve soldier capability to counter newly emerging battlefield threats. Research and development is focused on the design of lighter weight equipment, ballistic and laser eye protection, and improved chemical protective clothing which take advantage of the latest progress in technology and advanced materiels.

WEAPONS AND MUNITIONS efforts increase the lethality of the soldier on the modern battlefield. Projects include a Soft Mount for the M2.50 caliber Machine Gun and the MK19 Grenade Machine Gun and improvements to the M24 Sniper Weapon System. Other efforts include optical lights for light weapons, a 30mm semi-automatic grenade launcher and neutralization of anitpersonnel mines.

QUALITY OF LIFE. Ongoing efforts include improved kitchen, laundry, shower and other collective support equipment as well as COMMUNICATION AND NAVIGATION AIDS projects include the Communication/Aural Protective System to provide improved communications capability in the Bradley while wearing the PASGT helmet and evaluation of the Digital Handheld Compass.

tems for the individual which will enhance the soldier's quality of life in the field.

There are 61 SEP projects in FY92, of which 24 are weapons and munitions, 23 CIE, 5 communications and navigation and 9 food/water and shelter. 37 projects are new starts in FY92. Work begins in FY92 on the Collective Support Package, a quality of

ilfe effort made up of latrines, kitchen, laundry, billeting and other facilities designed to support the soldier in the field.

PROGRAM STATUS:

PERFORMANCE

These included: Ballistic Laser Eye Protection, Sun/Wind/Dust Goggles w/laser protection, Improved Desert Boot, Machine Gun Lubricant, Flameless Ration Heater, Ammunition Pack for the Squad Assault Weapon, Lightweight Desert Uniforms, Improved Several items were provided to the troops in SWA which not only improved their combat effectiveness, but quality of life as well. Operational Ration Items and the Five Soldier Crew Tent.

POINT OF CONTACT:

PMCE

4300 Goodfellow Blvd St. Louis, MO 63120 TROSCOM 14050 Dawson Beach Rd Noodbridge, VA 22919

SESOM SESOM Rock Island, IL 61299 ATTN: AMSMC-RT AMCCOM

Ft. Monmouth, NJ 07703 ATTN: AMSEL-RD

Fielded Canoapt eval DBAVAL | BAD



PROTECTIVE MASK WORN BY APACHE HELICOPTER PILOTS AND CREWMEN



LIGHTWEIGHT DECONTAMINATION SYSTEM DECONTAMINATING A M113 ARMORED PERSONNEL CARRIER



REMOTE SENSING CHEMICAL AGENT ALARM DEPLOYED TO SOUTHWEST ASIA DURING OPERATION DESERT STORM



PROTECTIVE MASK WORN BY A SOLDIER IN FULL CHEMICAL PROTECTIVE CLOTHING



CHEMICAL AGENT MONITOR CHECKING AN ARMORED PERSONNEL CARRIER FOR POSSIBLE CHEMICAL CONTAMINATION



PROTECTIVE MASK WORN BY AN ARMORED VEHICL .. CREWMAN

NUCLEAR, BIOLOGICAL, AND CHEMICAL DEFENSE

MISSION:

mplementing this doctrine requires effective capabilities for reconnaissance, detection and identification; individual and collective personnel protection; decontamination of personnel and equipment, and medical management of NBC casualties. A Nuclear, biological and chemical (NBC) defense provides essential defensive materiel to allow U.S. Forces to fight on the contaminated battlefield. NBC defense doctrine stresses contamination avoidance when the scheme of maneuver permits; protection of soldiers from incapacitating or lethal agents, NBC survivable equipment, and effective decontamination. strong NBC defensive capability deters employment of NBC weapons against U.S. Forces.

COUNTERPARTS: FOREIGN

arsenal. These weapons are especially becoming widespread in the Middle East. Both chemical and biological (C/B) weapons Even though the U.S. is negotiating chemical weapons treaties, many nations still have an extensive chemical weapons were a threat to the U.S. Forces participating in Operation DESERT STORM.

PROGRAM STATUS:

NBC defense technology initiatives emphasize maturing technologies and reducing development risk of future generation VBC DETECTION: The U.S. fielded the Fox NBC reconnaissance vehicle and is developing enhancements to remotely detect systems. Cooperative NBC defense programs include development efforts with Canada, the United Kingdom and France. chemical agents. A new chemical and biological agent detector is in development.

PROTECTION: The new M40 mask is being fielded to soldiers throughout the Army. The new M43 series aviator mask is being ssued to all Army aviators. Development of the next generation overgarments is nearing completion.

DECONTAMINATION: The M17 Lightweight Decontamination System is being deployed down to battalion level. The new Modular Decontamination System will be the new system for complete equipment decontamination.

NBC MEDICAL MANAGEMENT: The new M291 Skin Decontamination Kit has been fielded to protect soldiers from chemical agents. Drugs against nerve agents and vaccines against various biological agents are being developed. The M43 Aviator mask, Fox NBC Reconnaissance System, Chemical Agent Monitor and M17 Lightweight Decontamination system were fielded to troops during DESERT STORM. Although not required for actual use in an NBC environment, they

significantly improved the confidence and morale of our soldiers.

PERFORMANCE

ATTN: SMCCR-FP U.S. Army CRDEC

Aberdeen Proving Ground, MD 21010

POINT OF CONTACT:

Aberdeen Proving Ground, MD 21010 ATTN: AMC-PM-NN PM NBC Defense

Brunswick Defense (Deland, FL) ILC Dover (Dover, DE)

Mine Safety Appliance (Pittsburgh, PA) ETG, Inc. (Towson, MD)

> General Dynamics Land Systems (Detroit, MI) Engineered Air Systems, Inc. (St. Louis, MO)

Battelle Memorial Institute (Columbus, OH)

CONTRACTORS:

Rohm and Haas Co. (Springhouse, PA)

Fielded Concept Eval | DBM/VAL | EMD Tech Base

STRATEGIC CONFLICT

inter-continental or transoceanic inter-theater conflict. The U.S. Army Strategic Defense program is the Army's only strategic weapons development The Strategic Conflict mission area relates to program.

þe	
Helded	
Production	
Q	
EMD	
DEVELOPMENT DEM/VAL	Theater High Altitude Area Defense Ground Based Anti-Satellite System Ground Based Interceptor Cround Based Surveillance and Tracking System Ground Based
Concept	High Endoatmospheric Defense Interceptor
Tech Base	Extended Range Interceptor Technology Airborne Surveillance Testbed





STRATEGIC CONFLICT - TECH BASE


OVERVIEW:


orces to simulate strategic threat scenarios, to provide technologies to facilitate discrimination of threats The goal of the Strategic Conflict technology base is to develop capabilities for application by strategic in flight, and provide robust capability to neutralize and/or destroy threats in a strategic defense context.


The following are some initiatives in the area of strategic defense:


support Battle Management and Command, Control and Communications (BMC3) experimentation and flexible, easily reconfigured, and cost effective research computing center. This center is designed to demonstration and advance processing technology validation and evaluation. It is a node of the Strategic Defense Initiative National Test Bed and host to the Extended Air Defense Test Bed, Surveilance (Sensor) ADVANCED RESEARCH CENTER (ARC) in Huntsville, AL: The Advanced Research Center is a highly Test Bed and the Mid-Course (Space Phenomenology) Data Center.

strategic defense applications. The major deliverable of the GTA program is the demonstration of mission capable output parameters for an integrated system with technologies that are traceable to space NEUTRAL PARTICLE BEAM (NPB) GROUND TEST ACCELERATOR (GTA): The Ground Test Accelerator capabilities and technologies that are necessary to field a robust weapon discrimination system for (GTA) is a major component of the national NPB program whose objective is to demonstrate the parameters, operations. NEUTRAL PARTICLE B." AM (NPB) CONTINUOUS WAVE DEUTERIUM DEMONSTRATOR (CWDD): The objective of the Continuous Wave Deuterium Demonstrator (CWDD) is to develop and demonstrate the low energy sections of a negative deuterium ion particle a celerator able to operate continuously at cryogenic The fabrication, assembly and demonstration phase of the CWDD are currently in progress. The program is scheduled for completion in FY97. temperatures.









198

EXTENDED RANGE INTERCEPT TECHNOLOGY (ERINT-1)

MISSION:

The Extended Range Intercept Technology (ERINT-1) program will demonstrate a hit-to-kill capability for all systems that can be applied to Theater Missile Defense.

CHARACTERISTICS:

ERINT is being developed as a hit-to-kill anti-missile missile. Missile components and subsystems are being enhanced and miniaturized to continue the successful co spt of a small, lightweight agile missile while increasing performance.

FOREIGN COUNTERPARTS:

The Soviet-developed SA-12 is comparable to ERINT in advanced technology and potential effectiveness.

PROGRAM STATUS:

lower radar cross sections and more complex radar signatures at a greater range. Missile software is being The ERINT missile is a technology demonstration being considered for PATRIOT integration. The missile's onboard radar sensor performance is being improved to permit terminal homing against targets with much expanded to engage a variety of targets.

The ERINT-1 Fire Control System (FCS) hardware is essentially the same as that used in the successful intercept by the Flexible Lightweight Agile Guided Experiment (FLAGE). FCS software, however, will be improved to perform against various targets. The FCS software is being made to be compatible with Patriot and other launchers

1992. The first two flights will be control rocket motor test flights, followed by two guided test flights against surrogate tactical ballistic missiles containing a simulated chemical payload (one bulk and one submunition). The third guided test flight will be conducted against an aircraft drone. The fourth guided test flight will be another simulated bulk chemical ballistic target with the final two guided tests flights The ERINT-1 flight test program consists of eight flight tests beginning in the second quarter of fiscal year against surrogate Maneuvering Tactical Ballistic Missiles containing a simulated submunition chemical

POINT OF CONTACT:

U.S. Army Strategic Defense Command ATTN: CSSD-KE-F

P.O. Box 1500

Huntsville, AL 35807-3801


CONTRACTORS:

LTV Aerospace and Defense (Grand Prairie, TX)


Rockwell International (Seeker) (Anaheim, CA)

Atlantic Research Corporation (Attitude Control Motors & Solid Rocket Motor) (Gainesville, VA)

Lucas Aerospace & Power Equipment Corp (Aerodynamic Maneuvering System) (Aurora, OH)







AIRBORNE SURVEILLANCE TESTBED (AST)

MISSION:

technology. The technology advancements to be tested include LWIR sensor components, real-time The Airborne Surveillance Testbed project, formerly called the Airborne Optical Adjunct (AOA), is an Anti-Ballistic Missile (ABM) Treaty-compliant technology experiment to validate airborne long wave infrared (LWIR) surveillance sensor functional performance and to provide a testbed for advanced surveillance onboard signal and data processing, target signature measurements, and aero-optic effects and controls.

CHARACTERISTICS:

The system consists of a state-of-the-art Long Wave Infrared (LWIR) sensor and data processor installed in a modified Boeing 767 commercial jet aircraft. The key to AST performance is ability of the LWIR sensor system to detect the heat of objects at long ranges against the cold space background within its field of view. The system will be used to test LWIR and data processing performance and as a testbed vehicle for other sensors and Strategic Defense Intitiative systems.

FOREIGN COUNTERPART:

None.

PROGRAM STATUS:

locations, including White Sands Missile Range, NM, Cape Canaveral, FL; Vandenberg Air Force Base, CA, Minuteman III in September 1990 at Kwajalein Atoll. AST flew successful missions in FY91 at a variety of and USAKA. Several challenging missions are planned for FY92

The AST completed CONUS flight testing in the summer of 1990 and flew its first mission against a

POINT OF CONTACT:

ATTN: CSSD-AB P.O. Box 1500

U.S. Army Strategic Defense Command


Huntsville, AL 35807-3801

Boeing (Prime) - (Kent, WA) Hughes (Sensors) - (El Segundo, CA)

CONTRACTORS:

Honeywell (Data Processing, Computer Hardware) - (Clearwater, FL)

Tech Base house the last wat as headen maked



HIGHENDOATMOSPHERIC DEFENSE INTERCEPTOR (HEDI)/ EXOATMOSPHERIC ENDOATMOSPHERIC INTERCEPTOR (E2I)

MISSION:

HEDI is a strategic, ground-based, hypervelocity interceptor. This system is the terminal layer of the Ballistic Defense system. Associated with HEDI is the Kinetic Kill Vehicle Integrated Technology Experiment (KITE) which is designed to address and resolve critical issues associated with performing endoatmospheric intercepts.

retains the classical endo commit/endo intercept operational mode with the increased operational modes of exo entry Vehicles before, during and after reentry, as well as short-range and depressed trajectory Sea Launched The Endoatmospheric/Exoatmospheric Interceptor (E2I) is a multi-operational mode defense interceptor which commit/endo intercept. The multi-mode capability allows E2I to intercept Intercontinental Ballistic Missile Re-Ballistic Missiles.

CHARACTERISTICS:

rapid divert capabilities. The vehicle and its individual components must also be able to withstand the high The requirement for HEDI to function in the atmosphere at a high velocity requires emphasis on propulsion and temperatures generated by atmospheric friction. The battlespace characteristics require E2I to be a lightweight interceptor with particular emphasis on target hit-to-kill. The vehicle and its individual components also must be able to withstand the high temperatures and selection/designation using transatmospheric phenomenology effects, and propulsion and divert capabilities for stringent environments during hypervelocities generated by atmospheric friction.

FOREIGN COUNTERPART:

: Soviet-developed Gazelle.

PROGRAM STATUS:

vulnerability, etc.). In FY90, the first KITE flight test (KITE-1) was successfully completed at White Sands Missile Range (WSMR). In September 1991, a second KITE test failed to achieve its objectives when a premature could be initiated. The second KITE test flight is expected to be rescheduled for 3QTR FY92. This flight will measure seeker performance and aero-optical effects while viewing a parachute flare target delivered by aircraft. The KITE program is a flight technology demonstration program designed to resolve critical issues associated detonation of the test vehicle's self-destruct system destroyed the test vehicle before onboard experiments with high velocity interceptors using existing and developing technologies (e.g., window coding, Kinetic Energy

The HEDI KITE Program, scheduled to conclude with the KITE-3 scheduled for FY93 at WSMR, will evolve into a series of E2I flights at WSMR and the U.S. Army Kwajalein Atoll (USAKA). The procurement process for the E2I Demonstration/Validation is ongoing.

POINT OF CONTACT:

U.S. Army Strategic Defense Command SFAE-SD-HED P.O. Box 1500


Huntsville, AL 35807-3801

CONTRACTORS:

HEDI KITE --- McDonnell Douglas (Prime) - (Los Angeles, CA)
Hughes (Seeker) - (Canoga Park, CA)
Aerojet (Controls) - (Sacramento, CA)

Perhaps Concept Marva as Present Reserved Perhaps Reserve

ENGAGEMENT CONCEPT



DEFENSE ALTITUDE AREA (THAAD) HUH THEATER

MISSION:

area coverage in both mature and contingency theaters. THAAD will engage tactical/theater ballistic missiles at high attitudes which minimizes debris and chemical/nuclear damage. THAAD will be The THAAD system, the upper tier of a two-tier active theater missile defense system, will provide large interoperable with U.S. Air Defense Systems, Air Force space-based sensors and NATO systems.

CHARACTERISTICS:

The THAAD system elements include a THAAD battery with launchers, a missile with a kinetic energy kill vehicle, a battery tactical operation center (TOC) and support equipment. The Theater Missile Defense Ground Based Radar (TMD-GBR) will provide fire control and surveillance for THAAD. The THAAD battery TOC will be compatible with the battalion air defense TOC's to enable cuing to the lower tier. The THAAD system will be C-130 transportable and will use standard government power systems.

FOREIGN COUNTERPART:

SAAM, SAMP/N and SAMP/T (France & Italy) Arrow/ACES (United States & Israel)

MSAM (Germany)

PROGRAM STATUS:

1992. A series of ten flight tests will begin in 1994 followed by ten system tests. Completion of a prototype THAAD system is scheduled for 1996. The THAAD Concept Definition phase will be completed July 92. A Defense Acquisition Board Review was held 21 Jan 92 and a demonstration/validation competitive contract award is expected in the summer of

U.S. Army Strategic Defense Command ATTN: CSSD-TM-H P.O. Box 1500


POINT OF CONTACT:

Huntsville, AL 35807-3801


Lockheed (Sunnyvale, CA) Sparta (Huntsville, AL)

CONTRACTORS:

McDonnell Douglas (Long Beach, CA)







ANTISATELLITE (ASAT)

MISSION:

ASAT weapons and their command and control elements constitute the space forces necessary to execute space control operations. Accomplishing this mission requires the ability to provide space surveillance, actively defend friendly space systems against a variety of threats, disrupt, degrade, and destroy the warfighting potential of enemy space systems, and engage The objective of the ASAT System is to achieve space control. enemy satellites in space.

if necessary, defense against enemy attack; assured access to and freedom of action in space; negation of hostile space systems; and enhancement of the operations of U.S. and Allied forces. The ASAT system will The military strategy for space supports U.S. policy objectives and Army mission requirements: deterrence and, operate across the spectrum of conflict.

ASAT is designed to be a direct ascent kinetic energy missile carrying a non-nulcear hit-to-kill warhead.

CHARACTERISTICS:

Indicative of the Soviet-developed military program of space is the development and maintenance of the world's only currently operational ASAT system, a ground-based co-orbital interceptor. Using a radar sensor and a pellet-FOREIGN COUNTERPART:

PROGRAM STATUS:

preparation for the Milestone I decision, an initial Cost and Operational Effectiveness Analysis, and a Test and

As the result of the January 1989 Defense Acquisition Board (DAB) decision, the Department of Defense (DoD) designated the Army as interim lead service for the development of a Kinetic Energy (KE) ASAT system. In

ASAT capabilities. The nuclear-armed GALOSH ABM interceptor deployed around Moscow has an inherent ASAT capability against low-altitude satellites. Some of the lasers located at the Sary Shagan Missile Test Center may be capable of conducting damaging sensitive electronic warfare against space systems.

type warhead, the interceptor can attack all current low-altitude satellites. Other Soviet-developed systems have

system and the Battle Management/ Command and Control portion of the program. A Major Decision Review

(MDR) is scheduled for FY94.

Evaluation Master Plan were developed along with Life Cycle Cost Estimates for both the Kinetic Energy weapon


U.S. Army Strategic Defense Command ATTN: ASAT JPO P.O. Box 1500 POINT OF CONTACT:

CONTRACTORS:

Rockwell International Corporation (El Segundo, California)

Huntsville, AL 35807-3801

1 Development Tech Base



GROUND BASED INTERCEPTOR (GBI)

MISSION:

GBI is designed to conduct non-nuclear intercepts of reentry vehicles (RV) dispersed from Intercontinental Ballistic Missiles (ICBM) and Submarine-Launched Ballistic Missiles (SLBM). Relying on information provided by precommit sensors and battle management components, GBI would be launched toward an incoming target or target cluster. GBI's onboard computer would then receive additional updates from the precommit sensors and control intercept course correction maneuvers during the initial stage of the flight. Once uncapped, the onboard seeker would acquire, designate and track the target, providing "end game" maneuvering of the kill vehicle to achieve a direct-impact

CHARACTERISTICS:

kill. An interceptor-to-interceptor communication system will inform following interceptors of real-time target signature designed to provide low cost per RV kill, estimated to be \$1-2 million. The GBI interceptor is designed to acquire and intercept the target in the presence of decoys and use the high kinetic energy of target impact to cause a non-nuclear data. A lethality enhancement device may be used to increase the interceptor lethal radius and negate threat The GBI is a lightweight vehicle, incorporating a sophisticated multi-band seeker and onboard data processor, countermeasures.

FOREIGN COUNTERPART:

Soviet-developed GALOSH.

PROGRAM STATUS:

lest is scheduled for early 1992. The DEM/VAL effort is seeking state-of-the-art technologies (seekers, cooled Technology Validation (FTV) and GBI Demonstration/Validation (DEM/VAL), to resolve critical interceptor issues prior to Engineering and Manufacturing Development (EMD). ERIS is demonstrating and validating tactical and technical 1991, an ERIS FTV test vehicle successfully intercepted a mock reentry vehicle in the presence of decoys. A second optics, fiber gyro, improved avionics, and high speed processors) that are mature enough to support government The GBI program consists of two phases, Exoatmospheric Reentry-vehicle Interceptor Subsystem (ERIS) Functional concepts associated with a cost-effective dormant interceptor within the strategic defense system. On January 28, baseline concepts for a Milestone II decision and provide competition for a GBI EMD.

POINT OF CONTACT:

U. S. Army Strategic Defense Command ATTN: SFAE-SD-GBI

P.O. Box 1500

Huntsville, AL 35807-3801

CONTRACTORS:

ERIS FTV: Lockheed (Prime) - (Sunnyvale, CA)

Texas Instrument (Seeker) - Dallas, TX))
Honeywell (Avionics) - (Clearwater, FL)

Kearfott Navigation Controls Co (IMU) - (Little Falls, NJ) TRW (Divert Propulsion) - (Redondo Beach, CA)


Hercules (Booster Propulsion) - (Magna, UT)
Rocket Research (Lethality Enhancement) - (Redmon, WA)

Hughes Aircraft Company (Prime) - (Canoga Park, CA)

GBIDEM/VAL:

Martin Marietta Corporation (Prime) - (Orlando, FL) Rockewll International (Prime) - (Seal Beach, CA)

Tech lices Concept DEM/VAL 840 Preduction Pleased



GROUND-BASED SURVEILLANCE AND TRACKING SYSTEMS (GSTS)

MISSION:

The GSTS will support tracking and discrimination in the midcourse phase of the Ballistic Missile Defense systems. It uses sensors launched at the appropriate time after attack warning to manage correlated data on reentry vehicles.

CHARACTERISTICS:

discrimination, and impact-point prediction of both intercontinental and submarine-launched ballistic missile reentry vehicles. The GSTS is a fixed, ground-based system and is launched into space on a The GSTS is a missile-borne, long wave infrared (LWIR) sensor system designed to provide track, suborbital trajectory to perform its functions during its exoatmospheric flight tracking.

FOREIGN COUMTERPART:

PROGRAM STATUS:

None.

A prototype GSTS is being developed to provide for technical validation experiments and test flights to support midcourse discrimination and tracking. The GSTS will be integrated with sensors for a full end-toend tracking and discrimination experiment. A validator GSTS system concept will complete demonstration and validation in the mid-1990's.

POINT OF CONTACT:

U.S. Army Strategic Defense Command ATTN: SFAE-SD-GSTS P.O. Box 1500

Huntsville, AL 35087-3801

McDonnell Douglas (Prime) - (Huntington Beach, CA)
Hughes (Sensors) - (El Segundo, CA)
TRW (Software) - (Huntsville, AL
Honeywell (Data Processor) - (Clearwater, FL)
SPARTA (Systems Engineering) - (Huntsville, AL)

CONTRACTORS:

1ech lase concept DEM/VAL sub hoduction feated

212

GROUND-BASED RADAR (GBR)

MISSION:

The Ground-Based Radar (GBR) encompasses the development of a family of radars which will support theater missile defense (TMD) and ballistic missile defense (BMD) interceptors in the acquisition, tracking and discrimination of incoming targets.

CHARACTERISTICS:

Each GBR is an X-Band phased array radar. The various radar missions to be performed will influence the physical size and configuration. Modularity and commonality of components will be emphasized during adar development to reduce development costs as well as production and support costs.

FOREIGN COUNTERPART:

the long-range Hen House radar; the Dog House radar; and the Try Adds radar. The Hen House radars operate at about 150 MHZ. The Dog House radars accept targets from the Hen House network and pass to appear to function as an early warning surveillance radar. They have very large array antennas and them on to the Try Adds radar for engagement. The Dog House also employs a large array and operates The Soviet-developed counterpart to the GBR-T seems to consist of a suite of three ABM radar systems: around 100 MHZ.

Missiles similar to the TMD-GBR. The SA-12 system consists of two radars both of which appear to be phased array radars. The acquisition radar is deployed at the brigade and battalion levels and designates The Soviet SA-12 is thought to have capability against high performance aircraft and Tactical Ballistic largets for the fire control radar. The fire control radar is an X-band radar deployed with the firing battery and appears to have autonomous search capability.

PROGRAM STATUS:

common to both the TMD and BMD versions are ongoing. Testing of the TMD DEM/VAL version is scheduled for FY94, the TMD UOEs in FY95 and the USAKA strategic defense DEM/VAL in FY96. System Engineering efforts aimed at identifying and defining modular requirements two User Operational Evaluation (UOE) radars at WSMR, and a strategic defense DEM/VAL radar at The program office has guidance from SDIO to develop the family of radars concept. Action for competitive procurement is in progress for a TMD DEM/VAL radar at White Sands Missile Range (WSMR), Kwajalein Atoll.

POINT OF CONTACT:

U.S. Army Strategic Defense Command ATTN: SFAE-SD-GBR


O. Box 1500

Huntsville, AL 35807-3801

To be determined

CONTRACTORS:

Tech base Concept DEM/VAL BIRD Preduction resided





SCIENCE and TECHNOLOGY BASE

The quality of American technology, thanks to the American worker, has enabled us to successfully deal with difficult military conditions and heth minimize precious loss of life. We have given our men and women the very best. And they deserve it."

President Bush January 1991 State of the Union Address

INTRODUCTION

The goal of the Army Technology Base is to continue providing future soldiers with the very best.

the high technology tools employed so successfully by our forces in Operation Desert Storm. Infrared and night vision technology, for example, let us own the night and saved many soldiers' lives. The Army's "Big 5" weapon systems, started two decades ago, proved themselves: the Apache and Blackhawk helicopters, Abrams tank, Patriot missile system, and Bradley Fighting Vehicle system. Operation Desert Storm also demonstrated that certain weapon system capabilities, based on superior technologies, are essential for success with minimum friendly losses on the modern day battlefield. These include: stealth, anti-tactical ballistic missiles, smart weapons/munitions, air mobility, chemical/biological detection and protection, mine/countermine, airland battle management, and exploitation of space.

Strategic plans start at the top. They contain a vision of the future, establish priorities and provide guidelines for implementation. The President's National Military Strategy (NMS) specifies that the principal focus of U. S. military planning is on deterrence and regional crisis response. The Army, in concert with the other services, is the strategic contingency force which must respond rapidly to regional crises and ensure that, if deterrence fails, these warfighting objectives can be achieved:

- Win decisively, swiftly
- Minimize casualties
- Minimize risk against future uncertainties.

Three independent categories of resources are needed for the Army to accomplish this mission throughout the next 15 years:

- * A trained force of appropriate size and composition.
- * Appropriate modernization of these forces throughout the next
- Lift assets to ensure rapid deployment of these modernized forces worldwide.

As the world security environment continues to evolve, and as the Army continues to digest the many lessons from 1991's Operation Desert Storm, the Army's modernization strategy will also continue to evolve. Some things do not change, however. A central principle of the U. S. Army has been and remains that of providing the U. S. soldier with the world's best training and equipment. This principle is at the heart of the Army's force modernization strategy. This strategy calls for the continuous improvement and modernization of Army systems being put in the hands of its soldiers.

The technology base must continue to pursue technological advances that will provide tomorrow's soldiers with both evolutionary and revolutionary improvements in fighting capability. The Army modernization strategy recognizes that increased attention must be devoted to retaining viable technology and production bases in the face of declining resources for modernization. Once lost, many of these capabilities would be difficult if not impossible to recover.

The Army Technology Base Master Plan (ATBMP) is the Army's strategic plan for the technology base. It is based on the Army leadership's vision of the future Army, as constrained by realistic funding limits. It serves as "top down" guidance from the Headquarters, Department of the Army, to all Army technology base organizations, and is a vital link between DoD technology planning and the master plans of individual Army major commands, major subordinate commands, and laboratories.

BASIC PRINCIPLES

- Satisfy our uttimate customer, the soldier, with superior technology embodied in quality equipment.
- Strengthen the process of identifying future requirements through objective technology assessments, the sponsoring of technology demonstrations.
- Explore revolutionary technologies and gapabilities. Speed their technology maturation and transition through technology demonstrations.
- Improve efficiency by stabilizing science and technology priorities and funding.
- o Improve program execution, oversight and peer review.
- o Focus on "world class" research relevant to the Army, aided by outside peer review and cooperative research and development agreements with industry and academia.
- o Attract, develop and retain quality scientists and engineers.
- Restructure the Army laboratory and Research and Development Center system to better serve the Army of this decade and the next century.
- o Meet our obligations to society through support of small and disadvantaged businesses, Historically Black Colleges and Universities/Minority Institutions (HBCU/MI), youth out-reach programs, and sponsorship of environmental research.
- Publish the Army vision, and the science and technology strategic plan in the Army Technology Base Master Plan (ATBMP).

RETURN ON INVESTMENT

The ATBMP projects the development and maturation of technologies for the Army's future systems. Indeed, it is this transferal of technology into hardware which makes the technology base a sound investment for Army resources. Over the last fifty years, Army R&D has developed and fielded a number of significant technologies.

In the future, we must be able to deploy overwhelming lethality while minimizing our losses. This requires:

- o Advanced land combat vehicles which will be lighter and more survivable due to the use of composite materials and integrated survivability technologies to be demonstrated on our Composite Armored Vehicle (CAV) technology demonstrator.
- o A product of the rotorcraft technology base, the Comanche Helicopter provides us the ability to self deploy unprecedented helicopter lethality, survivability, and versatility.
- The Advanced Anti-Tank Weapon System (AAWS-M) provides the infantryman with a revolutionary fire and forget anti-armor capability, thanks to its focal plane array technology.

Once deployed, we must see the battlefield and command and control our forces while denying the enemy this capability. This requires:

- o Tactical application of satellites for communications, location (Global Positioning System, GPS) and intelligence.
- AirLand Battle Management technologies including microelectronics, artificial intelligence, data fusion and advanced displays.

The deployed force must have air defense. This requires:

- Dactical Missile Defense.
- Multi-role helicopter air-to-air missile with offensive as well as defensive capability.

In the battle, we need to see the enemy first, shoot first, and possess overwhelming stand-off lethality. This requires:

- Advanced sensors and superior night vision technology.
 - * Brilliant weapons and smart munitions.
- Automatic target recognition.
- Positive Identification Friend or Foe (IFF).

More important than any of these systems or technologies is the soldier. To prepare the soldier for the 21st century we will:

- o Exploit advanced distributed simulation coupled to modernized training ranges, centers and schools to provide the individual soldier, units, and commanders with unprecedented training.
- o Improve chemical and biological remote detection, protection, and decontamination.
- o Provide the best medical care via continued R&D for disease prevention and combat casualty care, exploiting biotechnology and vaccine research.

Finally, we need to improve the acquisition process to reduce the cost of our systems and technologies.

- Advanced manufacturing technology and consideration of the manufacturing processes earlier in development to reduce costs.
- o Flexible, automated manufacturing for affordable quality at smaller quantities.
- Advanced technology and product improvements for operating and support cost reduction (OSCR).
- o Increased technology demonstrations and prototyping to be sure we understand the technology, improve requirement definition, and ensure we are ready for development.

CONCLUSION

The Army Technology Base Master Plan is approved by the Secretary of the Army and the Chief of Staff of the Army. This plan is provided to government, industry, and academia to convey the Army's Science and Technology vision, objectives, priorities, and corresponding investment strategy. This document is resource constrained and is Department of Army guidance to drive funding priorities and the technology base program as a whole.

As defense budgets decline and international competition in science and technology continues to rise, we must protect our technology base. Technological superiority is a significant deterrent in itself. Technological superiority is essential if we are to defeat an increasingly lethal and wider array of potential threats to U. S. interests. Our Army Technology Base Master Plan is our road map to the future. With continued support, the Army technology base will ensure our technological superiority, avoid technological surprise, and afford us revolutionary warfighting capabilities for the next century. Today's soldiers benefit from past commitments to a robust technology base. Tomorrow's soldiers deserve no less.

Index

Abrams Tank (M1)	25
_	//
Advanced Field Anillery Tactical Data System (AFATDS)	167
Air-To-Ground Missile Systems (AGMS).	6
	201
alveie (A	ט ז
And the state of t	2 6
Armored Combat Earthmover (ACE)(M-9)	121
Armored Gun System (AGS)	21
Army Data Distribution System (ADDS)	161
Army Tactical Missile System (Army TACMS)	000
Automatic Grenade Launcher (40mm)/MK193)	4
Avenuer	- 6
Risck Hask	2 5
Bradley Fighting Vehicle (BFVS)	50
Brilliant Anit-Armor Technology (BAT)	5
- 22	69
Circuit Switch and Message Switch.	181
Close Combat Tactical Trainer (CCTT)	189
Comanche	=
Combat Service Support Control System (CSSCS)	155
Communication System Control Element	177
Corps Surface-To-Air-Missile	53
Deployable Medical Systems (DEPMEDS).	145
Digital Transmission Assemblages	179
Extended Range Interceptor Technology (ERINT)	199
Family of Medium Tactical Vehicles (FMTV)	135
Family of Vehicles (FOV)(M113)	29
Forward Area Air Defense Command, Control and Intelligence (FAAD C2I)	157
Forward Area Air Defense System (FAADS)	55
73	77
Based /	207
Based	101
Based	209
Based	213
Based	61
Ground Based Surveillance and Tracking System (GSTS)	211
Guardrail	13
Hawk	67
	143
Heavy Expanded Transporter System (HETS)	131
High Endoatmospheric Defense Interceptor (HEDI)	203

High Mobility Multipurpose Wheeled Vehicle (HMMWV)	109
Howitzer , 105 mm(M119)	139
Javelin.	17
Joint Surveillance and Target Attack Hadar System (John Strand)	33
Nowa warrior Light & Special Division Interim Sensor (LSDIS)	59
Lightweight Manportable Radio Direction Finding System	105 2 4
Line of Sight Antitank (LOSAT)	147
Logistics Support Vessel	15
Maneuver Control System (MCS)	159
Military Satellite Communications (MILSATCOM)	1/5 171
MobileSubscriber Equipment (MSE)	115
	23
Multiple Launch Rocket System (MLRS)	တ္တ ဝ ထ
Multiple Purpose Individual Munition (MPIM)	173
Night Vision and Flectro-Optics	. 47
Non-Line of Sight (NLOS)	. 57
Nuclear, Biological, and Chemical Defense	2 F
Nuclear, Biological, and Chemical Heconhaisance System (MDChO)(AMSO)	133
Palletized Load System (PLS)	65
Parsonal Defense Weapon (M9 9mm)	6 9
Quick Fix	117
Recovery Vehicle (M88A1)	137
Reverse Osmosis Water Purification Unit (HOWPU)	32
Rifle (M16A2)	. 85
Sense and Destroy Armor (SADARM)	6
Single Channel Ground and Airborne Radio System (SINCGAHS)	5 = 2
Smoke and Obscuratis	191
Special Operations Aircraft (SOA)	103
Squad Automatic Weapon (SAW)	163
Standardized Integrated Command Post System (SICPS)	35
Stinger	. 19
Sungray Tactical Quiet Generators (TQG)	129
Tank Main Gun Ammunition, 120mm	205
Theater right Alitique Area Describe (Tricks)	32
Trackwolf	141
Taick & Ton	

